

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 255 RANGE 3W SEC. 9 PLSS # 340540

Date: 11/23/2021 By: X

DOUGLAS COUNTY OREGON

DATE 10-12-21

This survey consists of:
Map: _____

Corner Designation

Narrative: _____
Corner Rpt: CS67/51-17

DOUGLAS COUNTY
SURVEYOR

C 1/4 59

Previous Renewals BLM BRASS CAP
Monument(s) Found: (Condition and Source)

- ___ Condition Report
- ___ Not Found
- ___ Renewed
- ___ Unrecorded
- ___ Surveyed In

MONUMENT DETAIL

BLM Subdivision of
Section 9

T255 R3W

3 1/4" BRASS CAP 6" Above
Ground

C 1/4
59
1987

Accessories Found

Root only of 16" Hemlock S23 1/2° W 12.9 FT

C.S. File 67/51-17

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

23" X 3 FT Burnt Fir Stump 4" MAG NAIL TOP,
Center with Douglas Co. Surveyor BRASS washer
N 84° E 41.8 FT

27" X 3 FT Burnt Fir Stump 4" MAG NAIL & BRASS WASHER
Douglas CO SURVEYOR TOP & CENTER S 56° E 30.0 FT
16" Burnt Hemlock FACE with Alum Nail & BRASS
WASHER Douglas Co. Surveyor 9" MAG NAIL & Steel
WASHER Douglas Co. Surveyor IN ROOT CROWN
S 76° W 20.0 FT

20" Burnt Hemlock N 41 1/2° W 33.0 FT Alum Nail & BRASS
WASHER IN FACE 4" MAG NAIL & Steel WASHER IN ROOT CROWN

Sketch of Monument, Accessories, and General Area

Location & Comments

LAT. 43° 24' 56.48" N
LONG 123° 03' 29.76" W

Moderate North Slope
Burnt Clear Cut To
East & South Burnt
old second growth
NW Quad
AREA Burnt
9-2020

Comp. Decline. 14 1/2° E
Agency DCSD
Party Chief S. FLAUS
Note keeper
Witnesses J. LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Qumby
OREGON
JULY 14, 1978
RONALD A. QUMBY
1854

Expires: 12/31/2022

10/12/21

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bureau of Land Management Survey, Subdivision of Section by Wayne Rogers, etal - Group #1386 - Survey, June 1987 Sept. 1988 (DCSO records, Volume 48 Page 18497)

Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd. T 25 S R 3 W

3 1/4 BLM CAP PROT 6" C 1/4 S 9

NO EvinA Fir 6" dia., bears S. 48 1/2° E., 7 lks. dist., mkd. 1987 4 62 from which C 1/4 S 9 BT.

BURNED AWAY Hemlock 16" dia., bears S. 53 1/2° W., 19 1/2 lks. dist., mkd. 12 87 ROOT ONLY C 1/4 S 9 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

MM GPS COORDS CONTROL PNT. RD. SHLDR. ABV. COR.

43° 24' 56.48" N
123° 03' 29.76" W - PROCESSED COR. COORDS

PNT # 1111

43° 24' 56.95136" N
123° 03' 29.95925" W
ELEV. 454.5731 M
COR. LAT. LONG OF CONTROL PNT

NEW B.T.S

23" x 3 FT BURNED FIR STMP AS BELOW TOP CNTR. N 84° E, 418
27" x 3 FT BURNED FIR STMP 4" MAGNAIL BRASS DOUGLAS CO. SURVEYOR S 56° E, 300

16" BURNED DEAD STMPG HEMLOCK AS BELOW " 576° W, 200
20" BURNED STMPG DEAD HEMLOCK CNTR FACE ALM NAIL BRASS 4" NAIL STEEL WASH RCC, N 41 1/2° W, 330

MODERATE NORTH SLOPE, BURNED CLEARCUT TO EAST & SOUTH, BURNED OLD SECOND GROWTH NW QUAD 20

CS 67/51-17 1