

TOWNSHIP 26S RANGE 2W SEC. 3 PLSS # 500600

Date: 4-11-2022 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 12-7-21

Map: _____

Narrative: _____

Corner Rpt: CS 67/51-40

Corner Designation

Sec. Cor S3/S2
S10/S11

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

3/4" BLM BRASS CAP

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

DCSO 1927 CS 14/31

BLM Resurvey 1959 Vol 30 pg 13727

BLM Resurvey 1992-1995 Vol 51

pg 19753

DCSO 2004 CS 64/49-39

LANG 2011 M162-46

MONUMENT DETAIL

T26S R2W

S3/S2

S10/S11

1959

Accessories Found

BT'S by Irving 1927

A Burnt Sawed Fir Stump 30" X 2 1/2' N 78 1/2 E

43.4 FT

Burnt out Shell & Tail 56 1/2° E 46.0 FT

BT by person unknown

29" X 8' SAWN FIR STUMP N 65 1/4 E 29° (Rec 29°)

Fully healed SCAR

BLM bearing trees

13" Fir Burnt snag S 10 1/2° E 19° (Rec 19°)

26" X 6' SAWN FIR STUMP S 49 1/2 W 54° (Rec 53°)

unrecorded BLM BT 2018

Double Trunk maple bark scribed T26S R2W

S 3 BT on 9" southerly trunk N 48 1/2° W 22°

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

Blank lines for Monument Set description.

New Accessories

5/8" I. Rod inside 3/4" I. Pipe NORTH 45° ON Easterly Road Shoulder

Sketch of Monument, Accessories, and General Area

See Attached Sheet

LAT 43°19'42.17"N
LONG 122°54'45.74"W

Location & Comments

Corner is approx 55' South of Access Road
AREA BURNT 9-2020

Comp. Decline. 14 1/2" E
Agency _____
Party Chief S. F. HAUSE
Note keeper _____
Witnesses J. LORSONG.

REGISTERED PROFESSIONAL LAND SURVEYOR

Ronald A. Gumbay

OREGON
JULY 14, 1978
RONALD A. GUMBY
1654

Expires: 12/31/2022

CS 67/51-40 215-

T26S, R2W, 500600

12/7/21



(NO SCALE)

FOREST ACCESS RD.

NEW REF.
5/8" I.R. INSIDE 3/4" I.D. X 23" L.R.

NEW REF.
DBL TRUNK
MAPLE
N48 1/2° W, 222'

NORTH 45°

1927 B.T.
29" X 8 FT.

FIR STUMP

1927 B.T.
30" X 2 1/2'
FIR STUMP

N55 1/4° E
299'

N78 1/2° E, 63 1/2'

B.C.

S66 1/2° E, 662'

S49 1/2° W, 546'

1992-95 BLM B.T.
13" FIR SNAG
S10 1/2° E, 196'

1927 B.T.
BURNED OUT
FIR SNAG, 8' TALL

1992-95 BLM B.T.
26" X 6 FT. FIR STUMP

CS 67/51-40 3/5

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

12/7/21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28", long. 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. ^{✓ PROT 4"}

T26S R2W
 S 3 | S 2 ✓ 3 1/2 BLM CAP
 S 10 | S 11
 1959

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19753)

The cor. of secs. 2, 3, 10, & 11, monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above ground, and in a collar of stone, 3 feet dia., with brass cap mkd. from which the remains of an original bearing tree

A decayed fir stump, 63" dia., bears undetermined. 35 1/2° E., 79 lks., with fragmentary scribe marks visible on open blaze. (Record, N. 35° E.)

and the remains of BTs mkd. by Irving, in 1927 63 1/2 ✓

A sawed fir stump, 40" dia., bears N. 78 1/2° E., 96 lks., with partially healed blaze.

A fir snag, 47" dia., bears S. 66 1/2° E., 100 lks., with 8 FT TALL healed blaze. 66°

A decayed sawed fir stump, size undetermined, bears S. 62 1/2° W., 36 lks., with healed blaze. GONE

A decayed snag, size undetermined, bears N. 9 1/2° W., 102 lks., with no marks visible. 67 3/2

and a bearing tree mkd. by person(s) unknown 293 299

A fir, 22" dia. bears N. 65 1/4° E., 44 1/2 lks. with healed blaze FHSB

and new bearing trees

A fir, 7" dia. bears S. 10 1/2° E., 30 lks. mkd. T26S R2W S11 BT " 1980 196

A fir, 12" dia., bears S. 49 1/2° W., 81 1/2 lks. mkd. T26S R2W S10 BT. 53 54 5

A fir, 8" dia. bears N. 59 3/4° W. 56 1/2 lks. mkd. T26S R2W S3 BT NOT SEEN

Fd ok by Ed Monrean 4/2004 C.S. 65/49-38

6/2011: Fd. as per C.S. 65/49-38 by G. Lang, M162-46

MM GPS 12/06/21	UNRECORDED BT 3018 BLM?
TIME - 11:22	
H.I. - 1.0985M	

NEW REF
 (5/8" I.R. INSIDE 3/4" I.D. X 23" IRON PIPE)
 NORTH, 45° ON EASTLY RD. SHLD.) + DOUBLE TRNK MAPLE SURFACE SCRIBED T26S R2W S3 BT
 ON 9" STAINY TRNK N 48 1/2° W, 222'

MOSTLY BURNED AWAY 30" X 2 1/2 FT
 BURNED OUT SHELL 8 FT TALL
 GONE
 FALLEN OUT OF POS.
 SAWN BURNED STUMP 29" X 8 FT
 BURNED DEAD SNAG 13" 26" X 6 FT SAWN STUMP

CS 67151-40 4/15

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4203)

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 2, 3, 10, & 11, marked T26S S2 on NE, R2W S11 on SE, S10 on SW, S3 on NW faces, with 5 notch on S & 2 notches on E edges; from which

A fir, 12" dia. bears N.35°E., 79 lks. mkd: T26S R2W S2 BT

A fir, 12" dia., bears S.39°E., 100 lks., mkd: T26S R2W S11 BT.

A fir, 8" dia. bears S.41°W., 32 lks. mkd: T26S R2W S10 BT

A willow, 5" dia., bears N.85°W., 58 lks., mkd: T26S R2W S3 BT.

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Witnesses: R.L. Irving & Carl Messing - Dec. 5, 1927 - C.S. File 14/31

Location identified OBT N.35°E., 79 lks. which I chop out. Also rotten snag S.50°40'W., 32 lks bearing scribe marks. Set stone "x" 6" chiseled X on top W notches E face 5 notches S face, new BTs:

36" fir N.78°35'E., 96 lks.

30" fir S.66°20'E., 100 lks. OBT

10" fir S.62°30'W., 36 lks.

33" fir N.10°15'W., 102 lks.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12727)

The cor. of secs. 2, 3, 10, & 11, perpetuated & recorded by Irving, in 1927, monumented with a mound of stone, 1½ ft. base, 1 ft. high; from which the only remaining original BT:

A fir, 57" dia., bears N.35°E., 79 lks., with scribe marks T26 visible on an opened blaze.

and County Surveyor's BTs

A fir, 36" dia., bears N.78½°E., 96 lks., with a healed blaze.

A fir, 45" dia., bears S.66½°E., 100 lks. bark scribed T26S R2W S11 CS BT.

A fir, 17" dia., bears S.62½°W., 36 lks., with a healed blaze.

A fir, 41" dia., bears N.9½°W., 102 lks., with a healed blaze.

At the corner point

continued next page

CS 62/51-40 s/s