

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 255 RANGE 2W SEC. 20 PLSS # 240340

Date: 8/11/2022 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-10-22

Map: _____

Narrative: _____

Corner Rpt: CS 67/52-48

Corner Designation

DOUGLAS COUNTY
SURVEYOR

C 1/4 sec 20

Monument(s) Found: (Condition and Source)

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

5/8" Iron Rod 1" Above
Ground

Previous Renewals

Set by BAUGHMAN 1976
M 56-35

DeGroot 2010 CS 65/69-20

MONUMENT DETAIL

Accessories Found

BAUGHMAN BT
Mostly burnt CEDAR N 59 3/4 E 18.8 FT

DeGroot BD'S
Burnt-SAWN 17" X 1/2" TALL FIR STUMP S 16 1/2 E
21.7 FT (REC S 15 1/4 E 21.3) Set 3" PK NAIL

Top Center
5/8" Iron Rod S 63° 00' 42" W 22.28 FT PROJ

4" CAP GONE
5/8" Iron Rod N 14° 49' 22" W 21.08 FT PROJ
5" CAP GONE

New Accessories

14" X 8' TALL BURNT - SAWN D. FIRE STUMP
N 83° W 2' FT Not BLAZED or Scribed
3" PK RIGHT Side Center

116ftN / 116ftS South 2 FT

Sketch of Monument, Accessories, and General Area

Location & Comments

LAT 43° 22' 49.41" N
LONG 122° 54' 45.89" W

For sketch see attached
Sheet.

90° Curve 1/2 ROAD
EAST ± 70 FT

AREA BURNT
9-2020

Comp. Decline 14 1/2° E

Agency DCSO

Party Chief S. FIAUSE

Note keeper

Witnesses J LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2022

CS 67/52-48

214

T25S, R02W, 240340

MAY 10, 2022

G1/4 S20

2010 DE GROOT B.O.
5/8" IRON ROD

N14 3/4° W 21.1 FT.



(NO SCALE)

NEW REF.
14" X 8 FT FIR STUMP
N83° W, 26 FT.

5/8" I.R.

S63° W, 22.3'

S16 1/2° E 21.7'

2010 DE GROOT B.O.
5/8" IRON ROD

2010 DE GROOT B.T.
17" X 1/2 FT FIR STUMP

DECLINATION 14 1/2° E

CS 67/52-48

3/4

RENEWED 5/10/22

MM GRS 5/3/22
TIME - 13:00
H.L. - 2.00DM

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Glenn Baughman - For: Weyerhaeuser Co. - Jan. 1976 - M56-35

Set - 5/8" iron rod.
 A 10" W.Fir, bears N.72°W., 5.6 ft. scribed C¹/₄ S20 BT.
 A 24" Cedar, bears N.61°E., 18.5 ft. scribed C¹/₄ S20 BT.

Kris DeGroot - May 6, 2010 - C.S. File 65/69-20

Found - A 5/8" iron rod by G. Baughman in 1976 per M 56-35, firmly set, projecting 1" above the ground:
 From which a bearing tree by Baughman in 1976:
 A 28" Cedar bears N.59°E., 18.8 ft with scribe marks visible on a partially healed blaze. (Record N.61°E., 18.5 ft)
 A 11" D.fir bears S.15°E., 21.3 ft scribed "C¹/₄ S20 BT"

MOSTLY BURNED AWAY
BURNED SAWN STUMP 17" x 1/2" TALL

PROT 4" A 5/8" x 30" iron rod with plastic cap stamped "BTS ENG SURV" bears S.63°0'42"W., 22.28 ft. CAP GONE
 PROT 5" A 5/8" x 30" iron rod with plastic cap stamped "BTS ENG SURV" bears N.14°19'22"W., 21.08 ft. CAP GONE

Note - All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blazed face. Bearings are measured to the center of the tree at the root crown and distances are measured to a nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed faces painted red and bearing tree signs nailed to the tree.

This corner renewal was performed by Lester L. Fanning, PLS 2664, and Scott McCurdy.

DECLINATION 14 1/2° E

NEW REF

14" x 8" TALL BURNED SAWN D.FIR STMP NOT BLZD OR SCRIB. N 83° W, 26 SET 3" PK RSC

METAL LATH SET SOUTH 2 FT.

90° CURVE IN GRAVELLED RD EAST ≈ 70 FT.

CS 67152-48
414