

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 25S RANGE 2W SEC. 20

PLSS # 300340

Date: 10/18/2022 By: JC

This survey consists of:

DOUGLAS COUNTY OREGON

DATE 10/5/22

Map: _____

Narrative: _____

Corner Rpt: CS 67/54-23

Corner Designation

DOUGLAS COUNTY
SURVEYOR

1/4 COR S20/S21

Monument(s) Found: (Condition and Source)

___ Condition report

3/4" BRASS CAP ON 2 1/2" IRON
PIPE UP 12"

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

McChesney 1957 CS 53/112-24
BLM Resurvey 1962 Vol 32 pg 13232
BLM Resurvey 2001-2002
Vol 54 pg 20932-3

MONUMENT DETAIL

1/4
S20/S21
T25S R2W
1962

Accessories Found

Original BT
Burnt - Rotted 26" x 2 FT N 89° E 8.6 FT
BLM BT
30" x 1 FT SAWN - Burnt Fir Stump N 79 1/4° E
25.1 FT
Burnt SAWN 20" x 9' D. FIR Stump N 41° W
5.1 FT ADD 3 1/2" MAG NAIL RIGHT SIDE
Center

C.S. File 67/54-23

Monument Set (Procedure and Description)

MONUMENT DETAIL

Blank lines for monument set procedure and description.

New Accessories

23" Burnt - Dead D. Fir N 18°E 23.5 FT
3 1/2" Mag Nail RIGHT SIDE CENTER

14" Burnt-Dead D. Fir N 80 1/2°E 29.4 FT
3 1/2" Mag Nail RIGHT SIDE CENTER

Sketch of Monument, Accessories, and General Area

Location & Comments

LAT 43°22' 49.53" N
LONG 122° 57' 09.58" W

Monument is
Approx 200' North
of Rock Creek
Road

AREA Burnt

9/2020
Comp. Decline. 14 1/2° E

Agency DCSD
Party Chief S. Fause
Note keeper _____
Witnesses J Loring

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2022

CS 67/54-23
2/4

10/5/22

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Now 30" x 1 ft
SAWN BURNED
STUMP

SHATTERED
BURNED STUMP

and remains of accessories mkd. by Brooks

A fir, 20" dia. bears N.79 $\frac{1}{4}$ °E. 25.1 ft. with healed blaze.

A sawed fir stump, 42" dia., bears N.64°W., 36.6 ft., with a healed blaze.

A ~~steel~~ tube, $\frac{3}{4}$ " dia., firmly set, projecting 16" above ground, bears West, 1.5 ft. and new bearing tree

A fir, 14" dia., bears N.37°W., 5.6 ft., mkd. $\frac{1}{4}$ S20 BT.

NEED REFS

23" DEAD BURNED D. FIR 3 $\frac{1}{2}$ " MAGNAIL RSC N18°E, 23 $\frac{1}{2}$ FT

14" " " " " " " N80 $\frac{1}{2}$ °E, 29 $\frac{1}{2}$ FT

20" x 9 FT BURNED SAUN D FIR STUMP - N41°W, 5 $\frac{1}{2}$ FT.
3 $\frac{1}{2}$ " MAGNAIL RSC

MONUMENT IS \approx 200' NORTH FROM ROCK CRK RD.

10/5/22

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3631-2)

Set a hemlock post 3 ft. long, 3" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S20 on W & S21 on E faces, from which
 A fir, 30" dia., bears N.89°E., 13 lks., mkd: 1/4 S21 BT.
 A fir, 15" dia., bears S.35°W., 46 lks., mkd: 1/4 S20 BT.

Glen McChesney, WEYCO - 2/28/1957 - C.S. File 53/112-24

Found - 34" Fir stump N.89°E. 8.6 ft. ADDED "W" nail & plate
 18" Fir (indefinite because tree down) S.35°W. 30.4'
 New - 40" Fir N.63°W., 32.3 ft., "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13232)

The sec. cor. of secs. 20 & 21, determined at record bearing and distance from the original bearing trees:
 A sawed fir stump, 38" dia., bears N.89°E., 13 lks., with fragmentary scribe marks visible on opened blaze.
 A down fir, 15" dia., bears S.35°W., 46 lks., with no marks remaining.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground with brass cap marked

✓
 S 20 | S 21 3 1/4" PROT 1 FT.
 T25S | R2W
 1962

from which new BTs
 A fir, 4" dia., bears N.79 1/4°E., 38 lks., mkd 1/4 S21 BT.
 A fir, 48" dia., bears N.64°W., 54 lks., mkd S20 BT, & a nail, with a "W" embossed on the head, at the base.
 A steel tube, 1/2" dia., protruding 12" above the ground, bears West, 2 lks.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCSO rec. Vol. 54 Pages 20932-3)

The 1/4 sec. cor. of secs 20 & 21, monumented with an iron post, 2 1/2" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
 from which the remains of an original bearing tree
 A decayed fir stump, 37" dia., bears N.89°E., 8.6 ft., with scribe marks 1/4 visible on partially opened blaze. continued next page ✓

NOW ALSO BURNED 26" X 2 FT.

CS 67/54-23
414