

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540700

FIND OK
12/11/19

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 2; & 35, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

3 BT'S
CUT
STUMPS
SEE BELOW

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 631)

Set gr. sec. post; from which
 A Hemlock 10" dia., bears S.27°W., 26 lks. dist.
 A Dogwood 5" dia., bears N.45°E., 34 lks. dist.

Wilford N. Haines - For: Harold Woolley - March 1957 - M 4-52

Point for corner located by proportional measurement.
 Set a 1" x 36" Iron rod at corner inscribed "Wilford N. Haines Survey Point #239", (with brass cap), from which
 30" Fir N.10°30'W., 34.9 ft.
 44" Fir stump S.01°30'W., 8.2 ft.

Tony Hostetter - For: Seneca Jones Timber Co. - July 2003 - M142-68

Found - 1" T-post w/brass cap & both BTs as described by Haines in 1957 (M4-52)

New BTs- 14" W.Fir scribed "S2 1/4 BT" bears S.51°02'E., 10.1 ft. to spike.
 14" Hemlock scribed "S35 1/4 BT" bears N.72°33'W., 9.9 ft. to spike.
 14" Hemlock scribed "S35 1/4 BT" bears N.20°14'W., 11.3 ft. to spike.

FILED

Date: 11/3/2022 By: X

This survey consists of:

Map: _____

Narrative: CS 67/54-35

Corner Rpt: Harvey Christensen - For: Seneca Jones Timber Co. - Jan. 2005

- M147-9

Found - 1" "T" rod w/ brass cap (Haines) 0.6 ft above grade.
 ✓ 16" W. Hemlock N.20°W., 12.2 ft. (11.3 ft. to Hostetter spike in root face), open face, poor scribing visible "S35 1/H BT" on Cambium layer
 ✓ 16" W.Hemlock N.72°W., 11.0 ft. (9.9 ft to Hostetter spike in root face) open face, poor scribing visible S 35 1/4 BT" on Cambium layer
 14" W.Fir, S.51°E., 11.0 ft. (10.1 ft to Hostetter spike in root face), open face, poor scribing visible "S² 1/4 BI" on Cambium layer
 New ~~STMP~~ 19" D.Fir, S.75°W., 24.4 ft. blazed & scribed "1/4 S2 BT"
 7' STMP 15" D.Fir, South, 17.4 ft. blazed scribed 1/4 S2 BT"
 ✓ 21' W.Fir, N.43°E., 40.9 ft. blazed scribed "1/4 S35 BT"

Note - Corner falls north 80 feet of gravel road.
Distance to BTs measured side center (spike)

C.S. FILE 67/54-35

DOUGLAS COUNTY SURVEYOR