

FND OK 1/16/20

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 140440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Survey by Donald Peel, LS #752 - For: Weyerhaeuser Co. - July 1989 - M 108-55

Set 2" x 42" Iron pipe with brass cap mkd. "T21S R5W C¼ S18 PLS 752 1989". Set 6 ft. steel fence post 1 ft. away.
 BTs- 9" Alder N.33½°E., 3.7 ft. bark scribed C ¼ S18 BT.
 11" Fir N.28½°W., 23.8 ft. scribed C ¼ S18 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 19, 1991 - C.S. File 64/21-8

Found - 2½" dia. brass cap on a 2" O.D. Iron pipe protrudes 9" above ground.
 9" now 9" dia. Alder with bark scribing visible "C¼ S18 BT", a "W" nail is at base, bears N.27½°E., 4.2 ft. (Rec. N.33½°E. 3.7 ft. dist. is to "W" nail.)
 11" now 13" dia. D.Fir with a partially healed double blaze, scribing visible "¼ S18", a "W" nail is at base, bears N.32°W., 24.3 ft. (Rec. N.28½°W., 23.8 ft. dist. is to "W" nail) BT is pistol butted, bearings and distances taken to plumb portion of trunk.
 New BTs- 8" dia. Alder bark scribed "C ¼ S18 CS BT", bears S.14°E., 14.6 ft.
 5" dia. D.Fir double blazed and scribed "X BT" bears S.32½°W., 6.6 ft.
 Corner is approx. 30 ft. East of C/L of Upper Smith River Rd.

FILED
 Date: 11/3/2022 By: JC
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: CS 67/54-38

**DOUGLAS COUNTY
SURVEYOR**