

FND OK 3/17/20

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27 GAS C031711A

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dan Baker - For: Weyerhaeuser Co. - 11/2008 - M158-66

Found - 2½" BLM brass cap "1950"
 44" fir, N.61°E., 52.7' - closed face.
 26" Fir S.29°E., 36.7' - closed face 1995 BT
 44" Fir S.70°W., 21.4' - closed face
 27" Fir N.49°W., 43.8' - closed face
 5 foot post alongside.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page 22627

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Lytle

A fir, 44" dia., bears N.60¼°E., 51.5 ft., with a healed blaze.

A roothole bears S.37¼°E., 66.7 ft., alongside of which is a decayed fir trunk, 23" dia., with no marks visible.

A fir, 43" dia., bears S.70¼°W., 21.8 ft., with axe mark visible on the bark.

~~A fir, 30" dia., bears N.48¼°W., 44.2 ft., with a healed blaze.~~

and the remains of a bearing tree mkd. by Rogers, not reported by Patterson and Wanless

A roothole bears S.32½°E., 19.8 ft., alongside of which is a fir trunk, 7" dia., with no marks visible.

and a bearing tree mkd. by Patterson and Wanless

A fir, 27" dia., bears S.29¾°E., 37.0 ft., with a healed blaze.

Now A
31" X 9 FT TALL
SAWN STUMP

FILED
 Date: 11/3/2022 By: JC
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: CS 67/54-41

DOUGLAS COUNTY
SURVEYOR

C.S. FILE 67/54-41

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 683)

Set post for cor. to secs. 22, 23, 26, & 27, on top of ridge, bears N. & S; from which

- A Laurel, 6" dia., bears S.10°E., 15 lks.
- A Laurel, 6" dia., bears S.47°W., 45 lks.
- A Laurel, 4" dia., bears N.39°W., 11 lks.
- A Fir, 5" dia., bears N.6½°E., 40 lks.

BLM dependent resurvey by Marvin J. Lytle, Cadastral Surveyor under Group #293 dated May 1950, surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11321)

The cor. of secs. 22, 23, 26 & 27 is determined from the remains of the orig. BTs:

- A Fir stump, badly decayed, bears N.6½°E., 40 lks., showing a blaze facing south, with axe marks but with scribe marks burned out.
- A stump hole bears S.8°E., 15 lks., (rec. S.10°E.)
- A Madrona stump hole & stool bears S.49°W., 47 lks., (rec. S.47°W., 45 lks.)
- A Madrona stump & stool bears N.39°W., 11 lks.

At the corner point

Set an iron post, 3' long, 2" dia., 29" in the ground, with brass cap marked:

T 20 S R 6 W
S 22 | S 23
S 27 | S 26
1950

from which

- A Fir, 26" dia., bears N.60¼°E., 78 lks., mkd: T20S R6W S23 BT.
- A Fir, 26" dia., bears S.37¼°E., 101 lks., mkd: T20S R6W S26 BT.
- A Fir, 20" dia., bears S.70¼°W., 33 lks., mkd: T20S R6W S27 BT.
- A Fir, 22" dia., bears N.48°45'W., 67 lks., mkd: T20S R6W S22 BT.

This corner is on top of the divide between Smith River & Siuslaw River Basins, bears NW & S.20°E.

FD OK by BLM dependent resurvey by William W. Glenn, Cadastral Surveyor under Group #441 dated May 1962, surveyed June/July 1962 - (DCSO records Vol. 27 Page(s) 11324D)

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1495, surveyed Aug. 1989 - (DCSO records Vol. 50 Page(s) 18913)

 The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 2" diam., firmly set, projecting 4" above ground, with brass cap mkd.

T 20 S R 6 W

S 22 | S 23

S 27 | S 26

1950

from which the remains of bearing trees mkd. by Lytle

A fir, 38" diam., bears N.60¼°E., 78 lks., with healed blaze.

A root hole, bears S.37¼°E., 101 lks., with a down, decayed fir alongside, 30" diam., no marks visible.

A fir, 37" diam., bears S.70¼°W., 33 lks., with healed blaze.

A fir, 25" diam., bears N.48¾°W., 67 lks., with healed blaze.

and a new bearing tree

A fir, 6" diam., bears S.32½°E., 30 lks., mkd. X BT.

The corner is located on top of ridge, bearing N. 30° W. and S.30°E.

BLM dependant resurvey by Daniel Patterson & Craig Wanless, Cadastral Surveyors, Under group #1764 dated Jan. 1995, surveyed Jan./May 1995 - (DCSO records Vol. 52 Pages 19707-8)

 The cor. of secs. 22, 23, 26 & 27, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Lytle

A fir, 39" dia., bears N.60¼ E., 78 lks., with healed blaze.

A fir, lying on ground, 28" dia., bears S.37¼ E., 101 lks. no marks visible.

A fir, 41" dia., bears S.70¼°W., 33 lks., with healed blaze.

A fir, 27" dia., bears N.48¾°W., 67 lks., with healed blaze.

and a new bearing tree

A fir, 24" dia., bears S.29¾° E., 56 lks., mkd. T20S R6W S26 BT.

continued next page