

FND OK
7/14/20

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2859)

Set a basalt stone 20x8x8" 15" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which

A fir, 20" dia., bears N.49°E., 47 lks., mkd: 1/4 S BT.

A fir, 20" dia., bears S.25°W., 19 lks., mkd: 1/4 S BT.

This 1/4 sec. cor. is on a hillside, sloping S, about 25 ft. above last creek.

BLM dependent resurvey by Wm. W. Glenn, Cadastral Surveyor & Rollin D. Aanrud, Surveying Tech, under group # 533, surveyed Oct. 1963 - (DCSO records Vol. 31 Page(s) 13143)

The 1/4 sec. cor. of secs. 5 & 8, monumented with the orig. basalt stone, 20x8x8", firmly set, 4" in the ground, marked 1/4 on north face, from which the orig. BTs:

A fir, 35" dia., bears N.49°E., 47 lks. with healed blaze.

A fir, 26" dia., bears S.25°W., 19 lks. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap marked:

T24S R1W
1/4 S 5
S 8
1963

Deposit corner stone alongside the iron post.

FILED

Date: 11-3-2022 By: X

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: CS 67/54-42

Glen McChesney, Weyerhaeuser Co. - June 1976 (received 4/21/1977) - C.S. File 58/8

DOUGLAS COUNTY SURVEYOR

Found - Orig. stone marked 1/4 alongside brass cap & 2 orig. BTs.

New - Orig. 36" fir N.50°E., 29.7 ft., added "W" nail & plate.

Orig. 26" fir S.26°W., 11.8 ft., added "W" nail & plate.

42" Fir S.81°W., 104.5 ft., with "W" nail & plate.

42" Fir N.19°W., 96.4 ft. with "W" nail & plate.

Nick Juliano, Triangle Eng. - For: Weyerhaeuser Co. - Oct. 1976 - M 62-35

Found - 2" IP with a 1963 BLM brass cap and stone mkd. 1/4.

28" Fir, N.50°E., 29.7 ft., to W. Co. nail, closed face, BLM BT.

22" Fir S.26°W., 11.8 ft. to W. Co. nail, closed face, BLM BT.

continued next page

C.S. FILE 67/54-42

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

38" Fir, S.81°W., 104.5 ft. to W. Co. nail W. Co.
R.P.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause;
Oct. 30, 1996 - C.S. File 65/9-25

Found - 3¼" dia. brass cap on a 2½" O.D. iron pipe, protrudes
4" above ground (1963 B.L.M.)
20x8x8" stone, marked "¼" is fd on top of ground
along southeasterly side of BC/IP (orig. stone)
20" now 26" dia. 5½ ft. high D.Fir stump with a
healed blaze, bears S.26°W., 13.1 ft. (brg. agrees
with renewal record. Dist. is to center of root
crown, original dist. 12.5 ft. would fit well with
a face measurement) O.B.T.
20" now 35" dia. 2 ft. high D.Fir stump with a healed
blaze, bears N.50°E., 31.0 ft. (bearing agrees with
DCSO renewal rec; dist agrees w/orig. rec) O.B.T.
42" now 42" dia. 3 ft. high D.Fir stump with
Weyerhaeuser Co. "W" nail on east side of trunk,
center of stump bears S.80°W., 104.5 ft. (rec.
going to nail is S.81°W., 104.5 ft., bearing should
be S.79°W., possibly read wrong side of compass,
distance is good) 6/76 Weyerhaeuser Co.
42" now 42" dia. D.Fir with Weyerhaeuser Co. "W" nail
on south side of trunk, center of tree bears
N.21°W., 98.2 ft. (rec. going to nail is N.19°W.,
96.4 ft. possibly read wrong side of compass, dist.
is good) 6/76 Weyerhaeuser New Accessories -
10" dia. Chinquapin, double blazed and scribed "¼ S5
CS BT" bears N.32°E., 6.3 ft.
5" dia. Pine, double blazed and scribed "¼ S8 CS BT"
bears S.58½°W., 37.2 ft. to center of root crown.
9" dia. Hemlock, double blazed and scribed "¼ S8 CS
BT" bears S.13°W., 25.9 ft. to center of straight
trunk at upper blaze. Note: Tree is a pistol butt.