

None 8/5/21

END OK 8/5/21

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor Sec 31 (SW Tsp Cor)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2460-61)

Set post cor. to Tps. 23 and 24 South, ranges 7 and 8 West.

Also cor. to secs. 31, 36, 1 and 6, from which

A Fir 22" dia., bears N.80°E., 7 lks. dist.

A Fir 26" dia., bears S.60°E., 9 lks. dist.

A Fir 16" dia., bears S.65°W., 59 lks. dist.

A Fir 14" dia., bears N.28°W., 110 lks. dist.

FILED
 Date: 11/3/2022 By: JC
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: CS 67/54-44

Corner used in GLO survey by William Whipple, **DODGLES COUNTY SURVEYOR** under Contract #622, dated June 23, 1893 - (Page 2551)

GLO survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3224-25)

The Tp. corner which is a post, 4" sq., 2 ft. above ground marked T23S S31 on NE.; R7W S6 on SE.; T24S S1 on SW.; and R8W S36 on NW. faces, with 6 notches on each edge, from which

A Fir 22" dia., bears N.80°E., 7 lks. dist. mkd. T23S R7W S31 BT.

A Fir 26" dia., bears S.60°E., 9 lks. dist. mkd. T24S R7W S6 BT.

A Fir 16" dia., bears S.65°W., 59 lks. dist. mkd. T24S R8W S1 BT.

A Fir 14" dia., bears N.28°W., 110 lks. dist., mkd. T23S R8W S36 BT.

I destroy marks on both post and trees referring to Tps. and secs. South of the cor.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 1960 - C.S. File 49/41-48

Found - Orig. 16" now 36" Fir S.65°W., 38.9 ft., previously opened, shows good scribing "T24S".

Orig. NE. and SE. trees, now rotted stumps only.

Orig. 14" now 30" Fir N.28°W., 72.6 ft., shows good scars.

Set Brass cap at cor. mkd: County Surveyors Office

	T 23 S	
R	S 36 S 31	R
8		7
W	T 24 S	W
	1960	

(Cont. Next Page)

C.S. FILE 67/54-44 1

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor Sec 31 (SW Tsp Cor)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 18" R.Fir bears N.72°E., 62.5 ft. scribed S31 T23S
R7W CS BT.
12" R.Fir bears N.63°W., 53.6 ft. scribed S36 T23S
R8W CS BT.
Found corner to be East 216 ft. from corner for secs. 6 and
1, Tsp. 24 Rgs. 7 & 8. (Rec. 215.2 ft.)

Fd. and used in BLM resurvey by C. Albert White and Donald R. Beck, Cadastral Surveyors, under Group #515, Surveyed June/Oct. 1963 - (DCSO records Vol. 32 Page(s) 13479-80)

Fd. OK, March 1982 by L. Roberts - M 91-74

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22402-3)

The orig. cor. of secs. 31 & 36, T23S Rs 7 & 8 W, established by Hutchinson in 1857, remonumented by the Douglas County Surveyors Office in 1960, bears N.89°52'34"E., 216.01 ft., monumented with an iron post, 1½" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees
A decayed fir stump, 30" dia., bears S.65°W., 38.9 ft., with illegible scribe marks visible.
A fir, 40" dia., bears N.29°W., 75.9 ft., with a healed blaze. (Record, 72.6 ft.)
and bearing tree mkd. by the Douglas County Surveyors Office, reported by White and Beck
A fir, 29" dia., bears N.72°E., 62.7 ft., with a healed double blaze.
and bearing tree mkd. by the Douglas County Surveyors Office, not reported by White and Beck
A fir, 32" dia., bears N.63°W., 53.4 ft., with a healed double blaze.

CS 67/54 - 44