

FND OK 12/06/22

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29 & 30 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1132, surveyed May/June 1983 - (DCSO records Vol. 46 Page(s) 17788-89)

The Sec. cor., perpetuated and recorded by Powell in 1967, monumented with an iron post 1 1/4" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1967, from which the remains of an original bearing tree:

A sawed Fir stump 34" dia., bears N.75°W., 49 lks. dist., with fragmentary scribe marks visible on opened blaze.

and the remains of bearing trees mkd. by Powell:

NOW 14"

A Live Oak 13" dia., bears S.81°E., 22 1/2 lks. dist., with scribe marks S R2W CS visible on partially healed double blaze. **FHDB**

GONE

A Live Oak snag 6" dia., bears N.79°W., 8 1/2 lks. dist., with scribe marks 30 S R2W S30 CS BT.

and new bearing trees:

DID NOTCHK

A Fir 4" dia., bears N.63°E., 56 lks. dist. mkd. X BT.

A Fir 15" dia., bears N.34 1/2°W., 81 lks. dist. mkd. T30S R2W S30 BT.

UNRECORDED BT A 27" D. FIR WITH HEALED BLAZE AND TAG NAILS MEASURES SOUTH, 73 FT. NOW TAGGED.

From this point, the United States Coast and Geodetic Survey Station H-500, bears S.81°27'E., 108.35 chs. dist., monumented with a brass tablet 3 1/2" dia., set in concrete block, 2 ft. sq., with top mkd. UNITED STATES COAST AND GEODETIC SURVEY H 500 1949. The coordinates of this point were determined by the Douglas Co. Surveyors Office in 1975.

RIKED

STEEL FNC. POST APRX. 3 FT EAST

FILED

Date: 12/7/2022 By: X

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: CS 67/55-14

DOUGLAS COUNTY SURVEYOR

C.S. FILE 67/55-14 2