

Lat. $43^{\circ} 28' 32.01''$

Long. $122^{\circ} 52' 31.17''$

PLSS: 700 340

DATE: 6/4/2020

CREW:

T24 - R2

PARTY CHIEF - S. J. FLAUSE

TECHNICIAN - J. A. LORSUNG

MONUMENT:

(MONUMENT FOUND) IS A REFERENCE TO TRUE COR. POSITION WHICH FALLS 20 FT., EAST IN CHIPSEALED GRAVEL ROAD). FROM THE 1966 DCSD RENEWAL, A 2 1/2" DIA. BRASS CAP ON A 1" I.D. I.P. IS MARKED AS DESCRIBED

PROJ:

FILED JAN 9 2023

8 INCHES BELOW SURFACE AND LEANING APPROX. 0 3 FT. SSW FROM PLUMB MON. RETURNED TO PLUMB AND NOW PROJECTS 4" ABOVE GROUND

1966 CHISELED "X" REFERENCE TO THIS MON. NO LONGER EXISTS.

FOUND REFERENCES:

(THESE REFERENCES ARE MEASURED FROM THE TRUE 1/4 COR. POSITION I.E. 20 FT., EAST FROM ABOVE FOUND MON.) NO O.B.T.'S REMAIN. FROM THE 1965

C.S. FILE 67/55-18

OVER

T245 R02W PLSS 700340 CONT'D

SHANER RENEWAL A 60" DIA.
4⁺ FOOT TALL D. FIR STUMP; BEARS
S 82° 1/4' W, 57⁸ FT. DISTANT (AS PER
1967 BLM RECORD). OTHER SHANER
BT IN SLIDE AREA, NO EVIDENCE.
MONUMENT SET:

MEASURING 20² FT. EAST
FROM ABOVE FOUND 1966 DC SO
REFERENCE MONUMENT WE SET A
1 1/8" DIA. COPPER CAP STAMPED
"SURVEY MARK" JUST BELOW FLUSH
IN THE CHIPSEALED GRAVEL SURFACE
OF NORTH FORK ROCK CREEK RD.

NEW REFERENCES: (FOR MON. SET)

A 1 1/8" DIA. COPPER CAP STAMPED
"DOUG. CO. SURVEYOR" SET JUST
BELOW FLUSH IN ROAD SURFACE; BEARS
EAST, 12⁰⁰ FT. DISTANT.

A 1 1/8" DIA. COPPER CAP MARKED
AND SET AS ABOVE; BEARS SOUTH, 12⁰⁰ FT. DIST.

A 1 1/8" DIA. COPPER CAP STAMPED "SURVEY
MARK" SET VERTICALLY IN "V" SHAPED
CUT IN SOUTH FACING ROCK BANK; BEARS
N 43° W, 34⁵⁷ FT. DISTANT

CS 67/55-18-1- DECLINATION 14 3/12° E

AG-11-11-11

J L DARRIG (CORP) TAVANIA, MA 01924 1917
www.RiteInTheRain.com

No 312

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2875) and duplicate Pg.2763)

Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S. on W. face, from which
A Fir 20" dia., bears S.30°W., 19 lks. dist. mkd. 1/4 S BT.
A Hemlock 10" dia., bears N.20°E., 14 lks. dist. mkd. 1/4 S BT.

Fd. and used in GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2941)

Survey by Bruce A. Shaner - For: Evans Products Co. - April/May 1965 - M 29-65

Set Square stake from which a:
20" D.Fir, Orig. BT, with scribes visible, bears S.30°W., 12.5 ft.
16" Hemlock, Orig. BT, with old face, bears N.20°E., 9.2 ft.
New BTs- 60" D.Fir, I scribed "1/4S S24 BT", bears S.78°W., 56.0 ft.
28" D.Fir, I scribed "1/4S S24 BT", bears S.50°W., 72.6 ft.

SEE BLM'S RECORD FOR THESE

Corner is approx. 30 ft. West of L191+65 on proposed BLM access road.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July/Aug. 1966 - C.S. File 52/42

Found - Stumps of BTs as recorded by Shaner.
No trace of original BTs.
Corner falls in approx. center of new Rock Creek Access Road.
Set WITNESS CORNER 20 ft. West at bottom of vertical rock cut bank.
Set Brass cap at cor. mkd: County Surveyors Office
T24S R2W 1/4 S24 R1W
Wit. cor. 20'
East to cor.
1966
Chisel 4" "X" in rock face, N.1°W., 12.0 ft.
No trees available to West. This Wit. Cor. lies on W. side of road.

(Cont. Next Page)

6/4/20

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #634 Surveyed, May 1967 - (DCSO records Vol. 34 Page(s) 14171-72)

(Corner Report Only)

The 1/4 sec. cor., perpetuated and recorded by Shaner in 1965, at record bearing and distance from the original bearing trees, which are no longer in existence due to road construction, and again perpetuated and recorded by the DCSO in 1966, from the bearing trees mkd. by Shaner: ~~74 58~~

GONE SLIDE IN AREA
- A sawed Fir stump 28" dia., bears S.50°W., 113 lks. dist., with scribe marks 1/4 S24 BT visible on partially healed blaze. (Shaner record, 110 lks.)

NOW 60" x 4" TALL
A sawed Fir stump 60" dia., bears S.82 1/4°W., 87 1/2 lks. dist., with scribe marks 1/4 S24 BT visible on partially healed blaze. (Shaner record, S.78°W., 85 lks.)

The true corner point falls in the center of the spur of Rock Creek Road where it is impracticable to establish a permanent monument. In 1966, the DCSO established and recorded a Witness Corner, which bears West, 0.303 chs., dist., monumented with an iron post 1" dia., protruding 5" above ground, firmly set, with brass cap as mkd. in 1966. From which an accessory mkd. in 1966:

A cross chiseled on an exposed rock face, bears N.0 1/4°W., 12 = 18 1/2 lks. dist.

Witness Corner is located at the base of a vertical rock cut bank at the W. edge of the spur of Rock Creek Road.

LEAVING SSW 13 FT WE RETURN TO PLUMB

NOW BROKEN AWAY NO EVID.

SEAL COATED NORTH FORK ROCK CRK RD

582°W TREE IS RESET MON 20' EAST 1 1/8" COPPER CAP "SURVEY MARK"

573°W, 38 FT, FROM BC

TWO REF: "BOUG, CO, SURVOR"

550°W TREE IS

EAST 12' AND SOUTH 12'

37°46' W, 60 FT FROM BC

NEW BO'S

COPPER N43°W 34 52 "SURVEY MARK" ON SOUTH NORTH FACE, V" SHIMMED CUT IN ROCK FACE