

MM GPS POSITION ~~143~~ 43° 14' 33.69" N 123° 01' 11.60" W

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs 2 & 11

1/2023

Lat -  
Long  
only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4970)

-----

Set post for 1/4 sec. cor. from which  
 A W.Oak, 18" dia., bears S.8°W., 138 lks.  
 A W.Oak, 12" dia., bears N.70°E., 100 lks.  
 (Above cor. is in a small prairie)

F.C. Frear - J Wolford - Sept. 27, 1943 - No ref. fd. only hand written in "Old" cor. Book page 83

-----

Remarked old W.Oak 24" dia., S.8°W., 91.1 ft. fd. old blaze & checked into Old Cavite Creek Rd BTs.  
 Set 3/4"x36" iron bar & rock mound from which  
 A Cedar 30" dia. bears S.37 1/2°E., 26.3 ft.  
 A W.Oak 16" dia., bears S.30 1/2°W., 37.5 ft.  
 Note - Notes on this corner being reestablished fd by Ben B Irving Jan 6, 1945 being used as book mark. BBI

F. C. Frear, Co. Engineer - Wm. Paulen, Garrett, Skelton, etal - March 3, 1955 - C.S. File 46/86

-----

Set - 2 new witness trees as follows:  
 12" Fir N.35°E., 86.7 ft. (To be cut for rd purposes)  
 14" Cedar S.89°E., 64.5 ft.  
 3/4" iron pin still in place.  
 New - 10" W.O. S.8 1/4°W., 119.0 ft. - May 23, 1955 See CS 46/86

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12425)

-----

The 1/4 sec. cor. of secs. 2 & 11, perpetuated & recorded by Frear, in 1943 and 1955, at record bearing and distance from the original SW BT, which is no longer in existence, monumented with an iron pipe, 3/4" dia., firmly set, 8" above ground, from which the locally established BTs, as follows:  
 A cedar, 14" dia., bears S.86°E., 98 lks., with scribe marks 1/4 cor. sec 2 BT visible on opened blaze.  
 A W.Oak, 10" dia., bears S.8 1/4°W., 180 lks. with scribe marks S11 BT visible on a partially opened blaze.

At the corner point  
 Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd.  
 T27S R3W  
 1/4 S 2  
 S 11  
 1958

continued next page

CS 67/55-21