

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 26S RANGE 2W SEC. 19 PLSS # 140300

Date: 2/14/2023 By: SC
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 1-11-23

Map: _____

Narrative: _____
Corner Rpt CS 67/55-22

DOUGLAS COUNTY
SURVEYOR

Corner Designation

1/4 COR 19/30

Monument(s) Found: (Condition and Source)

DCSO BRASS CAP ON 1 1/4"
IRON PIPE SET FLUSH ORIG.
STONE ON N. EDGE OF B.C

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

DCSO 1967 CS 54/40-19

DCSO 1975 CS 57/17-21

BLM RESURVEY 2011 Vol

5B pg 22936

MONUMENT DETAIL

COUNTY SURVEYORS
OFFICE
T26S R2W
1/4 S19
S26
1967

Accessories Found

12" X 2 1/2 FT MADROVE STUMP S10³14°W 21.0 FT
BURNED OUT.

A SINGED 22" CEDAR N51 1/4°W 10.3 FT (REC 11.1)
HEXED BLAZE ADD 3 1/2" MAG NAIL RIGHT
SIDE CENTER

C.S. File 67/55-22

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

30" S. Pine N 53° E 5.0 FT 3 1/2" MAG Nail
RIGHT Side Center

31" D. Fir S 78° W 31.5 FT 3 1/2" MAG Nail
RIGHT Side Center

Aluminum Lath 0.5 FT ENE

Sketch of Monument, Accessories, and General Area

Location & Comments

LAT. 43° 17' 09.23" N
LONG 122° 58' 51.00" W

MONUMENT IS AT TOP
OF STEEP N.W. Slope
ON A ENE RUNNING
RIDGE 100' ± FT.
N. OF GRADY ROAD
AREA BURNED
9/2020

Comp. Decline. 14 1/2° E
Agency DCSD
Party Chief S. FRAUSE
Note keeper
Witnesses J. LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/55-22

24

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Note - Corner lies on top of ridge south easterly of old clearcut head of stream

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22936)

The 1/4 sec. cor. of secs. 19 and 30, perpetuated by the Douglas County Surveyor's Office in 1967 and 1975, monumented with an iron post, 1 1/4" dia., firmly set, flush with ground surface, (buried alongside of which I unearth and rebury the original basalt stone, 6x9x14" with marks 1/4 visible) with brass cap (properly) mkd. STONE ON NORTH EDGE OF B.L., from which bearing trees mkd. by person(s) unknown, recorded by the Douglas County Surveyor's Office in 1967

12" x 2 1/2" FT. BURNED OUT STUMP

A madrone, 13" dia., bears S.10 3/4° W, 21.0 ft., with scribe marks 1/4 S30 visible on a weathered, partially healed blaze. BLAZE G.C.N.

and the remains of BTs mkd. by the Douglas Co Surveyor's Office in 1967

NOT GOOD

A roothole, bears S.40 1/2° W., 16.3 ft., with a partially uprooted, sawed, decayed, fir stump alongside, size indeterminate, with no marks visible.

ALIVE BUT BADLY SINGED

A cedar, 22" dia., bears N.51 1/2° W, 11.1 ft., with a healed blaze.

10 3 ADDED 3 1/2" MAG NAIL R.S.C.

and the remains of a BT mkd. by the Douglas Co Surveyor's Office in 1975

A roothole, bears S.31 3/4° W., 24.1 ft., with an uprooted, decayed fir lying alongside, 12" dia., with no marks visible.

BURNED 26.4V

NEW REFS

30" S. PINE N53°E, 50 FT. 3 1/2" MAG NAIL R.S.C.

31" D. FIR S78°W 31 1/2 FT. " " "

ALUMINUM LATH ENE, 05 FT

MONUMENT IS AT TOP OF STEEP N.W. SLOPE ON A ENE RUNNING RIDGE
MONUMENT IS ~100 FT. NORTH FROM GRAVELLED FOREST RD.

MM GPS 1/11/23
TIME - 10:20
H.I. - 2.000M

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4247)

Set a granite stone 6x9x14" 10" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which

A cedar, 18" dia., bears S.63°W., 16 lks., mkd: 1/4 S30 BT.
A hemlock, 8" dia., bears N.40°E., 11 lks., mkd: 1/4 S19 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - July 1967 - C.S. File 54/40-19

Found - Orig. corner stone 6x9x12" mkd. "1/4" on N face & firmly set.

A large stump hole bears S.63°W., 10.0 ft. & a small stump hole bears N.40°E., 7.0 ft. These holes fit location for orig. BTs.

Find OBT as follows:
10" Laurel S.15°W., 20.9 ft. approx. ring count indicates this tree mkd. 50-55 yrs ago scribed "1/4 S30 BT".

Pacing from top of ridge to East, this corner fits call good, old blazes found west.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T26S R2W
OFFICE 1/4 S 19
1967 S 30

10" Cedar N.52°W., 10.9 ft. mkd: 1/4 S19 CS BT.
10" D.Fir S.38°W., 16.6 ft. mkd: 1/4 S30 CS BT.

Note - This corner lies on top of small rounding spur sloping N. Reset stone alongside Brass cap.
Also find 9" Laurel snag, open & find "S19B" scribe & reverse bears N.89°E., 19.1 ft.

Douglas Co. Surveyors Office - Gary E. Commons - Pete L. Earle - Feb. 25, 1975 - C.S. File 57/17-21

Found - 1967 County Surveyors Brass cap properly mkd.

An orig. corner stone 6"x9"x12" with 1/4 on North face along side.

A 9" Madrone snag N.89°E., 19.1 ft. is now down and apparently rotted.

A 10" Madrone now 11" S.15°W., 20.9 ft. with scribing 1/4 S30 CS BT visible.

A 10" Cedar, now 11", N.52°W., 10.9 ft. with scribing 1/4 S19 CS BT visible.

A 10" D.Fir, now 11", S.38°W., 16.6 ft. is blown down, scribing visible.

New BT - A 12" D.Fir, S.30°E., 23.0 ft. scribed 1/4 S30 CS BT.

continued next page