

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 245 RANGE 2W SEC. 4

PLSS # 300600

Date: 2/14/2023 By: X

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: CS 67/55-30

DOUGLAS COUNTY OREGON

DATE 1-31-23

DOUGLAS COUNTY SURVEYOR

Corner Designation

Sec Cor 5/4
8/9

Monument(s) Found: (Condition and Source)

1959 BLM BRASS CAP
proj 16" IN Rough Stone
Mound

Previous Renewals

Calder 1957 CS 40/399
BLM Resurvey 1959 Vol 1 30 pg 12741-2
Hoffine 2017 CS 65/97-1
BLM Resurvey 2018-2020 Vol
59 pg 24059-60
Quimby 2020 CS 65/106-55

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

MONUMENT DETAIL

T265 R2W
55/54
58/59
1959

Accessories Found

Burnt Dead 36" FIR N 43³/₄° E 43.2 FT Healed Scar
Burnt Dead 33" FIR S 20¹/₂° E 37.3 FT " "
Burnt Dead 16" FIR S 57³/₄° W 22.4 FT " "
Badly Burnt 28" FIR Stump N 83¹/₂° E 41.9 " "

5/8" X 30" Iron Rods with yellow Plastic Cap
Stamped 1 engineering with alum post
Along side

<u>N 65° E 5.2 FT</u>	<u>S 65° E 11.9 FT</u>
<u>S 32° E 10.1 FT</u>	<u>S 54° W 5.8 FT</u>

C.S. File 67/55-30

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

Sketch of Monument, Accessories, and General Area

Location & Comments

Lat 43°19'43.09" N
 Long 122°57'04.25" W

AREA BADLY
 BURNT 9-2020

Comp. Decline. 15 1/2° E
 Agency DCSO
 Party Chief S. F. HAUSE
 Note keeper
 Witnesses J. LOISUNG

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

OREGON
 JULY 14, 1978
 RONALD A. QUIMBY
 1654

EXPIRES: 12/31/2024

CS 67/55-30
 214

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 17" dia., bears S.42½°E., 57½ lks., mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc. mkd. Registered Engineer No. 2149.

A fir, 8", dia., bears S.9¼°W., 19½ lks., mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc mkd. Registered Engineer No. 2149.

A fir, 27" diam., bears N.55¼°W., 57 lks., mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc. mkd. Registered Engineer No. 2149.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

T26S R2W

S 5 | S 4

S 8 | S 9

1959

from which new BTs

A fir, 32" dia., bears N.43¾°E., 65½ lks., mkd: T26S R2W S4 BT.

A fir, 29" dia., bears S.20½°E., 56½ lks., mkd: T26S R2W S9 BT.

A fir, 9" dia., bears S.57¼°W., 34 lks mkd: T26S R2W S8 BT

A fir, 21" dia., bears N.83½°W., 63½ lks., mkd: T26S R2W S5 BT.

Reset the wooden stake alongside the iron post.

Ken Hoffine - For: Lone Rock - Aug. 2017 - C.S. File 65/97-1

Found - 1959 BLM brass cap 36" fir bears N.43¾°E., 43.2 ft. as per record healed face and tag.

33" Fir bears S.20½°E., 37.3 ft. as per record healed face and tag.

16" Fir bears S.57¼°W., 22.4 ft. as per record healed face and tag.

28" Fir bears N.83½°E., 41.9 ft. as per record healed face and tag.

Corner lies on southwest slope and southwesterly of large barren rock area.

FOUND OK 1/31/23

Ron Quimby - Crew: N. Fromdahl, L. Heddens & J. Ogden - 10/2020 - C.S. File 65/106-55

Found - 1959 BLM brass cap (properly marked) - PROT. 16" IN ROUGH

BURNED DEAD

36" burnt fir N.43¾°E., 43.2 healed scar

MOUND OF STONE

" "

33" burnt fir S.20½°E., 37.3 healed scar

" "

16" burnt fir S.57¼°W., 22.4 healed scar

BADLY

BURNED

28" burnt stump N.83½°E., 41.9 healed scar

continued next page

CS 67/55-30

2

314

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

FWD. OK

New - 5/8"x30" I.Rods with yellow plastic cap stamped "ie ENGINEERING" with post alongside:

N.65°E., 5.2 ft.	S.65°E., 11.9 ft.
S.32°E., 10.1 ft.	S.54°W., 5.8 ft.

Note- Area badly burnt 9/2020
Compass decl. 15½°E.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24059-60)

DONE BEFORE I.E. RENEWAL

The cor. of secs. 4, 5, 8, and 9, reported by Zirpel, Jr., and Glenn in 1959, monumented with an iron post, 2½" dia., firmly set, projecting 18" above ground, in a mound of stone, 3 ft. base, to the top, with a brass cap (properly) mkd. from which the remains of the bearing trees reported by Zirpel, Jr., and Glenn

- A decayed fir stump, 39" dia., bears N.16½°E., 28.2 ft., with a healed blaze. (Record, 30.4 ft.)
- A decayed fir stump, 31" dia., bears N.43¾°E., 43.2 ft., with scribe marks T26S R2W S4 visible on open blaze.
- A fir, 27" dia. bears S.42½°E., 36.6 ft., with a healed blaze. (Record, 38.0 ft.)
- A fir, 37" dia., bears S.20½°E., 37.3 ft., with a healed blaze.
- A fir, 20" dia., bears S.9¼°W., 12.9 ft., no marks visible.
- A fir, 18" dia., bears S.57¼°W., 22.4 ft., with a healed double blaze.
- A fir, 30" dia., bears N.83½°W., 41.9 ft., with a healed blaze.

and a new bearing tree

A madrone, 12" dia., bears N.61¼°E., 6.9 ft., mkd. T26S R2W S4 BT on bark.

NAD 1983 (2011)

Latitude: 43°19'43.09" N. Longitude: 122°57'04.25" W.

*CS 62/55-30
4/4*