

MINI GPS 43.81331
123.70396

MM GPS

9/1/21

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25, T20-9 *FMD OK*

Alias _____	Description _____	<i>Reported as Fd OK see pg 3</i>
Alias _____	Description _____	
Alias _____	Description _____	
Alias _____	Description _____	

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 353)

At point of intersection, I set a Cedar post, for closing corner to secs. 24 & 25, 4 ft. long, 4" sq., 24" in the ground, marked CC T20S S24 on N.; S25 on S.; CC R9W on W. faces, with 2 notches on S. and 4 notches on N. faces; from which

- An Alder 24" dia., bears S.80°E., 30 lks. dist. mkd. T20S R9W S24 & 25 CC BT.
- An Alder 18" dia., bears N.46°W., 60 lks. dist. mkd. T20S R9W S24 BT.
- A Maple 48" dia., bears S.64°W., 106 lks. dist. mkd. T20S R9W S25 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12468)

Point for the closing cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground with brass cap mkd:

T 20 S		T 20 S
CC S 24		S 19
S 25		R 9 W
		R 8 W
		1954

FILED 23
 Date: 3/21/20 By: X
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: CS 67/55-48

- from which
- A Maple 25" dia., bears N.25°W., 33 lks. dist. mkd. R9W S24 CC BT.
 - A Maple 105" dia., bears West, 172 lks. dist. mkd. T20S R9W S25 CC BT.
- (The ¼ sec. cor; sec. 19, T20S R8W bears N.0°42'E., 0.78 chs.)

DOUGLAS COUNTY SURVEYOR

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16711-12)

The closing cor., monumented with an iron post 2" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1954,

- from which the remains of the bearing trees mkd. in 1954:
- A root hole bears N.25°W., 33 lks. dist. with a down Maple alongside, 18" dia., with fragmentary scribe marks visible on decayed blaze.

(Cont. Next Page)

B.B. FILE 67/55-48

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25, T20-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees:

A Maple 25" dia., bears S.22°W., 153 lks. dist. mkd. T20S R9W S25 CC BT.

A Maple 39" dia., bears N.74°W., 253½ lks. dist. mkd. T20S R9W S24 CC BT.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 (added 12/31/2014) - (DCSO records Vol. 58 Page(s) 23080)

The closing cor. of secs. 24 & 25, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of a BT mkd by Glenn, et. al., in 1967

A Roothole bears S.22°W., 101.0 ft. with a down decayed maple, 26" dia., lying alongside, no marks visible.

and new BTs

An alder, 16" dia., bears S.72¼°W., 31.9 ft., mkd: T20S R9W S25 CC BT on bark, with a Mag nail on the left side center.

A fir, 17" dia., bears N.70¼°W., 59.1 ft., mkd: T20S R9W S24 CC BT.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22967)

The closing cor. of secs. 24 and 25, on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with a brass cap mkd. and accessories as described in the 2006-09 official survey by Forkner.

BLM retracement by Joseph M. Mannix, Cadastral Surveyor under Group No. 2500, Admin. file No. 1306, surveyed May 2013 - (DCSO records Vol. 58 Page(s) 23070 & **Survey plat 2014-1**)

The closing cor. of secs. 24 & 25, on the E. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 10 ins, above ground, with a brass cap mkd.

from which the bearing trees mkd. by Forkner in 2006-09

An alder, 20" dia., bears S.72¼°W., 31.9 ft., with scribe marks T20S R9W S25 CC BT visible on bark.

A fir, 22" dia., bears N.70¼°W., 59.1 ft., with a healed blaze.

continued next page

C.S. FILE 67/552-48

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION C C for Secs 24 & 25, T20-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From the corner
S.89°59'04"W., 90 ft., Smith River Road, asphalt surface,
20 ft. wide, bears N.50°E. and S.50°W.

~~FIND AS DESCRIBED 2013 BLM RETRACEMENT~~

ADD BLM TIE TO W¹/₄ 19, T20S, R8W
N 0°34'18"E, 5135 FT.

C.S. FILE 67/55-48₃

22967

**Subdivision of Section 19,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

A fir, 20 ins. diam., bears N. 34 1/4° E., 11.9 ft. dist., mkd. C1/4 S19 BT.

A fir, 17 ins. diam., bears S. 15 1/4° E., 5.1 ft. dist., mkd. C1/4 S19 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner falls on a W. slope.

Point for the center W 1/16 sec. cor. of sec. 19.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16
C ——— C
S 19
2011

from which

A fir, 12 ins. diam., bears S. 6 1/2° E., 1.4 ft. dist., mkd. X BT.

A fir, 16 ins. diam., bears N. 13 3/4° W., 32.1 ft. dist., mkd. CW1/16 S19 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner falls on a W. slope.

From the corner

N., 25 ft. dist., creek, 2 ft. wide, course S. 20° W.

W., 315 ft. dist., creek, 3 ft. wide, course N. 60° W.

The 1/4 sec. cor. of secs. 19 only, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd. and accessories as described in the 2005 official survey by Graham.

From this cor., the closing cor. of secs. 24 and 25, on the W. bdy. of the Tp., bears S. 0° 34' 18" W., 51.35 ft. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd. and accessories as described in the 2006-09 official survey by Forkner.

**Subdivision of Section 28,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

Point for the center 1/4 sec. cor. of sec. 28, at intersection of the N. and S. and the E. and W. center lines.

4/4

C.S. FILE 127 / 55 - 48