

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 255 RANGE 3W SEC. 25 PLSS # 640240

Date: 3/21/2023 By: JC
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 3-6-23

Map: _____

Narrative: _____

Corner Rpt: CS 67/55-59

Corner Designation

C 1/4 S25

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

NONE

Previous Renewals

CORNER set By DCSD 1948

CS 39/170

DCSD 1966 CS 54/27-170

MONUMENT DETAIL

Accessories Found

BURNED SAWN 21" X 6' Hemlock stump N 42° E
18.6 FT Add 3 1/2" MAG Nail RIGHT Side Center

BURNED SAWN 26' X 7' Hemlock stump S 46° E
29.4 FT Add 3 1/2" MAG Nail RIGHT Side Center

C.S. File 67/55-59

RENEWAL

Monument Set (Procedure and Description)

A 3 1/4" Alum. CAP ON 2 1/2"
Alum. Pipe AT DISTANCE -
DISTANCE INTERSECTION OF
FOUND BEARING TREES
CAP IS 3" ABOVE GROUND

MONUMENT DETAIL

Douglas County
T255 R3W
C 1/4 • S25
2023
Surveyor OFFICE

New Accessories

5/8" X 30" I. Rod S34°E 16.0 FT WITH
DCSO yellow PLASTIC CAP FLUSH WITH
GROUND

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS COORDINATE SYSTEM
COTTAGE GROVE - CANYONVILLE
ZONE

N 193679.450
E 252546.975

MONUMENT IS IN
RECENT CLEAR CUT ON
GENTLE EAST SLOPE

AREA BURNT

9/2020

Comp. Decline 14 1/2° E

Agency DCSO

Party Chief S. FRANKS

Note keeper

Witnesses J. LORNING

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/55-59
2/3

3/6/23

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 640240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

B. B. Irving, County Surveyors Office - For: Douglas County Lumber Co. - May-June 1948 - C.S. File 39/170

BC MONUMENT GONE DUE TO LOGGING

BURNED, SAWN 21" X 6 FT. STUMP

BURNED, SAWN 26" X 7 FT. STUMP

Set - 1" G.I.P. with brass cap mkd. County Surveyors Off
 C 1/4 S25 T25S R3W
 BTs - 8" Hemlock N.42°E, 18.6 ft. mkd. C 1/4 S25 CS BT.
 8" Hemlock S.46°E, 24.4 ft. mkd. C 1/4 S25 CS BT.

Cor. found OK, July 1966 - VRT, Co. Surv. Office - C.S. File 54/27-170

RESET NEW BC AT DISTANCE, DISTANCE INTERSECT FROM FOUND BTs

3/4" ALUMINUM CAP ON A 2 1/2" O.D. ALUMINUM PIPE. CAP IS STAMPED

" DOUGLAS COUNTY "

T25S R3W

C 1/4 • S25

2023

SURVEYOR'S OFFICE

GET MONUMENT NOW PROT. 3 INS. ABOVE GROUND

NEW REF.

5/8" x 30" I.R. / DC50 PISTC. SET TOP FLUSH WITH GROUND; BEARS S34°E, 16 FT.
CAP

MONUMENT IS IN RECENT LARGE CLEARCUT ON A GENTLE EAST SLOPE.

OORS CANYONVILLE COTTAGE GROVE COORDS

193679.450 N

252546.975 E

CS 67/59

3/3