

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 255 RANGE 2W SEC. 22 PLSS # 500300

Date: 4/26/2023 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 4-10-23

Map: _____

Narrative: _____

Corner Rpt: CS 67/56-1

Corner Designation

DOUGLAS COUNTY
SURVEYOR

See Cor

22 | 23
27 | 26

Monument(s) Found: (Condition and Source)

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

DCSO BRASS CAP
Severly Bent Reference
& Replace

Previous Renewals

DCSO 1958 CS 49/102-2

McChesney 1958 CS 53/112-31

Juliano 1973 M 51-27

BLM Resurvey 1972-1975 Vol 36 pg 15119

DCSO 1990 CS 64/10-9

BLM Resurvey 2001-2002 Vol 54 pg 20920-1

BLM Resurvey 2014-2015 Vol 58 pg 23334-5

MONUMENT DETAIL

County Surveyors
OFFICE
T255 R2W
522 | 523
527 | 526
1958

Accessories Found

58" X 5 FT Burned out inside pine stump N 39 1/2° E
41.9 FT Healed BLAZE

30" X 4 FT Burned Fir stump S 26° E 21.8 FT
(Rec S 23° E) Healed BLAZE ADD 3 1/2" MAG NAIL
Top Center

Burned 32" X 3 FT Fir stump N 42 1/2° W 35.2 FT
Rec 37.1 FT Healed BLAZE ADD 3 1/2" MAG NAIL
Top Center

Burned Dead 18" Double Trunk Hemlock S 21 1/4° W
24.7 FT (Rec 24.4 FT) Healed Double BLAZE
ADD 3 1/2" MAG NAIL RIGHT Side Center

Burned Dead 13" Hemlock N 40 3/4° W 8.8 FT (Rec
8.7 FT ADD 3 1/2" MAG NAIL RIGHT Side Center

C.S. File 67/56-1

Monument Set (Procedure and Description)

MONUMENT DETAIL

3 1/2" diam Alum. Cap on
2" x 32" I. P up 8"

Douglas County
Surveyor

T 255 R 2W

S 22 | S 23

S 27 | S 26

2023

New Accessories

22" x 1 FT Solid Fir Stump S 73° E 48.6 FT
3 1/2" MAG NAIL Top Center

Sketch of Monument, Accessories, and General Area

Location & Comments

LAT 43° 22' 23.20" N
LONG 122° 54' 50.18" W

CORNER on Steep
West Slope 55° E
Feet west of
GRAVEL ROAD

AREA Burnt
9-2020

Comp. Decline. 14 1/2° E

Agency DCSO

Party Chief S. F. AUSE

Note keeper

Witnesses J. LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/56-1

RENEWED 4/10/23

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor Secs 22, 23, 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCSO rec. Vol. 54 Page(s) 20920-1)

The cor. of secs 22, 23, 26, & 27, perpetuated by Byron, in 1958, further perpetuated by Smith, Flause and Franssen, in 1990, monumented with an iron post, 1 1/2" dia., firmly set, projecting 15" above ground, in a mound of earth, 2 ft. dia., 6" high, with brass cap (properly) mkd.

from which the remains of the original bearing trees

- A sawed pine stump with tin cap, 67" dia., bears N.39 1/2° E., 41.9 ft., with healed blaze. (Record, N.37° E., 38.9 ft)
- A sawed fir stump, 31" dia., bears S.23° E., 21.8 ft., with healed blaze. (Record, S.25° E., 23.1 ft.)
- A sawed fir stump, 39" dia., bears N.42 1/4° W., 37.1 ft., with healed blaze. (Record, N.44° W., 38.9 ft.)

and bearing tree mkd. by Byron

- A hemlock, 10" dia., bears S.83° W., 22.3 ft., with healed double blaze.

and bearing trees mkd. by Smith, Flause and Franssen

- A double trunk hemlock, 14" dia., bears S.21 1/4° W., 24.4 ft., with healed double blaze.

- A hemlock, 12" dia bears N.40 3/4° W., 8.1 ft with fragmentary scribe marks visible on partially healed blaze.

NEW CAP MARKED
"DOUGLAS COUNTY SURVEYOR"
T255 R2W
S22 S23
S24 S26
2023
3 1/2 Alum.
NEW 2 3/8" CAP / 2" 10 X 32" ALUM.
PROT. 8"

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749, surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23334-5)

The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 1 1/4" dia., firmly set, projecting 12" above the ground, with a brass cap (properly) mkd.

from which the remains of the original bearing trees

- A pine stump, 52" dia., bears N.39 1/4° E., 41.9 ft., with a healed blaze and tin cap.
- A fir stump, 32" dia., bears S. 23° E., 21.8 ft., with a healed blaze.
- A fir stump, 40" dia., bears N.42 1/4° W., 37.1 ft., with a healed blaze.

and BT mkd by Byron, in 1958, reported by Skeesick in 2001-02

- A hemlock, 11" dia., bears S.83° W., 22.3 ft., with a healed double blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1990, reported by Skeesick

- A double trunk schoolmarm hemlock, 17" dia., bears S.21 1/4° W., 24.4 ft with a healed double blaze.

- A hemlock, 13" dia., bears N.40 3/4° W., 8.1 ft., with a healed blaze (Record, 8.1 ft.)

DECLINATION 14" 2° E

NEW REF.

CS 67/56-1 3/3

22" X 1 FT. BURNED BUT SOLID FIR STUMP 3 1/2" MAG NAIL TOP CNTR, S 73° E, 48 6

MON. ON STEEP WEST SLOPE ~ 55 WEST OF GRAVELLED RD.

58" X 5 FT.
BURNED OUT INSIDE
BURNED STUMP 30" X 4 FT.
VERY BURNED STUMPA
32" X 3 FT.
FALLEN NO POSITION

BURNED DEAD 18"
BURNED DEAD 13"

CAP/PINE SEVERELY BENT, REF. PLUS 3 POS AT REF. POS SET
FALLEN OFF
352
82

ADD 3 1/2" MAG NAIL RSC