

TOWNSHIP 253 RANGE 1W SEC. 7

PLSS # 200540 Date: 6/5/2023 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-8-23

Map: _____

Narrative: _____

Corner Rpt: CS 67/56-14

Corner Designation

14 7/B

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

___ Condition report

UNRECORDED 3 1/2" GLO SURVEY
Drill Cap Set NEAR Center-South
Edge OF CORNER Stone

___ Not Found

Renewed

___ Unrecorded

Previous Renewals

___ Surveyed In

DCSD 1960 CS 52/30-1

DCSD 1966 CS 52/30-23

MONUMENT DETAIL

Accessories Found

Burned - DEAD 30" Hemlock S86°W 10.0 FT
Fully Healed Single BLAZE ADD 3 1/2" MAG
NAIL RIGHT Side Center

Burnt- DEAD 28" Hemlock N6°W 13.1 FT
Fully Healed Single BLAZE ADD 3 1/2" MAG
NAIL RIGHT Side Center

Unrecorded 24" D. Fir S3E 23.0 FT (Per
Tag) Tree BURNED- DEAD ADD 3 1/2" MAG
NAIL Rt Side Center

A Galv. Metal Lath is South 1ft I

C.S. File 67/56-14

New Accessories

Burnt-Dead 14" D. Fir 522°E 19.6 FT
3 1/2" MAG NAIL RIGHT side Center
Tree Not BLAZED or Scribed

Sketch of Monument, Accessories, and General Area

Location & Comments

Lat 43° 24' 55.70" N
Long 122° 50' 29.48" W

COR. IS APPROX 300'
NORTH OF GRAVEL
ROAD

Corner lies 50ft (rec 40') west of
Small Creek, course S. 15° W

AREA BURNED
9-2020

Comp. Decline. 14 1/2° E
Agency DCSO
Party Chief S. KAUSE
Note keeper
Witnesses J LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/56-14

M M GPS 5/8/23
TIME - 12:00
RANGE 01

RENEWED 5/8/23

TOWNSHIP 25 11 - 21000 M RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3566)

The point for 1/4 sec. cor., falls on a basalt stone, in place, 24x12x7" above ground which I mark, at the exact cor. point, with a cross (+) and 1/4 W of cross for 1/4 sec. cor. from which
A cedar, 14" dia., bears S.77 1/2°E., 28 lks., mkd: 1/4 S8 BT.
A fir, 15" dia., bears West, 40 lks., mkd: 1/4 S7 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - Clete Putnam - July 13, 1960 - C.S. File 52/30-1

Found - Basalt stone as recorded
Orig. SE BT shows good scar & is in good condition.
Orig. West BT is down, shows good scar.
New BT - 15" Hemlock S.86°W., 10.0 ft. scribed 1/4 S7 CS BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Oct. 1966 - C.S. File 52/30-23

Found - Orig. Basalt Stone 24x12x7" above ground mkd' "1/4 X" on top, very solid.

15" now 16" Hemlock S.86°W., 10.0 ft., shows ~~1/4 S7 CS BT~~ on unhealed blaze. **FHSB ADD 3 1/2" MAG NAIL R.S.C.**
Both Orig. BTs destroyed by logging. Because of size & rigidity of Stone, we do not set Brass Cap.

New BTs - 60" Fir Stump N.65°E. 25.5 ft. mkd. 1/4 S8 CS BT.
19" Hemlock N.6°W., 13.1 ft., mkd. S7 CS BT. **FHSB ADD 3 1/2" MAG NAIL R.S.C.**
Note - Corner lies (40 ft.) west of small creek course S.15°W (50 FT) COR. IS 300 FT. NORTH FROM GRAVEL RD.

ALSO FOUND UNRECORDED (GLO, BLM?) BT. **ADD 3 1/2" MAG NAIL R.S.C.**

A 24" D. FIR WITH FHSB, TAG BEARING AND DIST. (FROM CAP) S03°E, 23 1/2 FT. **23 1/2 FT.**
BURNED DEAD

NEW REF.

BURNED DEAD 14" D. FIR, 3 1/2" MAG NAIL R.S.C., TREE BEARS S22°E, 196

FOUND UNRECORDED GLO SURVEY 1 3/2" BRASS DRILL CAP SET NEAR CENTER SOUTH EDGE OF CORNER STONE
A GALV. METAL LATH IS ≈ SOUTH 1 FT.

CS 67/56-14
3/3

43 415437 122.841655

BURNED DEAD 32"

NO EVID.

BURNED DEAD 28"