

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 555 RANGE 2W SEC. 12

PLSS # 640500 Date: 6/5/2023 By: X  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-9-23

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_  
Corner Rpt: CS 67/56-15

DOUGLAS COUNTY  
SURVEYOR

Corner Designation

$\frac{1}{4}$   $\frac{S12}{S13}$

Monument(s) Found: (Condition and Source)

3/4" BLM BRASS CAP  
BURIED 8"

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

EVANS 1949 CS 43/158  
BLM RESURVEY 1962 Vol 32 pg 13220  
DCSO 1967 CS 54/27-118  
Johnstone 1982 CS 58/188-6  
Ness 1995 M 123-3A&B  
BLM RESURVEY 2001-2002  
Vol 54 pg 20917

MONUMENT DETAIL

$\frac{1}{4}$   $\frac{S12}{S13}$   
 T25S R2W  
 1962

Accessories Found

BURNED - Hollow 30" X 6 FT Cedar Stump  
S 57 1/4 W 50.8 FT ADD 3 1/2" MAG NAIL RIGHT  
Side Center

BURNED - Rotted 11" X 6 1/2 FT D. FIR STUMP  
S 19° E 38.5 FT BLAZE GONE

Steel Post North 0.3 FT  
Galv. Steel Post N 65° E 2.0 FT

C.S. File 67/56-15

New Accessories

5/8" x 30" Iron Rod with DCSO plastic  
CAP N 75° E 10.8 FT UP 6"

5/8" x 30" Iron Rod with DCSO plastic  
CAP N 7° W 9.2 FT UP 3"

Sketch of Monument, Accessories, and General Area

Location & Comments

Lat: 43° 24' 06.95" N  
Long: 122° 53' 04.80" W

MON. IS 545° E  
30 FT FROM SOUTH  
EDGE OF SMALL LOG  
LADDP9

AREA Burnt  
9-2020

Comp. Decline. 14 1/2° E  
Agency DCSO  
Party Chief S. F. HAISC  
Note keeper  
Witnesses J. LORSUNG

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald A. Quimby*

OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654

EXPIRES: 12/31/2024

CS 67/56-15

MMGPS 5/9/23  
TIME - 10:40  
H.I. - 2:00 PM

RENEWED 5/9/23

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. Fir BT, now only shattered remains of sawed stump, S.54°W. 12.5 ft. no scribe found.  
 No trace NE BT.  
 New BTs- 8" hemlock N.19°E., 141.6 ft. mkd. ¼ S12 CS BT.  
 24" Cedar, S.57°W. 51.0 ft. mkd. ¼ S13 CS BT.  
 Set - 6' Red steel fence Post alongside Brass Cap. This corner recent logged off unit approx. 200 ft. N of East fork Rock Creek Road.

Howard Johnstone - Feb. 5, 1982 - C.S. File 58/188-6  
 -----  
 Found - 1962 Cadastral BC. under 10" of dirt and rock with steel fence post alongside.  
 39" fir stump bears S.54°W., 12.5 ft.  
 16" hemlock bears South, 28.4 ft. (broken off at stump).  
 New BTs- 5" D.Fir bears N.89°W., 24.6 ft. (scribed)  
 5" D.Fir bears S.20°E., 39.0 ft. (scribed).  
 \*Note: brass disc on each face with "RLS 495"  
 Note - Corner sets alongside a small dry stream bed - entire area is covered with 1 - 4 feet of dirt & rock that has washed in from up above.

Fd. Ok by S. Ness 10/1995 - M123-3A&B

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page 20917)

The ¼ sec. cor. of secs. 12 & 13, monumented with an iron post, 2½" dia., firmly set, buried 8" below ground, with brass cap (properly) mkd. 3¼" B.C. MONUMENT IS S 45° E ~ 30 FT. FROM from which the remains of an original bearing tree SOUTH EDGE OF SMALL LOG LANDING.

GONE NO EVIDENCE

A decayed fir stump, size indeterminate, bears ~~S.50¼°W., 12.5 ft.~~, with no marks visible. (Record, S.54°W.)  
 and remains of a bearing tree mkd. by Brooks

GONE NO EVIDENCE

A decayed hemlock stump, size indeterminate, bears ~~S.3°W., 28.4 ft.~~, with no marks visible. (Record, South)

BURNED HOLLOW 30" X 6 FT STUMP

and a bearing tree mkd. by Tracy, in 1967  
 A cedar, 32" dia., bears S.57¼°W. 50.8 ft., with healed blaze. FACE INSIDE? ADD 3½" MAG NAIL R.S.C.

BURNED ROTTED 11" X 6 ½ FT STUMP

and bearing trees mkd. by Johnstone, in 1982  
 Fir, 12" dia. bears S.19°E, 38.7 ft., with healed blaze  
 A fir, 12" dia., bears N.88¼°W., 24.9 ft., with healed blaze.

BLAZE GONE

GONE NO EVID.

Cor. sits on edge of dry streambed, 5 ft. wide, with steel fence post driven alongside. STEEL POST ~ NORTH 03 FT  
 DECLINATION 14½°E GALV. STEEL LATH N 65° E, 2 FT.

NEW REFS  
 5/8" X 30" I.R. / DCSO SET PROT 6", BEARS N 75° E, 108 FT  
 PLSTC CAP " 3", BEARS N 07° W, 92 FT

CS 67/56 - 15 3/3 11