

TOWNSHIP 255 RANGE 2W SEC. 18 PLSS # 140 440

Date: 6/5/2023 By: X  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-18-23

Map: \_\_\_\_\_  
Narrative: \_\_\_\_\_  
Corner Rpt: CS67/56-20

Corner Designation

C 1/4 S 18

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

\_\_\_ Condition report

5/8" IRON ROD BENT  
Reference - Straighten &  
Replace CAP DESTROYED

\_\_\_ Not Found

Renewed

\_\_\_ Unrecorded

Previous Renewals

\_\_\_ Surveyed In

Quimby Set per M167-3A A & B  
FEB 2014

MONUMENT DETAIL

Accessories Found

SAWN BURNT 15" X 1 FT D. FIR STUMP  
N 87° E 24.4 FT BLAZE GORE ADD  
3 1/2" MAG NAIL TOP CENTER

13" X 1/2 FT W. FIR STUMP S 45° E 10.7 FT (REC  
S 46° E 10.8 FT) BLAZE GORE ADD 3 1/2" MAG  
NAIL TOP CENTER

SAWD - BURNT 14" X 2 FT D. FIR STUMP N 19° W  
3.9 FT PARTLY HEALED BLAZE SOME ILLEGIBLE  
SCRIBES VISIBLE ADD 3 1/2" MAG NAIL  
TOP CENTER

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

5/8" x 30" I. Rod with DCSD yellow Plastic  
CAP N 9° E 13.8 FT up 6"

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS Coordinate System  
Cottage Grove - Canyonville  
Zone

AREA BURST  
9-2020

N 204932.671  
E 257247.202

Comp. Decline. 14 1/2° E  
Agency DCSD  
Party Chief S. F. LAISE  
Note keeper  
Witnesses J. LORSUNDY

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald A. Quimby*

OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654

EXPIRES: 12/31/2024

CS 67/56-20

213

5/18/23

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140440

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - For: Roseburg Resources - Feb 2014 - M167-34 A&B  
 -----  
 Set - 5/8" with 2 1/2" alum. cap mkd:  
 TOP 1 FT BENT ROSEBURG RESOURCES COMPANY REMOVE ROD  
 SOUTH'LY 10" T25S R2W A STRAIGHTEN  
 REF. PLUMB LOCATION C 1/4 S18 RESET AT REF. POSITION  
 2014 NOW PROT. 3"  
 RLS 1654  
 New BTs- 14" D. Fir bears N. 87° E., 24.4 ft. scribed "E 1/4 S18 BLZ GONE  
 BT" 45° 103"  
 13" x 1/2 FT 12" W. Fir bears S. 45° E., 10.8 ft. scribed "C 1/4 S18 ADD 3 1/2" MAG NAIL TOP CNTR.  
 BT" BLAZE GONE  
 GONE NO EVID 10" W. Fir bears S. 38° W., 11.4 ft. scribed "C 1/4 S18  
 BT"  
 SAWN BURNED STUMP 14" x 2 FT. 15" D. Fir bears N. 19° W., 3.9 ft. scribed "C 1/4 S18 ADD 3 1/2" MAG NAIL TOP CNTR.  
 BT" PARTIALLY HEALED BURNED FACE SOME ILLEG. SCRIBG.  
 NEW REF.  
 5/8" IR/DOSO SET PROT. 6" BEARS NO 9° E, 138 FT  
 PLSTG.  
 CA  
 RTK POSITION  
 OCRS CANYONVILLE COTTAGE GROVE COORDS.  
 204932.671 N  
 257247.202 E

SAWN BURNED  
15" x 1 FT STUMP

SAWN BURNED STUMP

CS 67/56-20  
3/3

300 340