

TOWNSHIP 25S RANGE 2W SEC. 7 PLSS # 140500

Date: 6/5/2023 By: [Signature]  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-18-23

Map: \_\_\_\_\_  
Narrative: \_\_\_\_\_  
Corner Rpt: CS 67/56-21

DOUGLAS COUNTY  
SURVEYOR

Corner Designation

1/4 COR 57  
518

Monument(s) Found: (Condition and Source)

3 1/4" BLM BRASS CAP  
UP 4"

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

BLM Resurvey 1962 Vol  
32 pgs 13241-2  
DCSO 1995 CS 64/63-5  
BLM Resurvey 2010-2011  
Vol 57 pgs 22796-7  
Quimby 2014 M 167-34 AEB

MONUMENT DETAIL

1/4 57  
518  
T25S R2W  
1962

Accessories Found

BURNED OUT SNAG 5" CHINQUAPIN S89°E  
9.9 FT

BURNED - DEAD 27" FIR S50°E 3.6 FT (Rec  
3.4 FT) 3 1/2" MAG NAIL RIGHT Side Center

New Accessories

BURNT - DEAD 15" CHINGUAPID N38°W  
22.7 FT 3 1/2" MAG NAIL RIGHT SIDE CENTER

5/8" x 30" I. ROD, N1°W 8.9 FT WITH DCSD  
YELLOW PLASTIC CAP UP 6"

5/8" x 30" I. ROD S68°W 46.5 FT WITH  
DCSD YELLOW PLASTIC CAP UP 6"

Sketch of Monument, Accessories, and General Area

Location & Comments

OGRS COORDINATE SYSTEM  
COTTAGE GROVE - CANYONVILLE  
ZONE

N 207706.312

E 257262.991

AREA BURNT  
9-2020

Comp. Decline 14 1/2° E

Agency DCSD

Party Chief S. F. HAUSE

Note keeper

Witnesses J. LORSUNG

Monument on steep East slope  
Approx 85 ft north from dirt  
logging road.



EXPIRES: 12/31/2024

CS 6756-21

5/18/23

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22796-7

The sec. cor. of secs. 7 & 18, perpetuated by the Douglas Co. Surveyors Office in 1995, monumented with an iron post, 2" dia., firmly set, flush with a mound of stone 2 ft. base, 6" high, with brass cap (properly) mkd. 3 1/4 B.C PROT

NO COR EVID.

A hemlock stump, 28" dia., bears S.12 1/4°W., 39.4 ft., with a healed blaze. (Record, S.16°W., 40.9 ft.)

"

and the remains of a bearing tree mkd. by Brooks A sawed hemlock stump, 16" dia., bears N.50°W., 51.5 ft., with a healed blaze and a metal cover.

NO EVID.

and BTs mkd. by the Douglas County Surveyor's Office

A fir, 5" dia., bears N.28 1/4°E., 8.2 ft., with a healed double blaze.

BURNED OUT SNAG

A chinquapin, 7 1/2" dia., bears S.89°E., 9 ft., with scribe marks 1/4 S18 CS BT visible on a partially healed double blaze.

GONE

BURNED DEAD 27"

A fir, 22" dia., bears S.50°E., 3 ft., with a healed double blaze.

3.6

Ed as per rec. by R. Quimby, 2/2014 - M167-34 A&B

OCS

207706.312 N

257262.991 E

BURNED DEAD 15" CHINQUAPIN 3" 2 MAGNAIL R.S.C. N 75° W 22 2

78" x 30" IR / DCSO SET PROT. 6" BEARS N 01° W, 8 9  
PLSTG. CAP

" " " BEARS S 68° W, 4 5

MONUMENT ON STEEP EAST SLOPE APPROX 85 FT NORTH FROM DIRT LOGGING RD.

CS 67156-2  
3/3