

TOWNSHIP 25S RANGE 3W SEC. 34 PLSS # 440140

Date: 6/26/2023 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-31-23

Map: _____
Narrative: _____
Corner Rpt: CS67/56-28

DOUGLAS COUNTY
SURVEYOR

Corner Designation

C/4 S34

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Monument(s) Found: (Condition and Source)

NONE - GONE DUE TO LOGGING

Previous Renewals

BLM Resurvey 2008 Vol
57 Pg 2244Z

MONUMENT DETAIL

Accessories Found

Burnt - SAWN 10" X 1' D. FIR Stump N78 1/4° E
29.1 FT PART OF Lower blaze ADD 3 1/2"
MAG Nail Top Center

Burnt - SAWN 6" X 10" Cedar Stump N18 1/4° W
14.4 FT PART OF Lower blaze ADD 3 1/2"
MAG Nail Top Center

MM GPS 6/5/23

TIME - 9:15

H.I. - 2,000M

5/31/23

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 440140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22442)

Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. centerline.

GONE DUE TO LOGGING

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd. T25S R3M 2008

USING FOUND B.T.S SET PROT. 7" 5/8" x 30" I.R. / ALSO PLASTIC CAP

from which
fir, 9" dia., bears N.78 1/4° E., 24.1 ft., mkd. C 1/4 S34 BT.
cedar 7" dia. bears N.18 1/4° W., 14.4 ft. mkd. C 1/4 S34 BT.

ADD 3 1/2" MAGNAIL TOP CONTR. STUMPS BOTH LOWER PART BLZ.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located E. 185 ft. from a dirt road, 11 ft. wide, bears N.10° W. and S.25° E., in curve.

MINI GPS
43.3515
123.04018
FIR - CED. N72 3/4° W, 29.44

BURNED SAWN STUMP
10" X 1 FT AD
BURNED SAWN 6" X 10" STUMP

CS 67/56-28
3/3