

TOWNSHIP 26S RANGE 2W SEC. 20 PLSS # 240300

Date: 6/26/2023 By: JC  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 6-1-23

Map: \_\_\_\_\_  
Narrative: \_\_\_\_\_  
Corner Rpt CS 67/56-29

Corner Designation

$\frac{1}{4}$  COR  $\frac{20}{29}$

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" DCSO BRASS CAP  
UP 14"

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

GLD Resurvey 1916 - 1918  
Vol 10 pg 4334  
DCSO 1967 CS 54/40-13  
EDWARDS 2008 M 155-46

MONUMENT DETAIL

COUNTY SURVEYORS  
OFFICE  
T26S R2W  
 $\frac{1}{4}$   $\frac{520}{529}$

Accessories Found

BURNED- DEAD 23" D. FIRE N56°W 47.8 FT  
HEATED SINGLE BLAZE ADD 3 1/2" MAG NAIL  
RIGHT SIDE CENTER  
MOSTLY BURNED AWAY 3 FT CEDAR STUMP S33°W  
92.9 FT (REC 94.9 FT)

GALVANIZED STEEL POST 2 FT NORTH



MM GPS 6/1/23  
TIME - 9:35  
H.I. - 2,000M

6/1/23

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4246)

Set cedar stake, 3 ft. long, 4" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S20 on N & 29 on S face, from which  
A cedar, 10" dia., bears N.21°E., 24 lks., mkd: 1/4 S20 BT.  
A fir, 8" dia., bears S.38°E., 12 lks., mkd: 1/4 S29 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4334)

Intersect the 1/4 sec. cor. established by Deputy Gibb in 1909, which is a cedar post, 4" sq. 12" above ground, firmly set, marked & witnessed as described by the surveyor general

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - March 1967 - C.S. File 54/40-13

Found - *PROT 14"* Unrecorded 3/4" I.Rod which bears S.4 1/2°E., 9.6 ft. from true corner.

*NO EVID.* Orig. 10" now 22" Cedar, down & burned, N.21°E., 15.8 ft., no scribe found.

*NO EVID* Orig. 8", now 16" Fir snag, S.38°E., 7.9 ft., open & find "1/4S" scribe.

Set - 2 1/2" Brass cap at cor. mkd: County Surveyors Office T26S R2W 1/4 S 20 S 29

*BURNED HEAD 23"*

New BTs - *922* 9" D Fir N.56°W., 47.8 ft. mkd: ~~1/4 S20 CS BT.~~ *FHSB*  
15" Cedar S.33°W., 94.9 ft. mkd: ~~1/4 S29 CS BT.~~

*MOSTLY BURNED AWAY 3 FT STUMP*

Note - This area logged off & grown up to dense greasewood brush. Corner on gentle SE slope approx. 200 ft. E of logging road.

*GALVANIZED STEEL LATH 2 FT NORTH*

*DECLINATION 14 1/2° E*

Fd. BC & 2 BTs by D. Edwards, 4/2008 - M155-46

*NEW REF. 9*

*BURNED HEAD 14" D, FIR 3 1/2" MAG NAIL R.S.C. N82°E, 10 8*

*BURNED SAWN 20" x 1 1/2 3 1/2" MAG NAIL TOP CNTR S 55 1/2° W, 14 2  
D, FIR STUMP*

CS 67/56-29  
3/3 1