

TOWNSHIP 26S RANGE 1W SEC. 5 PLSS # 200600

Date: 6/26/2023 By: x
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 6-14-23

Map: _____
Narrative: _____
Corner Rpt CS 67/56-35

DOUGLAS COUNTY
SURVEYOR

Corner Designation

See Cor $\frac{6}{7} \frac{5}{8}$

Monument(s) Found: (Condition and Source)

2 1/2" DC SO BRASS CAP
ON 1" ID IP UP 12"
ORIG STOVE ON EAST EDGE

Previous Renewals

DC SO 1970 CS 52/77-29
DC SO 1986 CS 62/31-9

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

MONUMENT DETAIL

County Surveyors
OFFICE
T26S R1W

$\frac{56}{57} \frac{55}{58}$
1970

Accessories Found

BURNED - DEAD 72" D. FIR S 53°E 83.2 FT
Fully Healed Single BLAZE ADD 3 1/2" MAG
NAIL RIGHT Side Center

BURNED - DEAD 55" D. FIR S 6°W 71.3 FT
Fully Healed Single BLAZE ADD 3 1/2" MAG
NAIL RIGHT Side Center

Root Hole N 49°W 14.2 FT Rec D. FIR

BURNED DEAD 17" D. FIR N 17°E 13.7 FT
Fully Healed Single BLAZE Add 3 1/2" MAG
NAIL RIGHT Side Center

BURNED DEAD 22" D. FIR S 67°E 6.3 FT
(Rec 6.4 FT) Healed Single BLAZE ADD
3 1/2" MAG NAIL RIGHT Side Center

Monument Set (Procedure and Description)

MONUMENT DETAIL

Blank lines for Monument Set description.

New Accessories

Blank lines for New Accessories description.

Sketch of Monument, Accessories, and General Area

Location & Comments

CORNER IS ON LEVEL GROUND,
IN BURNED VERY OLD THINNING
APPROX 170' WEST FROM END
OF DIRT ROAD

AREA BURNED
9-2020

OCRS COORDINATES
COTTAGE GROVE - CANYONVILLE ZONE
180724.599 N
291534.444 E

Comp. Decline 14 1/2° E
Agency DCSD
Party Chief S. F. AUSE
Note keeper
Witnesses J. LORSON



CS 67/56-35

214

EXPIRES: 12/31/2024

MMGPS 6/14/23
TIME - 9:55
H.I. - 2.000M

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4164)

Set basalt stone 18x10x8", 12" in the ground for cor of secs 5, 6, 7, & 8 mkd with 5 notches on S & E edges, from which

- A fir, 6" dia., bears N.33°E., 87 lks. mkd: T26S R1W S5 BT
- A fir, 40" dia. bears S.53°E. 126 lks. mkd: T26S R1W S8 BT
- A fir, 18" dia. bears S.4½°W. 108 lks. mkd: T26S R1W S7 BT
- A chinquapin, 8" dia., bears N.59°W., 41 lks., mkd: T26S R1W S6 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1970 - C.S. File 52/77-29

Found - Corner stone, in place with "X" on top & 5 notches on S & E.

- Orig. 6" now 14" fir alive, N.33°E., 57.4 ft. open & find "\5" scribe.
- Orig. 18" now 40" fir alive S.4½°W., 71.3 ft. shows good scar, we tag.
- Orig. 40" now 60" fir alive, S.53°E., 83.2 ft. shows good scar, we tag.

Possible remains of NW orig. BT down & badly decayed

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T26S R1W (Reset old stone alongside) OFFICE 1970 ✓ S 6 | S 5 S 7 | S 8 ✓

New BTs- 18" D.Fir N.49°W., 14.2 ft. mkd: T26S R1W S6 CS BT
 12" D.Fir N.17°E., 13.7 ft. mkd: T26S R1W S5 CS BT
 14" D.Fir S.67°E., 6.6 ft. mkd: T26S R1W S8 CS BT
 6" D.Fir S.20°W., 18.7 ft. mkd: S7 CS BT.

This corner lies on very gentle almost flat, easterly slope, about 1400 ft. east of Burnt Creek access road. #2644

Douglas Co. Surveyors Office - Randall Smith - Stephen Flauser - Jan. 15, 1986 - C.S. File 62/31-9

Found - 1970 County brass cap protruding 12" above ground. A 15x8x7" stone with 5 marks found on one edge. (Rec. 18x8x7" stone with 5 marks on south & east edges orig. and an "X" on top (fd per 1970 Ren.) lays along northeast edge of IP.

Orig BT, a ~~6"~~ now 10" dia. 3½ ft. high rotted D.Fir stump scribing found in previously opened blaze " / 5" bears N.33°E., 57.7 ft. (Rec. N.33°E., 37.4 ft. to face of blaze.)

Orig. BT, a ~~40"~~ now 67" dia. D.Fir with a fully healed single blaze bears S.53°E. 83.2 ft. (agrees with record). continued next page

43.32813
122.85419

RENEWED 6/14/23

NO EVIDENCE REMAINS

BURNED DEAD 72"

CS 67/5635 1
314

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BURNED DEAD 55" Orig. BT, a ~~18"~~ now 46" dia. D. Fir with a fully healed single blaze bears S. 6° W., 71.3 ft. (Rec. S. 4½° W., 71.3 ft.) ADD 3½" MAG NAIL R.S.C.

No evidence of NW BT found.

~~18"~~ now 17" dia. 40 ft. high D. Fir snag with a partially healed single blaze scribing visible "T26S R1W S6 CS BT" bears N. 49° W., 14.2 ft. ROOT HOLE OK

BURNED DEAD 17" - ~~12"~~ now 13" dia. D. Fir with a fully healed single blaze bears N. 17° E., 13.7 ft. ADD 3½" MAG NAIL R.S.C.

BURNED DEAD 22" - ~~14"~~ now 17" dia. D. Fir with a fully healed single blaze bears S. 67° E., 6.8 ft. ADD 3½" MAG NAIL R.S.C.

~~6"~~ now 6" dia. dead D. Fir with a fully healed single blaze bears S. 20° W., 18.7 ft.

~~New BT 10" dia. D. Fir double blazed and scribed "T26S R1W S6 CS BT" bears N. 9° W., 49.0 ft.~~

NO EVID. REMAINS
NO EVID. REMAINS
NO EVID. REMAINS

DECLINATION 14½° E

IN BURNED VERY OLD THINNING
APPROX. 170 WEST FROM END OF DIRT RD.

CS 67/56-35
4/4 2