

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 269 RANGE ZW SEC. 5 PLSS # 200606

Date: 8/30/2023 By: JL  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 8-22-23

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/56-59

Corner Designation

sec Cor 56/55  
57/58

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

\_\_\_ Condition report

3/4" BLM BRASS CAP

\_\_\_ Not Found

4P 14"

Renewed

\_\_\_ Unrecorded

Previous Renewals

\_\_\_ Surveyed In

BLM Resurvey 1959 Vol 30 pg 12744-5

m<sup>c</sup> Chesney 1977 CS 58/8-48

BLM Resurvey 2018-2020

Vol 59 pgs 24062-3

MONUMENT DETAIL

T265 R2W

56/55

57/58

1959

Accessories Found

Burned Broken off 13" decayed Fir stump  
S71 1/2° E 59.4 FT

Burned Decayed 36" X 5 FT Fir stump  
N 21 1/2° W 36.6 FT

Burned - Decayed 39" X 5 FT Fir stump  
N 12 1/2° W 38.3 FT

Burned Decayed 43" Fir stump N 55 1/4° E  
60.1 FT

Burned - Decayed 46" Fir stump N 63 1/2° E  
66.8 FT

Burned - Dead 10" Fir N 69° E 19.7 FT open

Burned Face

Burned - SAWN 20" X 4" Fir stump S 67 1/4° E  
34.8 FT

Burned - SAWN 19" X 5" Fir stump N 11 1/2° W  
14.8 FT

C.S. File 67/54-59

New Accessories

BURNED - DEAD 8" D. FIR N 36° E 4.9 FT  
3 1/2" MAG NAIL RIGHT SIDE CENTER

BURNED - DEAD 7" D. FIR N 83° E 15.9 FT  
3 1/2" MAG NAIL RIGHT SIDE CENTER

BURNED - DEAD 12" D. FIR S 1° E 4.4 FT  
3 1/2" MAG NAIL RIGHT SIDE CENTER

BURNED DEAD 35" Hemlock S 87° W 32.0 FT  
3 1/2" MAG NAIL Right-Side Center

Sketch of Monument, Accessories, and General Area

Location & Comments

MON. ON moderate S.W  
Slope NE & SW QUADS LARGE  
Reprod N.W & S.E QUADS  
Clear Cut  
OCRS COORDINATE SYSTEM  
Cottage Grove - Canyonville  
Zone

AREA BURNED  
9-2020

Comp. Decline. 14 1/2° E  
Agency DCSO  
Party Chief S. K. KAUSE  
Note keeper  
Witnesses J. Corsun

N 180204.055  
E 260581.289

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald A. Quimby*

OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654

EXPIRES: 12/31/2024

CS 67/56-59

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias \_\_\_\_\_ Description OCCRS CANYONVILLE COTTAGE GROVE CORNER 5  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description 180204.055 N  
 Alias \_\_\_\_\_ Description 260581.289 E

Evidence of old Madrone scattered by logging at approx. location of orig. 20" Madrone, down and rotted S.50°E., 47 lks.  
 Down 38" Fir (W. Co. 7/7/67 record identified this BT S.60½°W., 21.6 ft.  
 50" Fir (W. Co. 1967 record identified this BT, N.12°W., 38.1 ft.  
 Down 16" Fir, face partly healed, BT tag. (1967 record identified this BT, N.25°E., 85.7 ft.)  
 28" Fir stump, face and plates intact. (1967 record identified this BT, S.71°E., 59.6 ft.)  
 22" Fir, down healed face and plate intact. (1967 record identified this BT S.40°W., 58.0 ft.)  
 48" Fir, face and plate intact, (1967 record identified this BT N.22°W., 36.6 ft.)

Accessories added this date:  
 W nails and plates on:  
 40" Fir stump, N.56°E., 59.2 ft.  
 54" Fir stump, N.64°E., 65.2 ft.

RENEWED 8/22/23

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24062-3)

DECLINATION 14½°E

The cor. of secs. 5, 6, 7, and 8, reported by Zirpel, Jr., 3 1/4" BC and Glenn in 1959; perpetuated by Williams, in 1977; PROPERLY MARKED monumented with an iron post, 2 1/2" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees reported by Zirpel, Jr., and Glenn PROT 14"

A decayed fir stump, size indeterminate, bears N.25°E., NOT LOOKED FOR -85.8 ft., with a healed blaze.

BURNED BAKED OFF A decayed fir stump, 13" dia., bears S.71½°E., 59.4 ft., with scribe marks T26S R2W S8 BT visible on open blaze.

OUT OF POS. A decayed fir stump, 23" dia., bears S.40½°W., 57.4 ft. NO POSITION no marks visible.

NOW BURNED A decayed fir stump, 36" dia., bears N.21½°W., 36.6 ft., with a healed blaze. 5 FT TALL

NOW BURNED A decayed fir stump, 39" dia., bears N.12½°W., 38.3 ft., with illegible scribe marks visible on open blaze. 5 FT TALL

and the remains of the bearing trees mkd. by Williams A decayed fir stump, 45" dia., bears N.55¼°E., 60.1 ft., no marks visible. 43"

A decayed fir stump, 48" dia., bears N.63½°E., 66.8 ft., no marks visible. 46"

and new bearing trees continued next page

NOW ALSO BURNED

" "

NEXT PAGE →  
2

CS67/56-59 3/4

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

**BURNED DEAD** A fir, 10" dia. bears N.69°E, 19.7 ft. mkd T26S R2W S5 BT **FACE OPEN BUT BURNED**

**BURNED SAWN** A fir, 13" dia., bears S.67½°E, 34.8 ft., mkd. ~~T26S R2W~~

**FALLEN OUT OF POSITION** A fir, 14" dia., bears ~~S.11½°W~~, 24.8 ft., mkd. T26S R2W **OPEN BURNED BLAZE SCRIBED VIS.**

**BURNED SAWN STUMP** fir, 13" dia., bears N.11½°W, 14.8 ft., mkd. ~~T26S R2W~~

2011 X 4 STUMPS 8 BT.  
19" X 5" 56 BT.  
NAD 1983 (2011)  
Latitude: 43°19'37.77" N. Longitude: 122°58'13.97" W.

NEW REFS.

<b>BURNED DEAD</b>	8" D. FIR	3 1/2" MAG NAIL RSC	TREE BEARS N36°E, 49
"	7" " "	" " "	" " N83°E, 159
"	12" " "	" " "	" " S01°E, 44
"	35" HEMLOCK	" " "	" " S87°W, 320

MON ON MODERATE SW SLOPE NE AND SW QUADS. LARGE REPROD  
NW AND SE " CLEARCUT

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4220)

-----  
Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 5, 6, 7, & 8, marked T26S S5 on NE, R2W S8 on SE, S7 on SW, S6 on NW faces, with 5 notches on S & E edges; from which  
A laurel, 10" dia., bears N.45°E., 24 lks., mkd: T26S R2W S5 BT.  
A laurel, 18" dia., bears S.50°E., 47 lks., mkd: T26S R2W S8 BT.  
A fir, 24" dia. bears S.55°W., 32 lks. mkd: T26S R2W S7 BT  
A fir, 30" dia. bears N.15°W., 58 lks. mkd: T26S R2W S6 BT

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12749-5)

-----  
The cor. of secs. 5, 6, 7, and 8, determined at record distance from each of the original bearing trees:  
A madrone, 13" dia., bears N.51½°E., 24 lks., with a burned and rotted center. (Record bearing, N.45°E.)  
A down and rotted madrone, 20" dia., bears S.50°E., 47 lks. dia., with no marks remaining.  
A fir, 37" dia., bears S.61°W., 32 lks., with illegible bark scribes. (Record bearing, S.55°W.)  
A fir, 45" dia., bears N.12½°W., 58 lks., with an opened and burned blaze. (Record bearing, N.15°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

T26S	R2W
S 6   S 5	
S 7   S 8	
1959	

from which

A fir, 13" dia. bears N.25°E. 130 lks. mkd: T26S R2W S5 BT  
A fir, 19" dia. bears S.71½°E. 90 lks. mkd: T26S R2W S8 BT  
A fir, 20" dia. bears S.40½°W. 87 lks. mkd: T26S R2W S7 BT  
A fir, 38" dia. bears N.21½°W. 55½ lks mkd: T26S R2W S6 BT

Glen McChesney - For: Weyerhaeuser Co. - April 1977 (Filed 12/1980) C.S. File 58/8-48

-----  
Found - 1959 GLO brass cap, in place.  
Down or broken remains of Madrone, N.51½°E., 15.8 ft. to root hole. (not fd. by Weyerhaeuser Co. records 7/7/67) (Orig. record 13", N.51½°E., 24 lks. 1959) 1883 Rec. N.45°E.) continued next page