

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 26S RANGE 1W SEC. 14

PLSS # 500408

Date: 9/11/2023 By: X

This survey consists of:

DOUGLAS COUNTY OREGON

DATE 8-23-23

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/56-60

Corner Designation

SEC COR	S15	S14
	S22	S23

DOUGLAS COUNTY SURVEYOR

Monument(s) Found: (Condition and Source)

6" x 8" x 10" stone with "X" ON TOP

Condition report

Not Found

Renewed

Unrecorded

Surveyed In

Previous Renewals

SHANER 1967 CS 55/66

MONUMENT DETAIL

Accessories Found

BURNED 72" CEDAR N 30° E 10.7 FT (REC 10.6 FT)  
ADD 3 1/2" MAG NAIL Left Side Center

D.FIR Root Hole S 26° W 23.8 FT

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

Reference stone Location  
Set 5/8" X 30" Iron Rod  
with DCSO yellow Plastic  
Cap up 4" Reset  
Stone on West Edge  
of Iron Rod

New Accessories

8" BURNED-DEAD FIR N 67°E 1.7 FT  
3 1/2" MAG Nail RIGHT Side Center

5/8" X 30" Iron Rod S 24°E 13.0 FT WITH  
DCSO yellow PLASTIC CAP UP 6"

5/8" X 30" Iron Rod S 74°W 8.3 FT WITH  
DCSO yellow PLASTIC CAP UP 6"

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS Coordinate Reference  
System Cottage Grove  
Canyonville Zone

AREA BURNT

9/2020

N 170257.085  
E 307259.198

Comp. Decline. 14 1/2° E  
Agency DCSO  
Party Chief S. F. Ruse  
Note keeper  
Witnesses J. Loring

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald A. Quimby*

OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654

EXPIRES: 12/31/2024

CS 67/56-60

2/3

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor Secs 14, 15, 22, & 23

Alias \_\_\_\_\_ Description OGRS CANNONVILLE COTTAGE GROVE CORNERS  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description 1702.57.085 N  
 Alias \_\_\_\_\_ Description 307259.198 E

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4118)

Set a basalt stone 15x10x8", 10" in the ground for cor. of secs. 14, 15, 22, & 23 mkd with 3 notches on S & 2 notches on E edge, from which

- A cedar, 48" dia., bears N.30°E., 16 lks., mkd: T26S R1W S14 BT.
- A cedar, 12" dia., bears S.22°E., 83 lks., mkd: T26S R1W S23 BT.
- A fir, 36" dia., bears S.26°W., 36 lks., mkd: T26S R1W S22 BT.
- A hemlock, 6" dia., bears N.66°W., 68 lks., mkd: T26S R1W S15 BT.

RENEWED 8/23/23

Bruce Shaner - For: USFS - Nov. 1967 - C.S. File 55/66

At the section corner common to section 14, 15, 22, 23, T26S, R1W, WM, Douglas County, Oregon, (Umpqua National Forest) I found a 6" dia. stone with "X" chiseled on top (record stone was 15"x10"x8") from which corner stone a:

- 72" 60" Cedar, orig. BT with scar grown over face, bears N. 30°E., 10.6 ft. 10Z TO LEFT SC, 3 1/2" MAGNAIL
- 12" Cedar snag, orig. BT with scribed "- 26S, R1W, S23" visible, bears S.22°E., 54.7 ft.
- 36" D. Fir, orig. BT, now blown down, bears S.26°W. 23.8 ft
- 6" Hemlock, orig. BT, bearing N.66°W., 44.9 ft., now missing.

STONE TOY FLUSH WITH GROUND.  
BLOWN DOWN

ROOT HOLE

REFERENCE OUT POSITION OF "X" ON FOUND CORNER STONE, REMOVE FROM GROUND, FIND STONE MEASURES 6"x8"x10"

AT REFERENCED POSITION SET A 5/8" x 30" IRON ROD WITH A DCSO YELLOW PLASTIC CAP. MONUMENT PROTRUDES 4" ABOVE GROUND ORIGINAL STONE MON. SET ON WEST EDGE OF I.R.

NEW REFS

- 8" BURNED DEAD FIR 3 1/2" MAGNAIL RSC, BEARS N67°E, 12 FT.
- 5/8" IR / YELLOW DCSO PLASTIC CAP PROT 6" " S24°E 13'
- " " " " " S74°W, 8'

C.S. 67/56-60  
3/3