

GOVERNMENT CORNER RESTORATION FORM

TOWNSHIP 25S RANGE 3W SEC. 34 PLSS # 500100

FILED
Date: 9/11/2023 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 9-6-23

Map: _____
Narrative: _____
Corner Rpt: CS 67/56-65

Corner Designation

T25S
34 | 35
3 | 2
T26S

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" BLM BRASS CAP
up 14"

___ Condition report
___ Not Found
 Renewed
___ Unrecorded
___ Surveyed In

Previous Renewals

GLB Resurvey 1940 Vol 27 pg 11506
McChesney 1965 CS 53/115
Christensen 1998 M 128-59
BLM Resurvey 1995 Vol 52 pg 19887
Christensen 1999 M 133-77
DCSO 2007 CS 67/24-45
BLM Resurvey 2008 Vol 57 pg 22417

MONUMENT DETAIL

T25S R3W
534 | 535
53 | 52
T26S
1943

Accessories Found

ORIG. BT'S
BURNED - DEAD 46" D. FIR S45°W 7.1 FT (REC 6.6 FT)
Healed BLAZE 3 1/2" MAG NAIL RIGHT SIDE CENTER
BT'S by Price
BURNED - SAWN 30" X 3 FT CEDAR STUMP N62 1/2° W
12.5 FT 3 1/2" MAG NAIL TOP CENTER
BT BY McChesney
BURNED MOSTLY ROTTED 47" FIR STUMP N0 1/2° W
23.1 FT
BT'S by Seibold
BURNED - DEAD 11" D. FIR N57 1/2° E 10.7 FT (REC
N56 1/2° E 10.9 FT) Healed BLAZE 3 1/2" MAG NAIL
RIGHT SIDE CENTER
BURNED - DEAD 15" D. FIR S25 1/2° E 41.9 FT
3 1/2" MAG NAIL RIGHT SIDE CENTER
Metal Post 1' NNW

C.S. File 67/56-65

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

BURNED - DEAD 31" Hemlock SAW 25.8 FT
3 1/2" MAG NAIL RIGHT Side Center

Note Tree Not BLAZED or Scribed

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS COORDINATE System
Cottage Grove - Canyonville
Zone

Area Burnt

9/2020

N 186301.569
E 244626.371

Comp. Decline. 14 1/2° E

Agency DCSD

Party Chief S. F. MUSE

Note keeper

Witnesses J. LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/56-65 2/3

9/6/23

PRIMARY CORNER DESCRIPTION Cor. Secs. 34 & 35; 2 & 3 T26-3

Alias _____ Description N 186301.569
 Alias _____ Description E 244026.371
 Alias _____ Description _____
 Alias _____ Description OCRS CANYONVILLE COTTAGE GROVE CORNERS

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22417)

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A sawed fir stump, 26" dia., bears N.69°E., 23.1 ft., with no marks visible on an opened blaze.

BURNED DEAD

- Ad. fir, 46" dia., bears S.45°W., 6.6 ft., with a healed blaze.

and the remains of bearing trees mkd. by Price

NO EVID. REMAINS

A decayed cedar stump, size indeterminate, bears N.20½°E., 29.7 ft., alongside of which is a down, decayed cedar snag, 12" dia., with scribe marks W 3 and other fragmentary scribe marks visible on a partially healed blaze.

BURNED SAW STUMP

cedar, 30" dia., bears N.62½°W., 12.5 ft., with a healed blaze.

and the remains of a bearing tree mkd. by McChesney, in 1965 A sawed, decayed fir stump, 47" dia., bears N.½°W., 23.1 ft., with no marks visible.

BURNED MOSTLY ROTTED

and bearing trees mkd. by Seibold

BURNED DEAD

11" Ad. fir, 10" dia., bears N.56½°E., 10.9 ft., with a healed double blaze.

BURNED DEAD

15" Ad. fir, 13" dia., bears S.26½°E., 41.9 ft., with a healed blaze.

Corner is located on a SE. slope.

FOUND A METAL LATH 2 1/2 FT. NNW

~~The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP", and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", are as follows:~~

20 9/11/2023
Wrong corner

Latitude: 43°20'38.07"N Longitude: 123°01'13.77"W

T26-3
44 535
52
126-3

DECLINATION 14½°E
NEW REF

BAD POS. SEE ABOVE OCRS POS

BURNED DEAD 31" HEMLOCK 3½" MAG NAIL RSC BEARS S 04°W, 25.8

CS 67/56-65
3/3