

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 24S RANGE 2W SEC. 21

PLSS # 400300 Date: 10/30/2023 By: X  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 10-24-23

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/57-8

Corner Designation

SEC COR 21/22  
28/27

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

\_\_\_ Condition report

DCSD BRASS CAP

\_\_\_ Not Found

UP 8" UNDER 40" CEDAR

Renewed

VISIBLE BELOW TREE

\_\_\_ Unrecorded

Previous Renewals

\_\_\_ Surveyed In

DCSD 1978 CS 58/46-75

COOK 2009 M 160-24

MONUMENT DETAIL

DOUGLAS COUNTY  
SURVEYOR  
T24S R2W

521/522

528/527

1978

Accessories Found

BURNED ROTTED 40" X 5 FT HEMLOCK STUMP

N39°E 40.2 FT

BURNED ROTTED 54" X 4 FT FIR STUMP N34°W

22.0 FT (REC N35°W 21.8 FT) ADD 5/8" X 30"

IRON ROD WITH YELLOW DCSD PLASTIC CAP

DRIVEN IN TOP CENTER

BURNED BROKEN FALLEN 40" CEDAR S20°E

14.6 FT

28" X 8 FT CEDAR S68°30'W 20.7 FT (REC

20.5 FT) ADD 3 1/2" MAG NAIL RIGHT SIDE

CENTER

25" X 4 FT HEMLOCK STUMP N84°30'E 41.0 FT

(REC 40.9 FT) ADD 3 1/2" MAG NAIL TOP

CENTER

C.S. File 67/57-8

Monument Set (Procedure and Description)

MONUMENT DETAIL

---



---



---



---



---



---

New Accessories

5/8" X 30" IRON ROD UP 15" N 86°W 3.0 FT

---



---



---



---



---



---



---



---

Sketch of Monument, Accessories, and General Area

Location & Comments

BCRS COORDINATE SYSTEM  
COTTAGE GROVE - CANYONVILLE  
ZONE

AREA BURNT  
9/2020

N 229840.289  
E 270445.855

Comp. Decline. 14 1/2° E  
Agency DCSO  
Party Chief S. FINUSE  
Note keeper  
Witnesses J. LOBSUNG

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald A. Quimby*

OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654

EXPIRES: 12/31/2024

CS 67/57-8 2/3

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 400300

10/24/23

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description OAKS CANYONVILLE COTTAGE GROVE CORNER

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description 229840.289 N

Alias \_\_\_\_\_ Description 270645.855 E

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5 1893 - (DCSO recs Vol 7 Pgs 2914-5)

-----

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 21, 22, 27, & 28, marked T24S S22 on NE, R2W S27 on SE, S28 on SW, S21 on NW faces, with 2 notches on S & 3 notches on E edges; from which

A hemlock 24" dia bears N.84°E. 62 lks mkd T24S R2W S22 BT

A cedar, 24" dia bears S.20°E. 25 lks mkd: T24S R2W S27 BT

A cedar, 5" dia., bears S.66°30'W., 31 lks., mkd: T24S R2W S28 BT.

A fir, 60" dia. bears N.35°W. 33 lks. mkd: T24S R2W S21 BT

Douglas Co. Surveyors Office - R.B. Kimberling - P.L. Earle - F.C. Silagy - March 14, 1978 - C.S. File 59/46-75

Found - 3" sq. wooden post, not orig.

*BURNED ROTTED 40" x 5 FT.* 24" now 41" Hemlock stump bears N.39°E., (rec. N.84°E.) 40.2 ft. with a well healed blaze.

24" now 30" Cedar bears S.20°E., 14.6 ft., (rec. 16.5 ft.) with scribing "2W 2" in a partly healed single blaze.

5" now 16" Cedar bears S.68½°W., (rec. S.66°30'W.) 20.5 ft. with an almost healed single blaze.

*BURNED ROTTED 54" x 4 FT.* 60" now 63" Fir stump bears N.35°W., 21.8 ft. with a well healed single blaze. *ADD 5/8" x 30" IRON ROD / YELLOW CAP DRIVEN IN TOP CNTR.*

Set - 1"x36" iron pipe with brass cap set 6" above ground mkd: DOUGLAS COUNTY SURVEYOR (1978)

T24S	R2W
S 21   S 22	
S 28   S 27	

New BTs- 11" Hemlock bears N.84½°E., 40.9 ft., double blazed & marked "T24S R2W S22 CS BT"

6" Hemlock bears N.14°W., 98.9 ft., double blazed & marked "T24S R2W S21 CS BT"

Robert A. Cook - For: Weyerhaeuser Co. - Dec. 2009 - M160-24

*CAPAS ABOVE PROT 8" - THE 40" CEDAR FALLEN NORTH OVER MONUMENT BUT MON. IS VISIBLE UNDERNEATH*

Found - 2½" Douglas County 1978 brass cap on 1" pipe up 6" on N. slope about 200 ft. east of a gravel road.

*BURNED BROKEN FALLEN 40" V CEDAR S.20°E 14.6 FT. (OVER CAP) and paint. TO BROKEN BASE*

28" x 8 FT 30" Cedar S.68°30'W 20.7 ft. with healed face and paint. *ADD 3 1/2" MAG NAIL R.S.C.*

25" x 4 FT. 24" Hemlock N.84°30'E 40.9 ft. with healed face and paint. *GONE 410 ADD 3 1/2" MAG NAIL TOP CNTR*

5/8" x 30" IRON ROD, PROT 15" BEARS N86°W, 30 FT.

CS 67/57-8  
3/3