

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 24S RANGE 2W SEC. 19

PLSS # 200300

Date: 10/30/2023 By: X  
This survey consists of:

Map: \_\_\_\_\_

DOUGLAS COUNTY OREGON

DATE 10-24-23

Narrative: \_\_\_\_\_

Corner Rpt: CS67/57-9

DOUGLAS COUNTY  
SURVEYOR

Corner Designation

Wit. Cor 19/20  
30/29

Monument(s) Found: (Condition and Source)

\_\_\_ Condition report

\_\_\_ Not Found

Renewed

\_\_\_ Unrecorded

\_\_\_ Surveyed In

DCSO BRASS CAP

Previous Renewals

McChesney 1972 CS 59/24-3  
DCSO 1976 CS 59/24-3

MONUMENT DETAIL

DOUGLAS COUNTY  
SURVEYOR  
Wit. Cor  
EAST 50 FT TO  
T24S R2W  
519/520  
530/529  
1976

Accessories Found

BURNED - Rotted 40" X 3 FT FIR STUMP  
S46°W 83.9 FT TO WITNESS COR. (Rec S62W  
124.7 TO TRUE COR)

BURNED Rotted 28" X 2 FT D. FIR STUMP  
S79°W 30.6 FT TO WITNESS COR. (Rec S86°W  
79.3 FT TO TRUE COR)

36" D. FIR STUMP WITH RAILROAD SPIKE  
IN CENTER BEARS S35½°E 33.6 FT (Rec S34½°E)

28" X 3 FT BURNED Rotted Hemlock STUMP  
IRON & CAP LOOSE ON GROUND RESET IN  
STUMP CENTER S36°W 39.2 FT

Very Rotted - BURNED 28" X 2 FT D. FIR  
STUMP N36°E 10.6 FT BRIDG SPIKE GONE

C.S. File 67/57-9

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

5/8" Iron Rod's with DCSO yellow Plastic  
CAP up 3" in Red Painted MOUND  
OF Stone BEARS

EAST 90.0 FT  
NORTH 82.0 FT

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS COORDINATE SYSTEM  
COTTAGE GROVE - CANYONVILLE  
ZONE

CORNER IS APPROX  
105 FT + 75'  
SOUTH OF ROAD  
WYO # 317

N 228501.090

E 260583.111

COORD. ON WITNESS COR.  
Set 50 FT West From TRUE  
CORNER

AREA BURNT  
9/2020

Comp. Decline. 14 1/2° E

Agency DCSO

Party Chief S. F. HAUSE

Note keeper

Witnesses J. LOBSUNG

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

Ronald A. Quimby

OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654

EXPIRES: 12/31/2024

CS 67/57-9

10/24/23

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Wit. Cor. Secs 19, 20, 29, & 30

Alias \_\_\_\_\_ Description OLMS CANYONVILLE COTTAGE GROVE CORNER S  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description 228501.090 N  
 Alias \_\_\_\_\_ Description 260583.111 E

**SEE BELOW** - 40" D. Fir stump with railroad spike in center, bears S. 50° W., 40.6 ft., (Weyerhaeuser rec. S. 50° W., 40.6 ft.)

**GONE**

**BURNED ROTTED**  
**X 3 FT TALL**  
**W NAIL GONE**

**BURNED ROTTED**  
**28" X 2 FT**  
**W NAIL GONE**

~~36" Hemlock stump with "W" nail bears S. 67° W., 23.3 ft.~~  
~~44" D. Fir stump with "W" nail bears S. 62° W., 124.7 ft.~~  
~~40" D. Fir stump with "W" nail bears S. 86° W., 79.3 ft.~~  
~~48" D. Fir stump with "W" nail bears N. 49° W., 125.0 ft.~~

**FROM WITNESS?**  
**54 1/2° W, 83 1/2'**  
**57 1/2° W, 30 1/2'**  
**FROM WITNESS**

We do not find the 1/2" IP set by Weyerhaeuser Co. since this cor. position falls on the road cut bank, We set a witness corner 50' West of the true corner.

Set - 1" x 30" I. Pipe, 24" in the ground with brass cap attached mkd: Douglas Co. Surveyor

Wit. Cor.  
 East 50 ft. to  
 T24S R2W  
 S 19 | S 20  
 S 30 | S 29

35 1/2°

from which we note the following bearing objects\*  
 The aforementioned railroad spike set in a 36" D. Fir stump bears S. 34 1/2° W., 33 1/2 ft., from the witness corner.

**IR AND CAP LOOSE**  
**AND GROUND**  
**RESET IN STUMP CNTR**

**VERY ROTTED AND**  
**BURNED 28" X 2 1/2 FT**  
**SPIKE GONE**

A 5/8" x 30" I. Rod driven 16" deep in the center of a 38" Hemlock stump, bears S. 36° W., 39.2 ft., with alum. cap attached mkd. "Douglas County Surveyor WC RP2" This stump has been notched for use as a logging anchor.

**BURNED ROTTED**  
**28" X 3 FT.**

A bridge spike driven in the center of a 30" D. Fir stump marked "WC RP3" bears N. 36° E., 10 1/2 ft.

Note - This corner is located approx. 50 ft. west of Weyerhaeuser R. #317. **105**

**AND 75 FT. SOUTH OF SAME RD. &**

**DECLINATION 14 1/2° E**

**NEW REFS**

**A 5/8" X 30" I.R. / PCSO YELLOW PLST CAP PROT. 3" IN RED PAINTED MND OF STONE EAST, 90 1/2 FT.**

" / " " " " " " " " **NORTH 82° FT.**

CS 67/57-9  
 3/3