

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2973)

Set dogwood post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 sec. cor. mkd. 1/4 S on W face from which
A hemlock, 12" dia., bears N.47°E., 13 lks., mkd: 1/4 S BT.
A hemlock, 12" dia., bears N.65°W., 26 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - V.R. Tracy - 3/1968 - C.S. 54/27-150

Find Weyerhaeuser method BTs as follows:
24" Fir stump S.48°W., 43.0 ft., "W" nail & tag.
48" Fir stump N.73°W., 36.6 ft. "W" nail & tag.
No cor. monument - No trace any orig. BTs.

LOOKED FOR 2022 & 11-7-23 AGAIN
WITH GPS TIES. NO EVIDENCE.

CS 67/57-13