

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 460200

PRIMARY CORNER DESCRIPTION East 1/16 Cor. for Secs. 27 & 34.

Alias _____	Description _____	FILED Date: <u>5/7/2024</u> By: <u>JC</u>
Alias _____	Description _____	This survey consists of: _____
Alias _____	Description _____	Map: _____
Alias _____	Description _____	Narrative: _____

Corner Rpt: CS 67/57-55

New Accessories:

11" dia., D.Fir scribed E 1/16 CS BT bears N.202° E., 59.0 ft.

The BLM split pipe monument with cap was dug up by this office. It will be reset in a monument box in the road when it is paved at the end of summer 1985. We set two iron rods on line with BTs using theodolite and meas. angle between trees. Fence corner post, 1" x 1" x 7', bears N.70°W., 1.5 ft. from corner.

DOUGLAS COUNTY SURVEYOR

FOUND OK 5/2/24

Douglas Co. Surveyors Office - Randall Smith and Stephen Elause, crew - April 20, 1988 - C.S. File 62/52

(Recent realignment of Co. Rd. #36 has caused removal of all previous monuments)

Found - One BT originally recorded in Wenderoth survey. A record 10" dia., ^{23"} Pine now a 14" DBH Ponderosa Pine with a fully healed double blaze, bears N.72 3/4°E., 91.1 ft. **BLAZE NOT VIS.**

NW. Madrone BT removed during road alignment.

^{18"} - An ~~11"~~ dia. D.Fir now a 12" DBH D.Fir with a partially healed double blaze with the scribing **FH DB** - "E 1/16 CS BT" visible, bears N.28 1/2°E., 59.0 ft.

A 5/8" dia. Iron rod with an alum. cap stamped "BO" 1" set flush with ground bears N.28 1/2°E., 53.38 ft.

A 5/8" dia. Iron rod with a alum. cap stamped "BO 2" 4" set ~~3"~~ below ground bears N.72 3/4°E., 59.89 ft.

We reestablish corner at referenced position by intersection distances and bearings recorded to bearing objects. The measured angle between the bearing objects is checked from the corner position and is found to agree with record. The reestablished corner position now falls in asphalt, so top of spike is set flush with surface. ~~Top of boat spike is marked~~

"E 1/16 27/34" SPIKE GONE DUE TO RD. RESURFACING

New Accessory:

A 3" dia. Doug. Co. Public Works Dept. disk stamped "GR 5 BM" is set in a 6" I.D. concrete filled plastic pipe protruding ~~2"~~ above ground bears N.88 1/2°E., 51.78 ft. **NOW FLUSH**

FORMER Location in West bound lane of Co. Rd. #36 near easterly end of Galesville.

ALL ACCESSORIES FOUND IN GOOD CONDITION, DID NOT CHECK BEARINGS AND DISTANCES

C.S. FILE 67/57-55