

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36: 1 & 2 **FILED** 1726-8

Date: 5/14/2024 By: Y

Alias _____
Alias _____
Alias _____
Alias _____

Description _____
Description _____
Description _____
Description _____

This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: CS 67/57-56

DOUGLAS COUNTY SURVEYOR

from which the remains of the original bearing tree
A root hole bears N.25°E., 62 lks. dist., with a down Fir alongside, 38" dia., no marks remaining.
A Chinquapin snag 17" dia., bears S.50°E., 21 lks. dist., with opened and decayed blaze.
A Fir snag 40" dia., bears S.50°W., 22 lks. dist. with fragmentary scribe marks visible on bark blaze.
A Madrone 22" dia., bears N.35°W., 14 lks. dist. no marks visible.
and bearing trees mkd. by Jelley in 1964
A Fir 18" dia., bears N.38°E., 42 lks. dist. with healed blaze.
A Fir 18" dia., bears S.84¼°E., 57 lks. dist., with healed blaze.
A Fir 10" dia., bears S.37½°W., 84 lks. dist., with healed blaze.
A Fir stump 8" dia., bears N.30°W., 75 lks. dist., with healed blaze.
and a new bearing tree:
A Fir 25" dia., bears N.44°W., 50 lks. dist., mkd. T25S R8W S35 BT.

Survey by Mark Smalley - For: Roseburg Forest Products - April 22, 1996 - C.S. File 65/8-5

Found - 1964 Cadastral brass cap/iron pipe.
22" dia. Fir, N.38°E., 42 lks., good condition, healed face.
21" dia. Fir, S.84¼°E., 57 lks., good condition, healed face.
New BTs- 8" dia. Fir, N.10°W., 30.0 ft. scribed "S35 BT"
6" dia. Hemlock, S.71°W., 18.9 ft. scribed "S2 BT"

FOUND OK MAY 9th 2024

Brent Knapp - Crew: N. Fromdahl, J. Ogden, & W. Keady - 5/1/2023 - C.S. File 65/111-57

Condition report

Found - Brass Cap (properly mkd)
✓ 25" D Fir, N.38°E., 27.7'; Healed scar & tag ✓
✓ 23" D Fir, S.84¼°E., 37.6'; Healed scar & tag ✓
✓ 17" D Fir, N.10°W., 30.0'; Healed scar & tag ✓
~~9" Hemlock, S.71°W., 18.9'; Healed scar & tag~~
~~Rotten stump, N.44°W., 33'~~

Note - 15°E Compass Declination

DECLINATION 14 1/2°E

OCCAS CANYONVILLE COTTAGE GROVE COORDS

186752.7389 N

91900.8510 E

C.S. FILE 67/57-56

SINGLE SAWN 18"x1 1/2" STUMP 17" D. FIR, N.10°W., 30.0'; HEALED SCAR & TAG GONE DUE TO LOGGING