MAY 9th 2024

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 700669

PRIMARY CORNER DESCRIPTION NW Cor. S6, T26-1E; SW Cor S31, T25½-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9549)

Intersect the Willamette Meridian, 47.75 chs. N.0°04'E., of the ¼ sec. cor. of sec. 1 only, (T26-1W). At point of intersection, Set an Iron post 3 ft. long, 3" dia., 16" in the ground to bedrock, supported in a mound of stone, with a 4 ft. base, 1 ft. high, for the closing Tp. cor. of Tps. 25½ and 26 S., R1E. with brass cap marked:

T26S T25½S
R1W R1E
S 1 S 31 / S 6 CC
T26S
1928

from which

A Fir 10" dia., bears N.17°E., 62 lks. dist. mkd. T25½ R1E S31 CC BT.

An Oak 4" dia., bears S.89°E., 41 lks. dist. mkd. T26S R1E S6 CC BT.

MINI GIS
43.34350
122.75560

MONUMENT NOT FOUND; USING MEASURED TIES TO THE WEST 1/4 CORNER OF SECTION 6, THE SECTION CORNER 73.23 CHAINS EAST AND GPS POSITIONING, NO CORNER EVIDENCE IS FOUND IN THE DETERMINED SEARCH AREA.

FILED
Date: 5/14/2024 By: X
This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: CS 67/57-57
DOUGLAS COUNTY SURVEYOR

C.S. FILE 67/57-57