

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 255 RANGE 1W SEC. 23

PLSS # 600300

Date: 5/21/2024 By: X  
This survey consists of:

Map: \_\_\_\_\_

DOUGLAS COUNTY OREGON

DATE 5-14-24

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/57-59

Corner Designation

Sec Cor 23/24  
26/25

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

\_\_\_ Condition report

1963 USPC 2 1/2" Alum

\_\_\_ Not Found

Cap on Iron Pipe

Renewed

4P 4"

\_\_\_ Unrecorded

Previous Renewals

\_\_\_ Surveyed In

DCSO 1962 CS 52/30-13

Shrum 1963 CS 51/254-2

DCSO 1962 CS 52/30-34A

M<sup>c</sup>Mahan 2020 M1 177-50

MONUMENT DETAIL

USPC Property Co

T255 R1W

23/24

26/25

RE 4287

Accessories Found

9" Hemlock S43°E 7.2 FT Fully Healed  
Double BLAZE ADD 3 1/2" MAG NAIL RIGHT  
Side Center

28" White Fir N35°E 12.5 FT Healed FACE  
ADD 3 1/2" MAG NAIL RIGHT Side Center

13" Hemlock N63°E 17.0 FT Healed Single  
BLAZE ADD 3 1/2" MAG NAIL RIGHT Side Center

28" I. Cedar S88°W 28.5 FT Partially Healed  
Single BLAZE T255 R1W 526 BT Visible  
ADD 3 1/2" MAG NAIL RIGHT Side Center

C.S. File 67/57-59

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

---



---



---



---



---



---

New Accessories

---



---



---



---



---



---



---



---



---



---

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS COORDINATE SYSTEM  
 Cottage Grove - Canyonville  
 Zone

N 199369.107  
 E 316128.316

---



---



---



---



---



---

Comp. Decline. 14 1/2° E  
 Agency DGGO  
 Party Chief S. F. RAUSE  
 Note keeper  
 Witnesses J. LORENTZ



EXPIRES: 12/31/2024

CS 67/57-59  
 2/4

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3509-10)

Set a basalt stone, 18x8x6", 12" in the ground for cor. of secs. 23, 24, 25, & 26, & marked with 2 notches on S & 1 notch on E edges, from which

- A fir 10" dia. bears N.35°E., 19 lks. mkd: T25S R1W S24 BT
- A hemlock, 5" dia., bears S.43°E., 11 lks., mkd: T25S R1W S25 BT.
- A hemlock, 5" dia., bears S.75°W., 15 lks., mkd: T25S R1W S26 BT.
- A hemlock, 6" dia., bears N.61°W., 22 lks., mkd: T25S R1W S23 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, Chainman - Oct. 1962 - C.S. File 52/30-13

Found -  $\frac{3}{4}$ " Iron Reinforcing Rod, no record.  
Did not find rock called for in Gov't Notes  
All Orig. BTs alive & standing vis:  
5" Hemlock, now 8", S.75°W. 9.9 ft. Prev. opened & scribing vis.  
6" Hemlock, now 8", N.61°W. 14.5 ft. shows good scar  
5" Hemlock, now 5", S.43°E. 7.3 ft. shows good scar.  
10" W.Fir, now 17", N.35°E. 12.5 ft., shows 2 good scars.

Corner & BT's. in good condition. Corner lies on E. slope approx. 150 ft. West of S end of bridge on Canton Creek Road. This corner found by Godfrey and Crew & everything checked so is a good corner but never has been recorded.

Thomas E. Shrum, Jr. by U.S. Plywood Corp. - Jan. 1963 - C.S. File 51/254-2

Found - Original Stone (broken)  
18" D.Fir, N.35°E., 12.5 ft.  
6" Hemlock, S.43°E., 7.3 ft.  
10" Hemlock, S.75°W., 9.9 ft.  
11" Hemlock, N.61°W. 14.5 ft.  
Set - 2½" Aluminum Cap.

*FND OK 5/14/24*

Fd. Ok by DCSO V.R. Tracy - 10/1962 - C.S. file 52/30-34A

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-50

~~PROPERLY-MARKED-PROT-4"~~  
Found - 1963 USPC 2½" Alum cap on iron pipe  
BTs - 9" 12" Hemlock, bears S.43°E., 7.2 ft "healed face" ✓  
continued next page

*FULLY HEALED DOUBLE BLAZE*

*CS 67/57-59<sup>1</sup>  
3/24*

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

*DECLINATION 141/4° E*

$\checkmark$  28" ~~W~~ Fir bears N.35°E., 12.5 ft "healed face"  $\checkmark$   
 BTs (No record found) -  
 13" ~~14~~ Hemlock bears N.63°E., 17.0 ft "healed face"  $\checkmark$  S.B.  
 28" ~~30~~ Cedar bears S.88°W., 28.5 ft "healed face" *PARTIALLY HEALED*  
*SINGLE BLZ "T25SRIWS26BT" VISIBLE*

*OGRS CANYONVILLE COTTAGE GROVE COORD.S*  
*199369.107 N*  
*316128.316 E*

*CS 67/57<sup>2</sup>-59  
4/4*