

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 253 RANGE R1W SEC. 6 PLSS # 140660

Date: 5/21/2024 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-15-24

Map: _____

Narrative: _____

Corner Rpt: CS 67/58-2

Corner Designation

S.E. COR Lot 3 Sec 6

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" Alum CAP ON IRON
ROD UP 3"

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

Established By EDWARDS
M 156-53

MONUMENT DETAIL

S.E. COR
Lot 3
56
LS 2339
2008

Accessories Found

BURNED DEAD 7" R. CEDAR N 67° E 5.9 FT
All scribing visible on partly heated single
BLAZE ADD 3 1/2" MAG NAIL RIGHT Side Center

BURNED SAWN 13" X 1 FT TALL FIR STUMP
562° W 8.2 FT EVIDENCE OF SCAR ADD
3 1/2" MAG NAIL TOP Center

C.S. File 67/58-2

Horizontal lines for Monument Set description.

New Accessories

Horizontal lines for New Accessories description.

Sketch of Monument, Accessories, and General Area

Location & Comments

MON 1: 3FT SOUTH OF TOP OF HIGH CUT BANK ON SOUTH SIDE OF DIRT LOGGING ROAD

AREA BURNED
9/2020

OGRS COORDINATE SYSTEM
COTTAGE GROVE - CANYONVILLE
ZONE

Comp. Decline 14 1/2° E
Agency DCGO
Party Chief S. F. WISE
Note keeper
Witnesses J. L. OSUNA

N 219235.134

E 292250.546

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/58-2
213

Map: H156-53
Narrative
Corner Rpt.
DOUGLAS COUNTY
SURVEYOR

LOCATED in Section 6, T. 25 S., R. 1 W., W.M.
in Douglas County, Oregon.

August 11, 2008

SURVEYED FOR: SENECA JONES TIMBER CO.
P.O. BOX 2129
ROSEBURG, OREGON 97470

AND

ROSEBURG RESOURCES CO.
P.O. BOX 1088
ROSEBURG, OREGON 97470

SURVEYED BY: DAVID EDWARDS LAND SURVEYING
P.O. BOX 361
OAKLAND, OREGON 97462
PHONE: (541) 459-0512

REGISTERED
PROFESSIONAL
LAND SURVEYOR
David A. Edwards
011910
DAVID A. EDWARDS
2339
RENEWS 727-31709

INDICATES BOUNDARY BLAZED AND POSTED THIS SURVEY.

LEGEND

- INDICATES B.L.M. OR COUNTY SURVEYOR BRASS CAP FOUND.
- INDICATES 5/8" X 3/32" STEEL REBAR WITH 2 1/2" DIAM. ALUM. CAP STAMPED WITH "LS 2339" AND "2008" AND GOVT LOT DATA AS NOTED IN NARRATIVE.
- () DENOTES B.L.M. RECORD DATA.

F.P. = PROPORTIONATE POSITION.

SCALE: 1" = 600'

BASIS OF BEARINGS; B.L.M. RESURVEY AS SHOWN

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO MARK THOSE BOUNDARIES SHOWN AS BOLD LINES AND TO MONUMENT CERTAIN GOVT. LOT CORNERS AS SHOWN HEREON. THE BOUNDARIES WERE MARKED BY BLAZING TREES ON EACH SIDE OF THE LINE, BY SETTING 6 FOOT STEEL POSTS ALONG THE LINES AT INTERVALS OF 200' OR LESS AND BY HANGING LIBERAL AMOUNTS OF RED FLAGGING ALONG TRUE LINE. ALL FOUND BEARING TREES HAVE A HEALED BLAZE.

FOR CORNERS SET THIS SURVEY THE CAP MARKINGS AND BEARING TREES ARE AS FOLLOWS:

AT THE NE CORNER GOVT. LOT 6 CAP IS STAMPED "NE COR. LOT 6 56"

A 7" DIAM. FIR BEARS S.27°E., 21.3 FEET.

A 4" DIAM. FIR BEARS S.46°W., 10.8 FEET.

BOTH SCRIBED "NE L6 S6 BT"

AT THE NW CORNER GOVT. LOT 3 CAP IS STAMPED "NW COR. LOT 6 56"

A 10" DIAM. FIR BEARS S.54°W., 19.6 FEET.

A 10" FIR BEARS S.84°W., 13.4 FEET.

BOTH SCRIBED "NW L3 S6 BT"

AT THE SE CORNER GOVT. LOT 3 CAP IS STAMPED "SE COR. LOT 3 56"

A 10" DIAM. FIR BEARS S.27°E., 21.3 FEET.

A 10" FIR BEARS S.84°W., 13.4 FEET.

BOTH SCRIBED "SE L3 S6 BT"

AT THE SW CORNER GOVT. LOT 3 CAP IS STAMPED "SW COR. LOT 3 56"

A 14" DIAM. FIR BEARS N.66°E., 21.4 FEET.

A 5" DIAM. CHINQUAPIN BEARS S.27°W., 5.9 FEET.

BOTH SCRIBED "SW L3 S6 BT"

AT THE SE CORNER GOVT. LOT 6 CAP IS STAMPED "SE COR. LOT 6 56"

A 12" DIAM. FIR BEARS N.4°E., 7.9 FEET.

A 10" DIAM. FIR BEARS S.27°E., 21.3 FEET.

A 10" FIR BEARS S.84°W., 13.4 FEET.

BOTH SCRIBED "SE L6 S6 BT"

AT THE SE CORNER GOVT. LOT 11 CAP IS STAMPED "SE COR. LOT 11 56"

A 5" DIAM. FIR BEARS S.69°E., 14.9 FEET.

A 4" DIAM. FIR BEARS S.7°W., 18.8 FEET.

BOTH SCRIBED "SE L11 S6 BT"

AT THE SE CORNER GOVT. LOT 21 CAP IS STAMPED "SE COR. LOT 21 56"

A 6" DIAM. HEMLOCK BEARS N.28°E., 15.2 FEET.

A 3" DIAM. CEDAR BEARS S.79°E., 23.1 FEET.

BOTH SCRIBED "SE COR. LOT 21 56 BT"

FIELD CREW: BRANT MILLER, ERIC SPRINKLE, CHRIS EDWARDS AND SULLIVAN EDWARDS.
EQUIPMENT: NIKON TOTAL STATION.

COMPUTATIONS AND DRAFTING: DAVID EDWARDS.

31 1075
219235.136 N
292250.546 E
SE LOT 6
21922312 N
27890.843 E
OAS CAMPVILLE COTTAGE GROVE COARDS

1/4 CORNER SEC. 31 ONLY
34" FIR SNAG N.44°W, 41.6"
17" FIR N.43.74°E, 24.4"
SET 6" STEEL POST 2' NORTH

1/4 CORNER SEC. 6 ONLY
24" FIR S.331/2°E, 31.7"
15" FIR S.471/2°W, 33.7"

