

JUST AT BEGINNING  
CANTON CRK.

TOWNSHIP 25 1/2 RANGE 01E POINT IDENTIFIER # 222200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31 (S); only T25-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9143)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. of sec. 31 only, with brass cap marked

1/4 S 31  
1927

from which

A fir, 8" dia., bears N.25°E., 96 lks., mkd: 1/4 S31 BT.

A fir, 6" dia., bears N.75°W., 21 lks., mkd: 1/4 S31 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & D. West - March/April 1967 - C.S. File 52/30-74

Found - 1927 US GLO Brass Cap properly marked & BTs as follows:

8", now 9" Fir Stump, N.25°E. 63.1 ft., shows "BT" scribe on unhealed blaze.

6", now 9" Fir, Alive, N.75°W. 13.9 ft., shows good scar. Don't open,

New BT - 7" D.Fir N.58°E. 16.9 ft. mkd. 1/4 S31 CS BT.

Note - This corner lies 100 ft. N. of Canton Creek Access Road.

FILED

Date: 7/18/24 By: X  
This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_  
Corner Rpt: CS 67/58-24

DOUGLAS COUNTY  
SURVEYOR

May 2024

no renewal -  
OCRS only

104802.621

206523.465

C.S. FILE 67/58-24

OCR -

~~10480.2621 N, 20652.3465 E~~

MINI GIS  
#3.34989  
122.73164