

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 255 RANGE 2W SEC. 13

PLSS # 640440

Date: 7/22/2024 By: X

This survey consists of:

DOUGLAS COUNTY OREGON

DATE 7-15-24

Map: _____

Narrative: _____

Corner Rpt: CS 6758-25

Corner Designation

C 1/4 S13

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

3 1/4" BLM BRASS CAP ON
2" IDIA UP 6"

Condition report

Not Found

Renewed

Unrecorded

Surveyed In

Previous Renewals

BLM Resurvey 2001-2002
Vol 54 pg 20941

MONUMENT DETAIL

T255 R2W
C 1/4
S13
2002

Accessories Found

BURNED Broken OFF 18" X 7 1/2 FT FIR
Stump S 37 1/2° E 18.8 FT (Rec S 35 1/2° E 18.3 FT)
Partly Healed Single BLAZE FACE BURNED
AWAY 2 1/2" MAG NAIL FD RIGHT Side Center

BURNED Broken OFF 22" X 6 1/2 FT FIR Stump
N 75 1/2° W 42.3 FT PARTLY Healed Single
BLAZE FACE BURNED AWAY FD 2 1/2"
MAG NAIL RIGHT Side Center

New Accessories

5/8" x 30" Iron Rod with DCSO plastic
CAP proj 22" From 38" x 2 FT Cedar
Stump N 65 1/2° W 11.0 FT

5/8" x 30" Iron Rod with DCSO plastic
CAP up 6" S 13° E 7.5 FT

Sketch of Monument, Accessories, and General Area

Location & Comments

MON. IS BURNED REPROD ON
SMALL BENCH AT BASE OF
STEEP NORTH SLOPE

MON IS ~ 200 FT
SOUTH OF GRAVEL
ROAD

AREA BURNED
9/2020

OCRS COORDINATE SYSTEM
COTTAGE GROVE - CANYONVILLE
ZONE

Comp. Decline. 14 1/2° E
Agency DCSO
Party Chief S. F. HAUSE
Note keeper
Witnesses J. LORSUNY

N 205154.581

E 283373.551

CS 67/58-25
2/3

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 640440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 13

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

RENEWED 7/15/24

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page(s) 20941)

DECLINATION 14° 14' E

Point for the center 1/4 sec. cor. of sec. 13, at the intersection with the E. and W. centerline. Set a stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd.

T25S R2W
C 1/4
S 13
2002

3 1/4" BC / 2" DIP PROT. 6"

from which

A fir, 16" dia., bears S. 35 1/2° E., 18.7 ft., mkd. C 1/4 S13 BT

A fir, 19" dia., bears N. 75 1/2° W., 42.3 ft., mkd. C 1/4 S13 BT " " "

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Each new bearing tree has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.

BURNED
BROKEN
OFF

MINI GIS
43.39485
122.88431

18" x 7 1/2" STUMP
22" x 6 1/2" STUMP

37 1/2° 188

PHSB FACE BURNED AWAY

NEW REFS

5/8" x 30" IR / DCSO PLSTZ CAP SET PROT. 22" FROM 38" x 2 FT TALL CEDAR STUMP, N 65 1/2° W, 11 FT

" " " " 6" ABOVE GROUND S 13° E, 7 1/2 FT.

MONUMENT IN BURNED REPROD ON SMALL BENCH AT BASE OF STEEP NORTH SLOPE. MON. IS ~200 FT. SOUTH OF GRAVEL RD.

OCRS CANYONVILLE COTTAGE GROVE COORD.S
205154.581 N
283373.551 E

CS 67/58-25
3/3