

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 259 RANGE 3W SEC. 12 PLSS # 700520

Date: 7/25/2024 By: X
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 7-18-24

Map: _____
Narrative: _____
Corner Rpt: CS 67/58-30

Corner Designation

5 1/16 S 12 ON 1/4

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

BLM BRASS CAP BENT
SOUTH AND LOOSE STRAIGHTEN
AND RETACH BRASS CAP - Project 4"
Previous Renewals cap now oriented south

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

JULIANO 1977 M 68-32
BLM RESURVEY 2010
Vol 57 pg 22789

MONUMENT DETAIL

5 1/16
S 12
2010

Accessories Found

PARTLY BURNED AWAY 10" X 3 FT FIR STUMP
N 14 3/4° E 33.9 FT - SPIKE GONE, FACE GONE
BROKEN - BURNED ROOTS N 35 3/4° W 16.0 FT
SPIKE LOOSE ON EXPOSED ROOT

BURNED - SAWN 10" X 1 FOOT FIR STUMP
S 34° W 16.5 FT SCRIBES VISIBLE IN REMAINING
BLAZE

BURNED - SAWN 24" X 1/4 FT CEDAR STUMP
N 66 1/4° W 13.6 FT NO BLAZE REMAINS

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

BURNED SAWN 32" X 2 1/2 FT Hemlock Stump
S 80°W 15.7 FT 3 1/2" MAG Nail Top Center

BURNED-SAWN 24" X 1 1/2 FT Hemlock Stump
N 5°W 18.9 FT 3 1/2" MAG Nail Top Center

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS COORDINATE SYSTEM
Cottage Grove - Canyonville
Zone

N 209245.911
E 255335.725

MON ON GENTLE
EAST SLOPE IN LARGE
CLEAR CUT GRAVEL
ROAD 150' FT WEST

AREA BUILT

9/2020

Comp. Decline. 14 1/4 °E

Agency DCSD

Party Chief S. F. HAUSE

Note keeper

Witnesses J. LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/58-30
2/3

UO 157
22789

Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	A decayed hemlock stump, size indeterminate, bears N. 15° W., 11.2 ft. dist., with no marks visible.
	and the remains of bearing trees mkd. by Price
	A fir, 38 ins. diam., bears S. 56 1/2° W., 31.0 ft. dist., with a healed blaze.
	A sawed fir stump, 23 ins. diam., bears N. 53 1/2° W., 24.4 ft. dist., with fragmentary scribe marks visible on a burnt, partially healed blaze.
	and a bearing tree mkd. by the Douglas County Surveyor's Office
	A fir, 11 ins. diam., bears S. 10 3/4° W., 9.1 ft. dist., with a healed double blaze.
	and a new bearing tree
	A hemlock, 7 ins. diam., bears N. 41° W., 42.8 ft. dist., mkd. T25S R3W S12 BT. <i>COORDS CANYONVILLE COTTAGE GROVE COORD.S</i> <u>209245.911 N, 255335.725 E</u>
	N. 0° 45' 38" E., bet. secs. 7 and 12, posting and blazing. <i>RENEWED 7/18/24</i>
1324.97	The S 1/16 sec. cor. of sec. 12 only, T. 25 S., R. 3 W., established by Nick Juliano, Oregon PE No. 3449, in 1977, and is accepted as the cor., monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 9 ins. above the ground, from which the remains of bearing trees mkd. by Juliano <i>DECLINATION 14 1/4° E</i>
<i>PARTIALLY BURNED AWAY 10" X 3 FT</i>	A sawed, decayed fir stump, 43 33.9 ins. diam., bears N. 14 3/4° E., 33.9 ft. dist., with a railroad spike in the face and axe marks visible on a partially healed blaze. <i>SPIKE GONE, FACE GONE</i>
<i>ONLY BROKEN BURNED ROOTS REMAIN</i>	A sawed, decayed hemlock stump, 32 16.0 ins. diam., bears N. 35 1/4° W., 16.0 ft. dist., with a railroad spike at the base and no marks visible. <i>SPIKE LOOSE ON EXPOSED ROOT</i>
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd. <i>PROT. 4"</i>
	<i>FOUND TILTED SOUTH ≈ 1 FT OFF FROM PLUMB, BRASS CAP BENT AND LOOSE. REPLUMB PIPE AND RE-ATTACH. B.C.</i>
	from which
	<i>BURNED SAWN 10" X 1 FT. STUMP</i> A fir, 7 ins. diam., bears S. 34° W., 16.5 ft. dist., mkd. S 446 S42 BT. <i>S 446 S42 BT. VISIBLE IN REMAINDER OF BLAZE</i>
	<i>BURNED SAWN 24" X 1/4 FT STUMP</i> A cedar, 14 ins. diam., bears N. 66 1/4° W., 13.6 ft. dist., mkd. S 446 S42 BT. <i>NO BLZ. REMAINS</i>
	<u>NEW REFERENCES A 3 1/2" MAG NAIL SET IN TOP CNTR OF FOLLOWING</u>

T 25-3
100520

M 68-32

PARTIALLY BURNED AWAY 10" X 3 FT
ONLY BROKEN BURNED ROOTS REMAIN

BURNED SAWN 10" X 1 FT. STUMP
BURNED SAWN 24" X 1/4 FT STUMP

ABURNED, SAWN 32" X 2 1/2 FT. TALL HEMLOCK STUMP BEARS S 80° W, 15 FT.
" " 24" X 1 1/2 FT. " " " BEARS N 5° W, 18 FT.
MON. ON GENTLE EAST SLOPE IN LARGE CLEARCUT. GRAVEL RD. ≈ 150 FT. WEST

CS 67/58-30 3/3