

GOVERNMENT CORNER RESTORATION FORM

TOWNSHIP 245 RANGE 3W SEC. 21 PLSS # 320340

FILED  
Date: 9/24/20<sup>24</sup> By: X  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 8/27/24

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/58-58

Corner Designation

CW 1/16 S21

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

\_\_\_ Condition report

\_\_\_ Not Found

Renewed

\_\_\_ Unrecorded

\_\_\_ Surveyed In

2 1/2" BRASS CAP

PROF. 14"

Previous Renewals

Set by Peel 1986

per M 100-29

MONUMENT DETAIL

T245 R3W

W 1/16

C - ● - C

S21

PLS 752

1986

Accessories Found

SAWN Very Rotted 24" X 5 FT FIR STUMP  
S62°E 17.3 FT BLAZE GONE

28" D. FIR S23°W 21.7 FT (Rec S28°W  
20.8 FT) Fully Healed Single BLAZE  
ADD 3 1/2" MAG NAIL RIGHT SIDE CENTER

Metal Post with witness sign  
South 2 FT

C.S. File 67/58-58

Monument Set (Procedure and Description)

MONUMENT DETAIL

Blank lines for monument set procedure and description.

New Accessories

6" D. FIR 583°E 15.5 FT Scribed X BT  
ON Double BLAZE 3 1/2" MAG NAIL  
RIGHT side center

Sketch of Monument, Accessories, and General Area

Location & Comments

MON ON GRADUAL Northwest  
Slope in older Reprod.

MON approx 175 FT  
North of DIRT  
ROAD

OCRS COORDINATE SYSTEM  
COTTAGE GROVE - CANYONVILLE  
ZONE

AREA BURNT  
9/2020

N 231291.784

E 235022.310

Comp. Decline. 14'14"E  
Agency DCSD  
Party Chief S. FLAUBE  
Note keeper  
Witnesses J. LORSUNG



EXPIRES: 12/31/2024

CS 67/58-58  
213

1/4 CORNER 16 & 21

FOUND: 1" IRON PIPE WITH G.L.O. BRASS CAP "1980"  
18" TRIPLE MAPLE, S10-1/2W, 63.3' (CENTER MEASURE)  
30" FIR STUMP, N7-1/2W, 34.8' (FACE MEASURE)  
S.E. BT NOW UPROOTED AND DOWN

SET NEW: 13" FIR, N39-1/2E, 30.4' - SCRIBED 1/4 S16 BT (DIST. TO "W" NAIL)

M 100-29  
1986

1/4 CORNER 20 & 21

FOUND: 1" IRON PIPE WITH G.L.O. BRASS CAP "1980"  
19" FIR, N83-1/2E, 24.0' (CENTER MEASURE)  
18" FIR, S20-1/2E, 13.4' (CENTER MEASURE)  
45" FIR STUMP, S14W, 35.8' (CENTER MEASURE)

SET NEW: 16" FIR, S36W, 34.0' - SCRIBED 1/4 S20 BT (DIST. TO "W" NAIL)

OGRS CANYONVILLE COTTAGE GROVE COORD.S

231291.784 N  
235022.310 E

DECLINATION 14 1/4 °E

CENTER - WEST 1/16 SECTION 21

SAN VERY NOTED 24" X 5 FT STUMP, BLAZE GONE - 1-1/2" X 4" IRON PIPE WITH BRASS CAP  
28" D. FIR WITH FHSB BEARS S23°W, 21 FT - 20" FIR, S62E, 17.3' - SCRIBED CW 1/16 S21 BT  
ADD 3 1/2" MAG NAIL R.S.C. - 20" FIR, S60W, 20.0' - SCRIBED CW 1/16 S21 BT  
FIND A METAL LATH WITH WITNESS SIGN  
BEARS 60UTH, 2 FT

NEW REF.

6" D. FIR SCRIBED "X" BT ON DOUBLE BLZ. S83E, 15.5 FT.

3 1/2" MAG NAIL R.S.C.

1298.00'



N10°19'E, 2598.86'

2 1/2" B.C. AS BELOW

T24S R3W PROT. 16"



MONUMENT ON GRADUAL NORTHWEST SLOPE IN OLDER REPROD. APPROX 175 FT. NORTH OF DIRT ROAD.

1298.00'

N 8:

CS 67/58-58  
3/3

1/1  
FOL

NO 7