

GOVERNMENT CORNER RESTORATION FORM

TOWNSHIP 24S RANGE 3W SEC. 22

PLSS # 400328

FILED Date: 9/24/2024 By: X

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/58-60

DOUGLAS COUNTY OREGON

DATE 8-29-24

DOUGLAS COUNTY SURVEYOR

Corner Designation

S 1/16 21/22

Monument(s) Found: (Condition and Source)

2 1/2" BRASS CAP

UP 3"

Condition report

Not Found

Renewed

Unrecorded

Surveyed In

Previous Renewals

Baker 1983 M 90-48

MONUMENT DETAIL

Accessories Found

25" Hemlock S 80°E 33.7 FT (REC S 78°E 31.8 FT TO FACE) Fully Healed Single BLAZE ADD 3 1/2" MAG NAIL RIGHT Side Center

Very Rotted 30" X 6 FT Fir Stump N 123°W 24.3 FT (REC N 21°W 22.8 TO FACE) FACE Fallen OFF Scribes S 1/16 S 21/22 Visible

Steel T Post N 35° Approx 2 FT

New Accessories

5/8" x 30" Iron Rod with DCSO  
Plastic Cap N40°E 26.3 FT Set in  
East Road Shoulder up 3"

Sketch of Monument, Accessories, and General Area

Location & Comments

MON IN Old FOREST Row with  
on moderate EAST slope  
Approx 10 FT West of  
Center of N-S Gravel Road

AREA BURN  
9-2020

OCRS Coordinate System  
Cottage Grove - Canyonville  
Zone

Comp. Decline. 1474°E  
Agency DCSO  
Party Chief S. Krause  
Note keeper  
Witnesses J. Lorusong

N 229974.004  
E 238915.032



EXPIRES: 12/31/2024

CS 67/58-60

M 90-48

FILED

RECEIVED

DEC 12 1983

COUNTY SURVEYOR  
LOUISIANA COUNTY, ORE

20 C-E 1/16 CORNER SECTION 22

SET: 2" X 31" IRON PIPE WITH BRASS CAP  
18" FIR, N3E, 39.4'  
24" FIR, S80W, 9.4'  
NOTE - 1" AL. PIPE SET BY WEYER CO BEARS  
N75°41'32"E, 64.74'

21 1/4 CORNER 22 & 23

SET: 2 1/2" X 36" IRON PIPE WITH BRASS CAP  
8" FIR, N57E, 22.2'  
6" HEMLOCK, N12W, 26.6'  
NOTE - 1/2" MONEL PIPE SET BY WEYER CO BEARS  
N80°15'49"E, 82.32'

22 1/4 CORNER 23 & 24

SET: 2" X 30" IRON PIPE WITH BRASS CAP  
12" FIR, N9E, 16.5'  
11" FIR, S61W, 15.6'

O.C.R.S. CANNONVILLE COTTAGE GROVE COORDS

229974.004 N  
238915.032 E

RENEWED 3/29/24 DECLINATION 14"4E

23 S 1/16 CORNER 21 & 22

2 1/2" BRASS CAP PROPERLY MARKED AS DESCRIBE, PROT. 3" FOUND STEEL "T"  
SET: 1 5/8" X 30" IRON PIPE WITH BRASS CAP  
25" 10" HEMLOCK, S70E, 31.8' (FACE MEAS.) S80°E, 33' FHSB  
30" X 6 FT. - 30" FIR STUMP, N21W, 22.8' (FACE MEAS.) N23°W, 24.3'  
NOTE - 1" AL. PIPE SET BY WEYER CO BEARS  
GONE FALLS IN ROAD S83°39'08"E, 10.69'

POST N03°E APPROX. 2 FT.  
ADD 3 1/2" MAG NAIL R.S.C.

FALLEN OFF FACE WITH GOOD SCRIBING  
"S 1/16 S21 BT"

BEARS N40°E, 26 3/4 FT. DISTANT

24 SW 1/16 CORNER SECTION 22

SET: 1 3/4" X 36" IRON PIPE WITH BRASS CAP  
23" HEMLOCK, N51E, 37.2'  
17" FIR, S75W, 28.3'

MONUMENT IS IN OLD FOREST REGROWTH  
RAMP EAST SLOPE AND APPROX  
10 FT. WEST FROM CENTER OF N-S  
RUNNING GRAVEL SPUR ROAD.

25 SECTION CORNER 21, 22, 27, 28

FOUND: 1 1/2" IRON PIPE  
60" FIR STUMP, S41E, 30.8' (dist to "W" nail)  
60" FIR STUMP, S53W, 53.3' (dist to "W" nail)  
31" CEDAR, N67W, 56.2' (dist to "W" nail)  
SET: 14" FIR, N72E, 39.0'

CS 67/58-60

2/3