

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 29 RANGE 9 W SEC. 25 PLSS # 640200

Date: 10-2-2024 By: X

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 67/59-1

DOUGLAS COUNTY
SURVEYOR

DOUGLAS COUNTY OREGON

DATE 10/1/2024

Corner Designation

1/4 S 25
S 36

Monument(s) Found: (Condition and Source)

1 1/2" IRON PIPE PROJECTING 5" AND ISI FT. NE FROM
OLD FENCE COR. FENCES RUN N-S AND W

Condition report

Not Found

Renewed

Unrecorded

Surveyed In

Previous Renewals

DCSO, COLE, 1920 CS6/17 AND VL 3 PGS 70-71

DCSO, BYRON, 1959 CS 49/100-69

STRINGER, 1984 M97-4

MONUMENT DETAIL

Accessories Found

26"X4 FT ROTTEN SHELL OF FIR STUMP BEARS N7°15'E. 39.60 (60 LKS) SCRIBE "1/4" VISIBLE

SAWN, METAL CAP, 25"X 6 FT. D.FIR STUMP BEARS N.7°E. (REC. N.5°E) 45.0 FT. WITH FULLY HEALED DOUBLE BLAZE

A GALVANIZED "U" POST FOUND ON EAST EDGE OF I.P.

C.S. File 67/59-1

RENEWAL

Monument Set (Procedure and Description)

AT CENTER OF FOUND I.P. DRIVE 5/8"X30" I.R./2 1/2"
ALUM CAP, MARKED AS SHOWN, PROTRUDING 11"

MONUMENT DETAIL

DOUGLAS COUNTY
T29S R9W
1/4 S25
S36
2024
SURVEYORS OFFICE

New Accessories

13" K.M.X. PINE BEARS S.46°E. 35.0 FT. SCRIBED "1/4 S36" "BT" ON A DOUBLE BLAZE

9" D.FIR BEARS S.65°W. 17.6 FT. SCRIBED "1/4 S36" "BT" ON A DOUBLE BLAZE

7" I.CEDAR BEARS N.36°W. 11.4 FT. SCRIBED "1/4 S25" "BT" ON A DOUBLE BLAZE

Sketch of Monument, Accessories, and General Area

Location & Comments

MONUMENT NEAR BOTTOM OF VERY GENTLE
NORTH SLOPE IN OLD REPROD FOREST

OCRS COORDINATE SYSTEM
COTTAGE GROVE - CANYONVILLE ZONE

N 64973.294 E 62715.138

Comp. Decline. 14 1/2°
Agency DCSO
Party Chief STEPHEN FLAUSE
Note keeper
Witnesses JEFF LORSUNG

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Handwritten Signature
OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2024

CS 67/59-1

213

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6617)

Set 1/4 sec. post, from which
An Oak 30" dia., bears S.65°W., 412 lks.
A Fir 40" dia., bears S.89°W., 758 lks.
No trees on N. side of line.

J. W. Cole, Deputy Co. Surveyor - Wit: P.D. Wolford; G.A. MachHenry - Aug/Sept. 1920 - Vol. 3 Page 70-71; C.S. File 6/17; Field book 48 Page 10+

Renew corner from remains of old BTs. Set Iron pipe 1p dia., from which

*RENEWED 10/11/24
DECLINATION 14 1/2° E*

*IN SKID RD. NO EVID. A Fir 26" dia., S.72 1/2° W., 39 lks. 25 3/4
ROTTEN SHELL OF STUMP
26" x 4 FT.*

~~A Fir 16" dia., N.7°15' E., 60 lks. 39 60~~

SCRIB 1/4" VISIBLE

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Oct. 16, 1959 - C.S. 49/100-69

Found - 1 1/2" Iron pipe at corner and both BTs as recorded by Cole. The NE. now stump. 1 FT. NE FROM OLD FNC, COR. FENCES

I do not set brass cap at corner. New BT - 1 1/4" R. Fir bears N. 5° E., 45.0 ft. scribed 1/4 S25 CS

*SAWN, METAL CAP
25" x 6 FT D. FIR STUMP*

BT. FHDB

AGALVANIZED "U" POST FOUND ON EAST EDGE OF I.P.

Fd. OK, June 1984 by D. Stringer - M 97-4
Fd. OK, Feb. 1997 by D. Bentz - M 126-39

AT CENTER OF FOUND I.P. DRIVE 5/8" x 30" I.R. / 2 1/2" ALUM. CAP MARKED, PROT. 11 INCHES

NEW REFS.

13" K.M.X. PINE 1/4 S36" BT ON D.B., S46°E, 35 FT.

9" D. FIR 1/4 S36" BT ON D.B., S65°W, 176 FT

7" I. CEDAR 1/4 S25" BT ON D.B., N36°W, 114 FT.

*" DOUGLAS COUNTY"
T29 S R 9W*

*1/4 S25
S36
2024*

SURVEYOR'S OFFICE

MONUMENT NEAR BOTTOM OF VERY GENTLE NORTH SLOPE IN OLD REPROD. FOREST

*OGRS CANYONVILLE COTTAGE GROVE COORDS
64973.294 N
62715.138 E*