

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 25S RANGE 3 SEC. 32 PLSS # 300100

Date: 12/5/2024 By: JC
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 11-27-24

Map: _____
Narrative: _____
Corner Rpt: CS 67/59-18

Corner Designation

Sec Cor

T 25S
332/533
55/54
T 25S

DOUGLAS COUNTY SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" GLO BRASS CAP
10" ABOVE GROUND

___ Condition report
___ Not Found
 Renewed
___ Unrecorded
___ Surveyed In

Previous Renewals

DCSO 1930 CS 37/21
GLO Resurvey 1940 Vol 27 pg 11503
DCSO 1966 CS 64/7-40
BLM Resurvey 1987-1988
Vol 48 pg 18475
DCSO 2007 CS 67/24-46
A. DeGroot 2020 M 178-27

MONUMENT DETAIL

T 25S R 2W
- 532/533
55/54
1943

Accessories Found

59" FIR N 25°E 18.8 FT BARK BLAZE NAIL
AND BRASS WASHER IN FACE AT 16.2 FT
19" 10 FT HIGH D. FIR STUMP S 20° 14'E
19.1 FT CHARRED HEALED FACE
19" X 6 FT HIGH D. FIR STUMP S 45 1/2° W 39.1
FT HEALED CHARRED HEALED BLAZE
15" D. FIR N 59° W 21.5 FT WITH CHARRED
BLAZE
Metal T-Post 2 FT S.E
All Trees AND stumps have TAG AND
side spiked

Monument Set (Procedure and Description)

MONUMENT DETAIL

Blank lines for Monument Set description.

New Accessories

Blank lines for New Accessories description.

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS COORDINATE SYSTEM
COTTAGE GROVE - CANYONVILLE
ZONE
N 186419.395
E 234083.492

CORNER IN E-W
FENCE
AREA BURNT
9-2020

Comp. Decline. 74 1/2° E
Agency DCSD
Party Chief J. Loring
Note keeper
Witnesses



EXPIRES: 12/31/2024
26

CS 67/59-18
213

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec Cor for 32, 33; 4 & 5 of T26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A sawed Fir stump 18" dia. bears S.24°E., 67½ lks. dist., with healed blaze.
and new bearing trees:
A Fir 6" dia. bears S.21°E., 29 lks. dist., mkd. T26S R3W S4 BT.
A Fir 9" dia. bears S.45¾°W., 60 lks. dist. mkd. T26S R3W S5 BT.
A Fir 6" dia. bears N.59°W., 33 lks. dist. mkd. T25S R3W S32 BT.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 11/8/2007 - C.S. File 67/24-46

Fd. Ok, 3 live BTs.

Adam DeGroot - For: Dollens & Strader - Dec. 2020 - M178-27

Found - ✓ A 2" iron post by Price in 1943, firmly set & projecting 10" above the ground with a 2½" brass cap properly mkd per the record:
✓ A 59" D.Fir bears N.25°00'E, 18.8 ft no mks on charred bark. I bark blaze and set nail & brass washer in face at 16.20 ft (N.25°E., 24 lks) OBT
Now 10 FT HIGH STUMP - A 19" D.Fir bears S.20°45'E., 19.1 ft. w/charred healed blaze (S.21°E., 29 lks) 1988
Now 6 FT HIGH STUMP - A 19" D.Fir bears S.45°30'W., 39.1 ft w/charred healed blaze (S.45°45'W., 60 lks) 1988
✓ A 15" D.Fir bears N.59°W., 21.5 ft w/charred blaze (N.59°W., 33 lks) 1988
Note - Corner falls in E-W fence line in low intensity burn area.
BTs are alive and trunks charred 15-20 feet high

OCRS N 186419.395 , E 234087.492
ALL HAVE TAGS + SIDE SPIKED
METAL T-POST - 2 FT SE

CS 67/59-18
3/3