

LOOKED FOR NOT FOUND

12/09/24

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700644

3

700640

PRIMARY CORNER DESCRIPTION E 1/4 Cor. Sec. 1 only, T25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3591)

FILED

Date: 12/11/20 By: By: [unclear] Set Dogwood post, 3 1/2 ft. long, 3 x 4 inches, 18" in the ground, for 1/4 sec. cor. marked 1/4 S on W face, from which

This survey consists of: A Fir 6" dia., bears N.71°W., 30 lks. dist., marked 1/4 S BT.

Map: _____ A Fir 10" dia., bears S.38°E., 40 lks. dist., marked

Narrative: _____ 1/4 S BT.

Corner Rpt: CS 67/59-26

DOUGLAS COUNTY SURVEYOR

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11519)

Point for original 1/4 sec. cor. which now refers to sec. 1 only, determined by reference to the record bearing and distance from the original SE bearing tree.

At point for corner, Set an iron post, 3 ft. long, 1" dia., 18" in the ground to bedrock, and in a mound of stone to top, for 1/4 sec. cor. of sec. 1 only, with brass cap mkd. 1/4 S1|

1943

from which

A dead Hemlock 12" dia., bears S.38°E., 40 lks. dist., mkd. 1/4 S BT. I obliterate the marks on this old bearing tree.

A Fir 42" dia., bears S.7°W., 61 lks. dist., marked 1/4 S1 BT. (New BT)

A Hemlock 8" dia., bears N.75°W., 16 lks. dist., mkd. 1/4 S1 BT. (New BT)

Doug. Co. Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June/July 1966 - C.S. File 54/27-177

Found - GLO brass cap mkd. "1/4 S1/1943" bent over. Straighten & reset in mound of stone.

NW BT gone, stumps of SE & SW BTs remain.

New BT - 12" Fir, snag 15 ft. high N.73°W., 39.4 ft. mkd. 1/4 S1 CS BT.

No live trees available. Corner lies on very steep, N. slope, 10 ft. N. of rock face 6.0 ft. high x 25 ft. long, course E & W.

LOGGED, BURNED, VERY STEEP CHECKED WIDLEY WITH PIN FINDER

C.S. FILE 67/59-26