

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 360200

PRIMARY CORNER DESCRIPTION East 1/16 Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

V.W. Hosford - Dec. 1953 - C.S. File 40/110

Set - 3" Hemlock post for corner.

A Hemlock, 10", bears N.85°E., 5.0 ft., mkd: 1/16 S28 PS 253 BT.

A Fir, 16", bears N.88½°W., 17.3 ft., mkd: 1/16 S28 PS 253 BT.

V.W. Hosford - Sept. 1957 - C.S. File 42/306

At the E 1/16 S28 & 33, the BTs marked in my survey of 1953 are in good condition. At the true point of the corner I drove a 1½" iron pipe 30" long 18" in the ground.

LOOKED FOR WITH A SINGLE GPS TIE FROM THE
EAST CENTER 16th. ALL TREES TO THE
NORTH HAVE BEEN LOGGED. NO TRACE OF
THE HOSFORD I.P.

12/23/2024

FILED
Date: 12/2025 By: X
This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: CS 67/59-34
DOUGLAS COUNTY
SURVEYOR

CS 67/59-34