

TOWNSHIP 32S RANGE 9W SEC. 9

PLSS # 400500 Date: 6/3/25 By: ke

This survey consists of:

DOUGLAS COUNTY OREGON

DATE 5-29-25

Map: _____

Narrative: _____

Corner Rpt: CS 67160-33

Corner Designation

59 | 510
516 | 515

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

Condition report

2 1/2" G L O BRASS CAP

Not Found

proj 9"

Renewed

Unrecorded

Previous Renewals

Surveyed In

DCSO 1967 CS 54/44-23

MONUMENT DETAIL

T32S R9W

59 | 510
516 | 515

1917

Accessories Found

40" D. FIR N14°E 174.2 Fully Healed
Single BLAZE (Dist. Not checked)

50" D. FIR S44°E 35.6 FT Fully Healed
Single BLAZE ADD 3 1/2" MAG NAIL RIGHT
Side Center

46" D. FIR S70°W 71.3 FT Fully Healed
Single BLAZE (Dist. Not checked)

33" Double Trunk D. FIR N48°W 164.3 FT
Fully Healed Single BLAZE (Dist not checked)
9" CHINGUAPIN N6°E 14.3 FT FACE Rotted
ADD 3 1/2" MAG NAIL RIGHT Side Center

24" D. FIR N61°W 38.6 FT Fully Healed
Double BLAZE ADD 3 1/2" MAG NAIL RIGHT
Side Center

Monument Set (Procedure and Description)

MONUMENT DETAIL

Blank lines for Monument Set description.

New Accessories

Blank lines for New Accessories description.

Sketch of Monument, Accessories, and General Area

Location & Comments

MON ON Bench Ground in
Very old Reprod OFFIR AND
Chinquapin

MON APPROX 200' +
WEST OF GRAVE 1
ROAD

OCRS COORDINATE SYSTEM
Cottage Grove - Canyonville
Zone

Comp. Decline. 14 1/2° E
Agency DCSO
Party Chief S. F. Fause
Note keeper
Witnesses J. Loring

N 12855.100
E 50852.356

CS 67/60-33

pg 2/3



EXPIRES: 12/31/2026

MINI GAS
42.79738
123.75572

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description <u>OCCS CANYONVILLE COTTAGE GROVE CO. RD. S</u>
Alias _____	Description _____

-12855.100 N
50952.356 E

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8899-8900)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd

T32S	R9W
S 9	S 10 ✓
S 16	S 15
1917	

from which

- A fir, 36" dia., bears N.14°E., 264 lks., mkd: T32S R9W S10 BT.
- A fir, 40" dia. bears S.44°E. 54 lks. mkd: T32S R9W S15 BT
- A fir, 36" dia. bears S.7°W. 108 lks. mkd: T32S R9W S16 BT
- A fir, 16" dia. bears N.48°W. 249 lks. mkd: T32S R9W S9 BT

RENEWED 5/29/25

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-23

Found ^{2 1/2"} GLO Brass Cap, 1917, properly marked at corner. ^{PROF. 9" MARK AS ABOVE} DIST. NOT CHK'D TO MANY TREES ON LINE

- 40" - 36", now 40" D Fir, N.14°E ✓ 174.2 ft. shows good scar. FHSB
- 50" - 40", now 48" D Fir, S.44°E ✓ 35.6 ft. shows good scar. FHSB
- 46" - 36", now 46" D Fir, S.7°W ✓ 71.3 ft. shows good scar. FHSB
- 33" - 16", now 27" D Fir, N.48°W ✓ 164.3 ft., shows fair scar. FHSB
- New BTs 7" 7" Chinquapin ✓ N.6°E ✓ 14.3 ft. mkd. T32S R9W S10 CS BT PH 18 FAKE ROTTEN
- 24" 8" D. Fir ✓ N.61°W ✓ 38.6 ft. mkd. T32S R9W S9 CS BT. FHSB

33" NOW SE PART OF DOUBLE TRUNK TREE

DECLINATION 14 1/2° E

ADD 3 1/2" MAG NAIL R.S.C. TO SE OBT AND 2 NEW IN 67 BT'S NAILS SET AT RECORD DIST.S

MONUMENT ON BENCH GROUND IN VERY OLD REGROWTH OF FIR AND CHINQUAPIN MONUMENT IS APPROX. 200 FT. WEST FROM GRAVEL RD.

23 5
12 8
36 4