

TOWNSHIP 32S RANGE 9W SEC. 9

PLSS # 340500

Date: 6/11/25 By: ke

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: CS 67160-38

DOUGLAS COUNTY OREGON

DATE 5/27/25

DOUGLAS COUNTY
SURVEYOR

Corner Designation

1/4 COR 9/16

Monument(s) Found: (Condition and Source)

2 1/2" GLO BRASS CAP
Flush with Ground

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

DC SO 1967 CS 54/44-10
BRANDT 1972 CG 55/257-2

MONUMENT DETAIL

1/4 59
516
1917

Accessories Found

29" Hemlock N34°E 12.3 FT (REC 11.8 FT)
(ORIG. DIST TO FACE) ADD 3 1/2" MAG NAIL
RIGHT SIDE CENTER

39" Hemlock S37°31'E 32.0 FT (REC 31.27
TO FACE) ADD 3 1/2" MAG NAIL RIGHT SIDE
Center

New Accessories

5" Chingwapid S63°W 4.3 FT Scribed
"X" BT on Double BLAZE 3 1/2" N114°
NAIL RIGHT SIDE CENTER

4" Chingwapid N41°W 11.1 FT Scribe
"X" BT on Double BLAZE 3 1/2" N114°
NAIL RIGHT SIDE CENTER

Sketch of Monument, Accessories, and General Area

Location & Comments

Mon on moderate N.W slope
Large old trees south old
Smaller Regrowth to North

Mon's approx
200 FT East of
Gravel Road

OCRS Coordinates
Cottage Grove - Canyonville
Zone

Comp. Decline. 14 1/2° E
Agency DCSO
Party Chief S. F. Huse
Note keeper
Witnesses J. Loring

N-12794.586
E 48031.139

CS 67/60-38 pg 2/3

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description <u>DCRS CANYONVILLE COTTAGE GROVE COORDS</u>
Alias _____	Description _____

MINI GIS
42.79734
123.76555

712794.586N
48031.138E

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8907)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S \ 9}{S \ 16}$
1917

from which

- A hemlock, 5" dia., bears N.85°E., 22 lks., mkd: 1/4 S9 BT.
- A fir, 24" dia., bears S.72°W., 36 lks., mkd: 1/4 S16 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/44-10

Found - GLO Brass Cap at Cor., 1917, properly marked.
 5", now 9" Hemlock Stob, N.85°E. 16.1 ft. (Record 14.5 ft.) scribe visible "S9 BT".
 24" D.Fir, now 30" Stob, S.72°W. 25.8 ft. (Record 23.8 ft.) shows scar.
 New BTs- 14" Hemlock N.34°E. 11.8 ft. mkd. 1/4 S9 CS BT.
 16" Hemlock S.53°E. 12.0 ft. mkd. 1/4 S16 CS BT.

RENEWED 5/27/25

Ronald A. Brandt - For: Robert Dollar Co. - 6/19/1972 - C.S. File 55/257-2

Found - Brass Cap, set 1917 by GLO, 12 3/4 ft 2 1/2" GLO CAP MARKED AS REV. WITH GRND. SET FLUSH BOTH RECORD FOUND BT DISTANCES CLOSE TO FACE MEASURE.
~~Old 9" Hemlock Stob, N.85°E., 16.0 ft., pushed over.~~
29" ~~14" Hemlock N.34°E. 11.8 ft., now 15.6" DBH. F.H.D.B~~
~~16" Hemlock S.53°E. 12.0, now 19.2" DBH to be felled~~
 New BT - 39" ~~22" DBH Hemlock S.37°31'E. 31.27 ft. mkd: 1/4 S16 PE~~ 32.0 ADD 3 1/2" MAG NAIL RSC TO FOUND B.T.S
 Note - One BT damaged in logging so replaced with New BT.

NOT GOOD EVID. ROTTEN AWAY

NEW REFERENCES

5" DIA. CHINQUAPIN SCRIBED "X" "BT" ON HIGH-LOW BLAZE; BEARS S63°W, 4 3/4 FT. DIST.
 4" DIA. CHINQUAPIN " " " " " " ; BEARS N41°W, 11 1/2 FT. DIST.
 BOTH NEW B.T.S HAVE A 3 1/2" MAG NAIL SET R.S.C.

MON. ON MODERATE NW SLOPE, LARGE OLD TREES SOUTH
OLD SMALLER REGROWTH TO NORTH
MON. APPROX 200 FT EAST FROM GRAVEL RD.