

TOWNSHIP 24S RANGE 3W SEC. 35 PLSS # 560140

Date: 10/7/25 By: KE  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 9/30/25

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67161-31

Corner Designation

CE 1/4 S35

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

3/4" BLM BRASS CAP  
Proj 8" IN Rough mound  
of stone

Previous Renewals

Set by BLM 1981  
Vol 45 pg 17441

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

MONUMENT DETAIL

C E 1/4  
S35  
1981

Accessories Found

Very Burnt 15" x 25' grand fir snag  
N19 1/2° E 7.6 FT Fully Healed Single BLAZE  
ADD 3 1/2" MAG NAIL Right side center

Very Burnt Down 11" yew S16 1/2° E  
26.7 FT TO Root Hole Burnt out BLAZE

Monument Set (Procedure and Description)

MONUMENT DETAIL

---



---



---



---



---



---

New Accessories

13" W. FIR DEAD BURNT BASE EAST 2.6 FT  
 3 1/2" MAG NAIL RIGHT SIDE CENTER

---



---



---



---



---



---



---



---

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS Cottage Grove To  
 Canyonville Zone Location

43°15'51.01923 N  
 123°00'53.96022 W

---



---



---



---



---



---

Comp. Decline. 14 1/4° E  
 Agency DCSO  
 Party Chief S. F. HOUSE  
 Note keeper \_\_\_\_\_  
 Witnesses J. LORSON

CS 67101-31

pg 2/3



EXPIRES: 12/31/2026

below surface of ground, with brass cap mkd.

PG. 17441  
Vol 45

T 26 S R 3 W

1/4  $\frac{S 26}{S 35}$

1972

from which bearing trees mkd. by Berry, Popken, and Carlson

A cedar, 30 ins. diam., bears N. 47 1/4° E., 86 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record, N. 53° E.)

NO 46' W, 1310.76

A cedar, 20 ins. diam., bears S. 83° E., 31 lks. dist., with scribe marks 1/4 S35 BT visible on open blaze.

The corner is located on E. edge of dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.

MINI GAS  
43.26418  
123.01500

From the 1/4 sec. cor. of secs. 35 and 36.

N. 89° 39' W., on the E. and W. center line of sec. 35.

Descend 170 ft. over SW. slope, through heavy timber and dense undergrowth.

11.00 Gravelled road, 25 lks. wide, bears N. 30° W. and S. 5° E., in curve.

17.45 Creek, 1 lk. wide, course N. 50° W.; asc. 5 ft. over NE. slope.

OGRS CANYONVILLE COTTAGE GROVE POS.

18.10 Spur, slopes N. 35° W.; desc. 20 ft. over NW. slope. 43° 15' 51.01923" N

19.30 Ravine, drains N. 35° W.; asc. 5 ft. over NE. slope. 123° 00' 53.96022" W

19.86 Point for the center E 1/16 sec. cor. of sec. 35. 26-3-560140

DECLINATION 14 1/2° E

RENEWED 9/30/25

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

3/4" B.C. C  $\frac{E 1/16}{S 35}$  C PROT. 8" IN ROUGH MOUND OF STONE

1981

from which

VERY BURNED 15" x 25 FT. SNAG - A grand fir 12 ins. diam., bears N. 19 1/2° E., ADD 3 1/2" MAG NAIL R.S.C. 11 1/2 lks. dist., mkd. CE 1/16 S35 BT.

7594 FHSB

VERY BURNED FALLEN 11" DIA. A yew 14 ins. diam., bears S. 16 1/2° E., 40 1/2 lks. dist., mkd. CE 1/16 S35 BT. BURNED OUT BLAZE

26 731 TO ROOT HOLE

NEW REF. Ascend 5 ft. over NE. slope. WITH 13" DIA. WHITE FIR DEAD BURNED BASE 3 1/2" MAG NAIL R.S.C. BEARS EAST, 2 1/2 FT. DIST. Spur, slopes N. 10° E.; desc. 400 ft. over NW. slope.

20.50

21.85

Gravelled road, 25 lks. wide, bears N. 25° E. and S. 25° W.

CS 67161-31 pg 3/3