

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 26S RANGE 2W SEC. 3 PLSS # 440100

Date: 10/22/25 By: ke
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 10-21-25

Map: _____

Narrative: _____

Corner Rpt: CS 67161-34

Corner Designation

$\frac{1}{4}$ COR $\frac{34}{3}$ T265
T275

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

BLM BRASS CAP

Condition report

Not Found

Renewed

Unrecorded

Surveyed In

Previous Renewals

GLD 1913 Vol 10 pg 4261-62

BLM RESURVEY 1957 Vol 29

pg 12204-05

BLM RESURVEY 1979 Vol 44 pg 16938

SHANER 2000 M 132-70

Shrum 1979 M 76-54

MONUMENT DETAIL

T265 RW

S 34

S 3

T275

Accessories Found

35" X 2 FT FIR STUMP N10°W 19.9 FT
(REC 15 LKS)

BURNT 27" X 2 FT FIR STUMP 19.3 FT (REC
30 LKS)

34" MADRONE N49 1/2 E 43.7 FT (REC 66 LKS)

44" X 3 FT FIR STUMP S23 1/2 W 50.3 FT
(REC 77 LKS)

ALL STUMPS HAVE 3 1/2" MAG NAILS
SET TOP CENTER

Monument Set (Procedure and Description)

MONUMENT DETAIL

Horizontal lines for Monument Set description

New Accessories

Horizontal lines for New Accessories description

Sketch of Monument, Accessories, and General Area

Location & Comments

OCRS Coordinates
Cottage Grove To
CANYONVILLE ZONE

Wagon on steep
slope Logged ADD
Burnt to west

AREA BURNED
9/2020

N 154913.928
E 273653.948

Comp. Decline. 14 1/4° E
Agency DLSD
Party Chief J. Loring
Note keeper
Witnesses

CS 67161-34

pg 2/4

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

TOWNSHIP 26 RANGE 2 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; & 34, T26-2-440100

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 10 Page(s) 4183-84)

Set Laurel post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S on N. and S. faces, from which

A Fir 20" dia., bears S.10°W., 30 lks. dist. mkd. 1/4 S BT.

A Fir 18" dia., bears N.10°W., 15 lks. dist. mkd. 1/4 S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4261-62)

The 1/4 sec. cor., located by reference to the bearing trees, as described by the surveyor general; all other traces of the cor. have disappeared. I re-establish this cor. in its original position as follows:

Set a basalt stone 20x10x8 ins., 15" in the ground, for 1/4 sec. cor. marked 1/4 on N. face, witnessed by the original bearing trees as follows:

A Fir 20" dia., bears S.10°W., 30 lks. dist. mkd. 1/4 S BT.

A Fir 18" dia., bears N.10°W., 15 lks. dist. mkd. 1/4 S BT.

BLM Resurvey by Harold D. Corbin, Cadastral Surveyor, under Special Instructions dated June 21, 1957 - (DCSO records Vol. 29 Page(s) 12204-05)

The 1/4 sec. cor., monumented with a basalt stone 20x10x8 ins., 10" above ground, firmly set, mkd. 1/4 on the N. face, from which the remains of the original bearing trees as follows:

35" x 2 FT - A Fir 42" dia., bears N.10°W., 15 lks. dist. with a healed blaze facing the cor. ¹⁹⁹

BURNED STUMP 27" x 2 FT - A Fir 38" dia., bears S.10°W., 30 lks. dist. with a healed blaze facing the cor. ^{198 FT}

At the corner point Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T26S R2W

1/4 S 34

S 3

T27S

from which

33" - A Madrone 11" dia., bears N.49 1/2° E., 66 lks. dist. mkd. 1/4 S34 BT.

44" x 3 FT - A Fir 50" dia., bears S.23 1/2° W., 77 lks. dist. mkd. 1/4 S3 BT

Fd. Cor. and used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #990, surveyed Aug/Sept. 1979 - (DCSO records Vol. 44 Page(s) 16938)

BURNED STUMP

BURNED STUMP

TOWNSHIP 26 ~~27~~ RANGE 02 POINT IDENTIFIER # 440100 ~~440700~~

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; & 34, T26-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. Ok by B. Shaner - 11/2000 - C. S. File 65/36-2F & M132-70

-OCRS - N - 154913.928 , E - 273653.948

FALLS ON STEEP SOUTH SLOPE, WEST
SIDE BURNED + LOGGED, STUMPS TOP
CENTER SPIKED + TAGGED.