

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 26S RANGE 2W SEC. 19

PLSS # 200340

Date: 11/2/25 By: ke
This survey consists of:

Map: _____

DOUGLAS COUNTY OREGON

DATE 11-05-25

Narrative: _____

Corner Rpt: CS 67101-37

Corner Designation

1/4 S19/520

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" DCSO BRASS CAP
ON 1" I.D. IRON PIPE
PROJ. 6"

Previous Renewals

GLD Resurvey 1916-1918 10/10 pg 4333
DCSO 1967 CS 54/40-16
Edwards 2008 M 155-46

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

MONUMENT DETAIL

COUNTY SURVEYORS
OFFICE
T26S 22W
1/4 S19/520

Accessories Found

37" D. Fir N 86 1/4° W 33.7 FT

Burned - dead 46" D. Fir N 54° E 31.7 FT

BURNED 14' x 2" Hemlock stump N 70° E
69.7 FT

New Accessories

14" X 2 FT TALL D. FIR STUMP 562°E
63.5 FT 3 1/2" MAG NAIL TOP CENTER

10" Buried - dead D. FIR S41W 11.0 FT
3 1/2" MAG NAIL RIGHT SIDE CENTER

Sketch of Monument, Accessories, and General Area

Location & Comments

OCES COORDINATE'S LOCATION
Cottage Grove - Canyonville
Zone

M60 IS APPROX
75 FT NORTH OF
GRAND SPUR ROAD

AREA BURIED
9/2020

43°17'35.73134 N
122°58'14.93441 W

Comp. Decline. 14 1/4°E
Agency DCSO
Party Chief S. F. AUSE
Note keeper
Witnesses J. LOISUR

CS 67/61-37 pg 2/3

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs 19 & 20

Alias _____	Description _____
Alias _____	Description <u>OCS CANYONVILLE COTTAGE GROVE POSITION</u>
Alias _____	Description _____
Alias _____	Description <u>43° 17' 35.73134"</u>
Alias _____	Description <u>122° 58' 14.93441"</u>

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4250)

Set a granite stone 6x8x12" 8" in the ground for 1/4 s cor. marked 1/4 on West face, from which
A maple, 6" dia., bears S.80°30'E., 10 lks., mkd: 1/4 S20 BT
A fir, 20" dia., bears N.86°15'W., 51 lks., mkd: 1/4 S19 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4333)

The 1/4 cor bet. secs. 19 & 20, established by Deputy Gibb in 1910, which is a granite stone, 4x8x6" above ground, firmly set, marked & witnessed as described by the surveyor general
DECLINATION 14 1/4° E

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - July 1967 - C.S. File 54/40-16

Found ^{37" 35"} Orig. 20" now 32" Fir, N.86°W., 33.7 ft., alive, SEE BELOW open & find "B" scribe.

No trace of Maple to SE 2 1/2" B.C. 1" I.D. I.P.
Set - Brass cap at cor. mkd: COUNTY SURVEYOR T26S R2W V PROT 6" OFFICE 1/4 S19|S20

Rescribed orig. 32" D. Fir N.86°W., 33.7 ft. mkd: "1/4 S19 CS BT" in bark GONE
4" 40" D. Fir N.54°E., 31.7 ft. mkd: 1/4 S20 CS BT in bark GONE
22" 12" Hemlock N.77°E., 63.7 ft. mkd: 1/4 S20 CS BT
Note - This corner lies on very steep northerly slope. No trace of corner stone.

Fd. BC & 3 BTs by D. Edwards, 4/2008 - M155-46 MONUMENT IS APPROX. 75 NORTH FROM GRAVEL SPUR RD.

NEW REFS

BURNED SAWN 14" x 2 FT TALL D. FIR STUMP 3 1/2" MAG NAIL TOP CENTER BEARS S 62° E, 63 1/2

10" BURNED DEAD D. FIR PLACE 3 1/2" MAG N.S.C. BEARS S 41° W, 110 FT

BURNED DEAD 37 1/2"
BURNED DEAD 46"
BURNED UP 14" x 2 FT.