

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 24S RANGE 2W SEC. 25 PLSS # 600200

Date: 12/2/25 By: KE  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 11/06/25

Map: \_\_\_\_\_  
Narrative: \_\_\_\_\_  
Corner Rpt: CS6716138

Corner Designation

Sec COR 26/25  
35/36

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" BLM BRASS CAP  
Proj 14" in Rough mound  
of stone

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

BLM Resurvey May 1951 -  
Aug 1963 Vol 32 pg 13290  
DCSO 1968 CS 52/42-56  
Quimby 10/2020 CS 65/106-51

MONUMENT DETAIL

+24S R2W  
52L/52S  
535/53L

Accessories Found

Singed 35" D. Fir N40°E 23.1 FT Shows  
Scar

29" Hemlock N30°E 25.1 FT

Buried Rotted 14" X 4 FT Fir Stub S79°E  
44.9 FT Exposed Scribe 53L

Singed 30" Hemlock S30°W 45.2 FT Fully  
Healed Single BLAZE

Sawn 26" X 2 FT D. Fir Stump N60°W  
41.0 FT Fully Healed Single BLAZE

Fd on Ground Steel post Reset on  
East Edge of BRASS CAP

Monument Set (Procedure and Description)

MONUMENT DETAIL

Blank lines for Monument Set (Procedure and Description)

New Accessories

Blank lines for New Accessories

Sketch of Monument, Accessories, and General Area

Location & Comments

Trimble 600 XT Position

43°26'56.513 N

122°53'37.312 W

MON ON Steep west slope 180'± EAST OF Rock Creek ACCESS ROAD

AREA Burnt

9/2020

Comp. Decline 14'14" E

Agency DLGO

Party Chief S. F. AUSE

Note keeper

Witnesses J. L. ORSHAN

CS 67161-38

pg 2/4

REGISTERED PROFESSIONAL LAND SURVEYOR

Ronald A. Quimby

OREGON JULY 14, 1978 RONALD A. QUIMBY 1654

EXPIRES: 12/31/2026

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Corner Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2891)

Set basalt stone 15x10x5", 10" in the ground for cor. to secs. 25, 26, 35, & 36 marked with 1 notch on S & 1 notch on E edges, from which

A fir, 24" dia. bears N.55°E. 35 lks. mkd: T24S R2W S25 BT

A hemlock, 12" dia., bears S.63°E., 53 lks., mkd: T24S R2W S36 BT.

A fir, 36" dia. bears S.81°W. 22 lks. mkd: T24S R2W S35 BT

A fir, 18" dia. bears N.75°W. 53 lks. mkd: T24S R2W S26 BT

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13290)

The cor. of secs. 25, 26, 35, & 36, determined at record dist. from the orig. BTs:

A fir, 28" dia., bears N.60°E., 35 lks., blaze healed, edge of face under 57 yrs. overgrowth. (Rec. bearing N.55°E,)

A hemlock, 20" dia., bears S.57°E., 53 lks., partial scribe marks visible. (Rec. bearing S.63°E.)

A down fir, 30" dia., bears S.66¼°W., 22 lks., blaze healed. (Rec. bearing S.81°W.)

A down fir, 20" dia. bears N.75°W., 53 lks., blaze healed.

At the corner point

Set an iron post, 36" long, 2" dia., 24" in the ground to solid rock & in a mound of stone, 4 ft. base to top with brass cap marked:

T 24 S R 2 W

S 26 | S 25

S 35 | S 36

1951

from which

A hemlock, 12" dia., bears N.30½°E., 38 lks., mkd: T24S R2W S25 BT.

A fir, 20" dia., bears S.79°E., 68 lks., mkd: T24S R2W S36 BT.

A hemlock, 14" dia., bears S.67½°W., 71 lks., mkd: T24S R2W S35 BT.

A hemlock, 14" dia., bears N.67°W., 97 lks., mkd: T24S R2W S26 BT.

continued next page

MIN GIS  
43.44901  
122.89377

CS 67/61-38 pg 3/4

PRIMARY CORNER DESCRIPTION Corner Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description <u>TRIMBLE GEO XT POSITION</u>
Alias _____	Description _____
Alias _____	Description <u>43°26'56.513"N</u>

DECLINATION 14 1/4° E 122°53'37.312"W FOUND OK 11/06/25

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1968 - C.S. File 52/42-56

Found - 1951 cadastral/brass cap, firmly set & properly mkd. 2 1/2" BC / 20 D.I.P. PROT 14"  
 Orig. 28" D. Fir alive, N. 60° W., 23.1 ft. shows scar IN ROUGH STONE MOUND  
 NO EVIDENCE Orig. 20" Hemlock, alive, S. 57° E., 35.0 ft., shows scar.

BASE SINGED 35"

29" 12" Hemlock alive, N. 30 1/2° E., 25.1 ft., alive, scribe visible on unhealed blaze.

BURNED ROTTED  
BROKEN FIRS  
BASE SINGED 30"  
SALUN

14" x 4" Fir S. 79° E., 44.9 ft., alive blaze pitched over. EXPOSED "S36"

New BTs - 7" Hemlock alive, S. 30° W., 45.2 ft. mkd: T24S R2W S35 CS BT FH SB  
 STUMP 26" x 2" 8" D. Fir N. 60° W., 41.0 ft., mkd: T24S R2W S26 CS BT FH SB

Note - This corner lies on steep west slope 150 ft. East of Rock Creek access road. 180

FOUND LOOSE ON GROUND GALV. STEEL LATH SET ON EAST EDGE OF BC MONUMENT.  
Fd Ok by R Quimby 10/2020 - C.S. File 65/106-51

